

WITCO CORP -- VV-P-236A -- 9150-00-250-0933

===== Product Identification =====

Product ID:VV-P-236A  
MSDS Date:06/09/1990  
FSC:9150  
NIIN:00-250-0933  
MSDS Number: BLJGR  
=== Responsible Party ===  
Company Name:WITCO CORP  
Box:84075  
City:DALLAS  
State:TX  
ZIP:75284-0075  
Country:US  
Info Phone Num:504-738-1623  
Emergency Phone Num:504-738-1623  
CAGE:WITCO

=== Contractor Identification ===

Company Name:UNI-KEM  
INTERNATIONAL  
Address:1001 HARIMAW COURT EAST  
Box:City:METAIRIE  
State:LA  
ZIP:70001  
Country:US  
Phone:504-835-7600/FAX:504-835-7608  
CAGE:4S446  
Company Name:WITCO CORP  
Address:2701 LAKE STREET  
Box:5446  
City:DALLAS  
State:TX  
ZIP:75284-0075  
Country:US  
Phone:504-738-1623  
CAGE:WITCO

===== Composition/Information on Ingredients =====

Ingred Name:GREASE, PETROLEUM  
CAS:8009-03-8  
Other REC Limits: 5 MG/M3 OIL MIST

===== Hazards Identification =====

R

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Health Hazards Acute and Chronic:PER MANUFACTURER THE PRODUCT IS  
NON-HAZARDOUS. EYE CONTACT MAY CAUSE REDNESS AND IRRITATION. SKIN  
CONTACT:DEFATING/SLIGHT IRRITATION.  
Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.  
Effects of Overexposure:IRRITATION OF AND REDNESS OF EYE., SKIN  
IRRITATION.  
Medical Cond Aggravated by Exposure:NONE KNOWN TO MFR.

===== First Aid Measures =====

First Aid:  
EYES:FLUSH IMMEDIATELY WITH COLD WATER, CALL A PHYSICIAN.  
SKIN CONTACT:FOR MOLTEN PETROLATUM, FLUSH IMMEDIATELY WITH COLD  
WATER, CALL A PHYSICIAN. FOR SOLIDIFIED PETROLATUM REMOVE EXCESS  
WITH PAPER TOWELS, WASH WITH SOAP AND WATER. INHALATION:NDA.  
INGESTION:CALL A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:>400F,>204C  
Lower Limits:NDA  
Upper Limits:NDA  
Extinguishing Media:DRY CHEMICAL, CO2, FOAM, WATER  
OR SAND/EARTH.  
Fire Fighting Procedures:WATER SPRAY IS AN UNSUITABLE EXTINGUISHING  
AGENT. FIRE FIGHTERS SHOULD USE SELF-CONTAINED BREATHING APPARATUS  
TO PROTECT AGAINST SMOKE INHALATION.  
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:SHUT OFF LEAK AND DIKE UP LARGE SPILLS, AFTER  
COOLING AND SOLIDIFICATION, SCRAPE AND/OR SHOVEL UP MATERIAL.  
FINALLY, CLEAN AREA WITH AN OIL ABSORBENT MATERIAL.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM FLAME, HEAT (200  
DEGREES F MAX) AND STRONG OXIDIZING AGENTS. AVOID SKIN AND EYE  
CONTACT.  
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED  
Protective Gloves:WEAR IMPERVIOUS GLOVES.  
Eye Protection:WEAR A FACE SHIELD OVER SAFETY GOGGLES  
Other:None

her Protective Equipment:WEAR OVERALLS

Work Hygienic Practices:READ ALL LABELS CAREFULLY BEFORE USING.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:NDA

Melt/Freeze Pt:M.P/F.P Text:110F,43C

Vapor Pres:NDA

Vapor Density:NDA

Spec Gravity:NDA

Evaporation Rate & Reference:NDA

Solubility in Water:NIL

Appearance and Odor:SEMI-SOLID, OIL LIKE, OPAQUE COLOR: YELLOW OR BROWN.

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STONG OXIDIZINING AGENTS

Stability Condition to Avoid:OPEN FLAMES

Hazardous Decomposition Products:XIDES OF CARBON, SMOKE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated

for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.