View NSN Online: https://aerobasegroup.com/nsn/8030-00-850-5717

## PRODUCTS RESEARCH & CHEMICAL CORPORATION -- PR-1440, PART A -- 8030-00-850-5717

Product ID:PR-1440, PART A

MSDS Date:12/06/1989

FSC:8030

NIIN:00-850-5717

Kit Part:Y

MSDS Number: BLLWH === Responsible Party ===

Company Name: PRODUCTS RESEARCH & CHEMICAL CORPORATION

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Info Phone Num:8

18-240-2060

Emergency Phone Num:800-424-9300 CHEM/800-228-5635 MED

Preparer's Name: AS

CAGE:DO563

=== Contractor Identification ===

Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Phone:818-240-2060

CAGE:83574

Company Name: PRODUCTS RESEARCH & CHEMICAL

Address: NOW DBA COURTAULDS AEROSPACE

Box:1800

City:GLENDALE

State:CA ZIP:91209

Phone:818-240-2060

CAGE:DO563

====== Composition/Informati

| on on Ingredients ========   |
|--|
| Ingred Name:MANGANESE DIOXIDE (EXPOS LIM BASED ON AIRBORNE PARTICLES. IN THIS PRODUCT MAT'L IS FULLY ENCAPSULATED-NO AIRBORNE PART) CAS:1313-13-9 RTECS #:OP0350000 Fraction by Wt: 60% Other REC Limits:NONE SPECIFIED OSHA PEL:5 MG/M3 STEL CEILING ACGIH TLV:5 MG/M3  |
| Ingred Name:1,3 DIPHENYL GUANIDINE (DPG) CAS:102-06-7 RTECS #:MF0875000 Fraction by Wt: < 5% Other REC Limits:NONE SPECIFIED   |
| ======================================   |
| L D50 LC50 Mixture:E CAUS912 Health Hazards Acute and Chronic:0-424-9300 CHEM/800-228-5635 MED 818-240- 2060 AS PRODUCTS RESEARCH & CHEMICAL CORP Explanation of Carcinogenicity:MIL-S-8802 Effects of Overexposure:CL B-4, TY II N/K N/K N/K NA 1.95 NA N/K NA N/K UNK NEGLIGIBLE N/K N/K N/K N/K NONE N/K NA NA CO2, DRY CHEMI Medical Cond Aggravated by Exposure:CAL, FOAM, WATER. USE AIR SUPPLIED RESPIRATOR. USE WATER TO COOL HEAT EXPOSED CONTAINERS. |
| ======================================   |
| First Aid:EXCESSIVE HEAT MAY CAUSE DECOMPOSITION OF MANGANESE DIOXIDE, RESULTING IN OXIDIZATION AND POSSIBLE IGNITION OF HYDROCARBON VEHICLE. YESN/K EASILY OXIDIZABLE MATERIALS.  |
| ======================================   |
| Flash Point:NONE Lower Limits:NA Upper Limits:NA  Fixting ruling Madia: CO2 DBY CHEMICAL FOAM WATER  |

Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER.
Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR. USE WATER TO COOL HEAT EXPOSED CONTAINERS.

Unusual

Fire/Explosion Hazard:EXCESSIVE HEAT MAY CAUSE DECOMPOSITION OF MANGANESE DIOXIDE, RESULTING IN OXIDIZATION AND POSSIBLE IGNITION OF HYDROCARBON VEHICLE.

| ====== Exposure Controls/Personal Protection ======== |
|---|
| Supplemental Safety and Health<br>KEY1:N1.            |
| ======================================                |
|   |

HCC:N1

Boiling Pt:B.P. Text:NA

Vapor Pres:NA Vapor Density:NA Spec Gravity:1.95

Evaporation Rate & Dr. Reference: UNK

Solubility in Water: NEGLIGIBLE

======

====== Stability and Reactivity Data =========

Stability Indicator/Materials to Avoid:YES EASILY OXIDIZABLE MATERIALS.

Hazardous Decomposition Products:PR-1440, PART A GM
06DEC8911JUN91GSASEALING COMPOUND, RUBBER POLYSULFIDE PAR
Conditions to Avoid Polymerization:OF 2 PRODUCTS RESEARCH & CHEMICAL
CORPORATION 5430 SAN FERNANDO ROAD 1800 GLENDAL

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the
Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.