

BAKER SEALANTS & COATINGS CO -- CID-A-A-2210, WOOD FILLER, X-730A -- 8010-00-283-0512

===== Product Identification =====

Product ID:CID-A-A-2210, WOOD FILLER, X-730A

MSDS Date:03/23/1990

FSC:8010

NIIN:00-283-0512

MSDS Number: BLNBY

=== Responsible Party ===

Company Name:BAKER SEALANTS & COATINGS CO

Address:234 SUYDAM AVE

Box:B

City:JERSEY CITY

State:NJ

ZIP:07304

Country:US

Info Phone Num:201-333-

6986 OR 201-333-6955/FAX #

Emergency Phone Num:201-333-6986

Preparer's Name:CHARLES FRIEDMAN

CAGE:FO833

=== Contractor Identification ===

Company Name:BAKER SEALANTS & COATINGS CO., INC.

Address:234 SUYDAM AVENUE

Box:B

City:JERSEY CITY

State:NJ

ZIP:07304-3306

Phone:(201) 333-6986

CAGE:FO833

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Phone:201-333-6986

CAGE:34094

Company Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:

8

City: BAYONNE
State: NJ
ZIP: 07002-3417
Country: US
Phone: 201-437-6501
CAGE: 33150

=====
Composition/Information on Ingredients
=====

Ingred Name: ISOPROPYL ALCOHOL (SARA III)
CAS: 67-63-0
RTECS #: NT8050000
OSHA PEL: 400 PPM/500 STEL
ACGIH TLV: 400 PPM/500 STEL; 9192

Ingred Name: STODDARD SOLVENT
CAS: 8052-41-3
RTECS #: WJ8925000
Other REC Limits: LIMIT-500
OSHA PEL: 500 PPM
ACGIH TLV: 100 PPM; 9293

Ingred Name: TALC (MAGNESIUM SILICATE)
CAS: 14807-96-6
RTECS #: VV7720000

Ingred Name: STODDARD SOLVENT
CAS: 8052-41-3
RTECS #: WJ8925000
OSHA PEL: 500 PPM
ACGIH TLV: 100 PPM; 9293

Ingred Name: XYLENES (O-, M-, P- ISOMERS) (SARA III)
CAS: 1330-20-7
RTECS #: ZE2100000
OSHA PEL: 100 PPM/150 STEL
ACGIH TLV: 100 PPM/150 STEL; 9192
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

=====
Hazards Identification
=====

Routes of Entry: Inhalation: NO Skin: YES Ingestion: NO
Health Hazards Acute and Chronic: EYE IRRITATION. SKIN IRRITATION AND
DERMATITIS.
Effects of Overexposure

:EYE AND SKIN IRRITATION. DERMATITIS.

=====
First Aid Measures
=====

First Aid:FLUSH EYES WITH WATER. WASH SKIN WITH SOAP AND WATER.

=====
Fire Fighting Measures
=====

Flash Point:110F,43C

Lower Limits:.8

Upper Limits:5

Extinguishing Media:EXTINGUISH WITH CO2, FOAM OR DRY CHEMICAL.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, SCOOP INTO
CONTAINERS.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP FROM SOURCE OF IGNITION.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:WEAR SELF-CONTAINED BREATHING APPARATUS.

Ventilation:LOCAL OR MECHANICAL.

Protective Gloves:RUBBER GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:IMPERVIOUS CLOTHING AND BOOTS.

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F4

Spec Gravity:1.59

Appearance and Odor:OFF WHITE VISCOUS MATERIAL/ODOR-ALIPHATIC

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE OF "AS PER FEDERAL, STATE AND LOCAL
REGULATIONS".

Disclaimer (provided with this information by the compiling agencies):

This info

Information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.