

DAVLIN PAINT CO -- B509TB ALKYD SG ODORLESS GREEN 24672 -- 8010-00-901-8048

===== Product Identification =====

Product ID:B509TB ALKYD SG ODORLESS GREEN 24672

MSDS Date:02/25/1991

FSC:8010

NIIN:00-901-8048

MSDS Number: BLVBG

=== Responsible Party ===

Company Name:DAVLIN PAINT CO

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Info Phone Num:510-848-2863

Emergency Phone Num:800-424-9300 (CHEMT
REC)

Preparer's Name:PATRICIA SHAW

CAGE:3Z268

=== Contractor Identification ===

Company Name:DAVLIN PAINT CO INC

Address:700 ALLSTON WAY

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Phone:510-848-2863

CAGE:3Z268

===== Composition/Information on Ingredients =====

Ingred Name:HYDROCARBON MIXTURE (VAPOR PRESSURE 2.0 MM HG @ 68F)

CAS:64741-41-9

Fraction by Wt: 20%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

Ingred Name:SILICA, QUARTZ

CAS:14808-60-7

RTECS #:VV7330000
Fraction by Wt: 0.26%
Other REC Limits:NONE SPECIFIED
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:PETROLEUM HYDROCARBON (VAPOR PRESSURE 50.0 HG MM @ 0 F)
CAS:8008-20-6
RTECS #:OA5500000
Fraction by Wt: 5%
Other REC Limits:100 PPM
OSHA PEL:500 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:INHALATION: RESPIRATORY IRRIT, CENTRAL NERVOUS SYS DEPRESSION. SKIN/EYE: PROLONG/REPEAT EXPOSURE--MODERATE IRRIT, DEFATTING & DERMATITIS. INGEST: DIGESTIVE TRACT IRRIT, LUNG INFLAMMATION. CAUSES DAMAGES TO CENTRAL NERVOUS SYSTEM, RESPIRATORY SYSTEM, LUNGS, EYES, SKIN, GASTROINTESTINAL TRACT, LIVER, SPLEEN AND KIDNEYS.
Explanation of Carcinogenicity:CRYSTALLINE SILICA IS LISTED (IARC) CARCINOGEN. ACGIH ASSIGNED TLV'S TO MATERIAL. SEE INGREDIENTS FOR TLV.
Effects of Overexposure:INHALATION: NASAL/RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA AND HEADACHE. EYE: IRRITATION, TEARING, REDNESS, & BLURRED VISION. SKIN: MODERATE IRRITATION. INGESTION: ASPIRATION HAZARD; THIS MATERIAL CAN ENTER THE LUNGS DURING SWALLOWING OR VOMITING AND CAUSE LUNG INFLAMMATION.
Medical Condition Aggravated by Exposure:RESPIRATORY TRACT IRRITATION, DERMATITIS, NAUSEA.

===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER--15 MIN, OCCASIONALLY LIFTING EYELIDS. OBTAIN MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP & WATER. IF IRRITATION PERSISTS, SEE DOCTOR. INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION OR ADMINISTER OXYGEN. CONSULT A DOCTOR. INGESTION: GIVE WATER/MILK TO DRINK & PHONE FOR MEDICAL ADVICE. DON'T INDUCE VOMIT UNLESS MEDICAL PERSONNEL ADVISES. MEDICAL ADVICE UNAVAILABLE, TAKE TO EMERGENCY HOSPITAL.

===== Fire Fighting Measures =====

Flash Point M

ethod:SCC

Flash Point:104F,40C

Lower Limits:0.7%

Upper Limits:6.1%

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:USE EXTINGUISHERS (NFPA FLAMMABLE LIQUID FIRE). WATER MAY BE INEFFECTIVE, USE AS FOG FOR COOLING. WEAR FULL PROTECT CLOTH/BREATH APP IF EXPOS TO COMBUST PROD.

Unusual Fire/Explosion Hazard:VAPORS FORM EXPLOSIVE MIX WHICH CAN BE IGNITED FROM MANY SOURCES. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. ISOLATE FORM IGNITION SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE NON-ESSENTIAL PERSONEL. REMOVE ALL IGNITION SOURCES. VENTILATE THE AREA. PROVIDE APPROPRIATE PROTECTIVE EQUIPMENT. DIKE AROUND THE SPILL AREA. COVER SPILL WITH INERT ABSORBANT AND TRANSFER USING NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 80 F IN A CLOSED CONTAINER

R. STORE IN ORIGINAL CONTAINER. AVOID FLAME & HIGH TEMPERATURES. DON'T STORE NEAR OXIDIZING AGENTS OR ACIDS.

Other Precautions:VAPOR HEAVIER THAN AIR & MAY TRAVEL DISTANCE TO IGNITION SOURCES & FLASHBACK. DON'T EAT. NO PROLONG/REPEAT INHALATION OF HEATED VAPORS/ SPRAY MISTS. KEEP FROM HEAT. GROUND ALL CONNECTIONS, CONTAINERS, ETC (DURING POURING/ TRANSFERRING). USE NON-SPARKING TOOLS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED EQUIPMENT WHEN AIRBORNE

EXPOSURE LIMITS ARE EXCEEDED. CONSULT RESPIRATOR MANUFACTURER TO DETERMINE APPROPRIATE EQUIPMENT FOR GIVEN APPLICATION. HIGH AIRBORNE CONCENTRATIONS MAY REQUIRE THE USE OF A SUPPLIED-AIR RESPIRATOR/SCBA.

Ventilation:PROVIDE SUFFICIENT VENTILATION TO CONTROL EXPOSURE LEVELS BELOW AIRBORNE TLVS. VENT EQUIPMENT MUST BE EXPLOSION PROOF.

Protective Gloves:CONSULT GLOVE MANUFACTURER FOR APPROPRIATE TYPE

Eye Protection:CHEMICAL SAFETY GLASSES/GOGGLES(SPLASH SHIELD)

Other Protective Equipment

equipment:WEAR IMPERMEABLE APRONS AND PROTECTIVE CLOTHING WHENEVER POSSIBLE TO PREVENT REPEATED OR EXTENDED EXPOSURE OF SKIN.

Work Hygienic Practices:AFTER USING, WASH BEFORE EATING, TOILETING OR SMOKING.

Supplemental Safety and Health

THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER OR REPRODUCTIVE HARM. THE USE OF HEAD CAPS WHENEVER POSSIBLE IS STRONGLY RECOMMENDED.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:315 TO 335F

Vapor Density:> AIR

Spec Gravity:1.4 (WATER=1)

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NOT SOLUBLE

Appearance and Odor:PIGMENTED LIQUID. SOLVENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:DO NOT EXPOSE TO HEAT OR IGNITION SOURCES.

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON

DIOXIDE AND/OR MONOXIDE, LOW MOLECULAR WEIGHT HYDROCARBONS AND ORGANIC ACIDS.

===== Disposal Considerations =====

Waste Disposal Methods:KEEP OUT OF DRAINS, SEWERS, AND WATERWAYS. DISPOSE OF PRODUCT IN ACCORDANCE WITH FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner

whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.