View NSN Online: https://aerobasegroup.gr/nsn/6750-01-313-1954

Product ID:P-22 BLEACH BL22.15 PART B MSDS Date:11/03/1989 FSC:6750 NIIN:01-313-1954 Kit Part:Y MSDS Number: BMDXT === Responsible Party === Company Name: ILFORD PHOTO CORP Address:70 W CENTURY RD City:PARAMUS State:NJ ZIP:07653 Country:US Info Phone Num:201-265-6000 Emergency Phone Num:800-842-96 60 CAGE:64145 === Contractor Identification === Company Name: ILFORD PHOTO CORP Address:W 70 CENTURY RD Box:City:PARAMUS State:NJ ZIP:07653 Country:US Phone:201-265-6000 CAGE:64145 Ingred Name: ACETIC ACID (SARA III) CAS:64-19-7 RTECS #:AF1225000 Fraction by Wt: 16-20% Other REC Limits:NONE SPECIFIED **OSHA PEL:10 PPM** ACGIH TLV:10 PPM/15 STEL; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: POTASSIUM IODIDE CAS:768111-0 RTECS #:TT2975000 Fraction by Wt: 12-15% Other REC Limits:NONE SPECIFIED

Ingred Name:SODIUM MERCAPTO PROPANE SULFONATE CAS:17636-10-1 RTECS #:TZ6655600 Fraction by Wt: 1-3% Other REC Limits:NONE SPECIFIED

Ingred Name:QUIONOXALINE ADDUCT CAS:17635-21-1 Fraction by Wt: 1-3% Other REC Limits:NONE SPECIFIED

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 60-65% Other REC Limits:NONE SPECIFIED

LD50 LC50 M

ixture:LD50 (ORAL RAT)=3310 MG/KG.(ACETIC ACID)
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: CAUSES IRRITATION AND BURNS TO
EYES AND SKIN. UPPER RESPIRATORY IRRITATION. IF INGESTED, CAUSES
SEVERE INJURY, BURNS TO THE MOUTH, THROAT, ESOPHAGUS AND STOMACH.
CHRONIC: MIST OR VAPOR CAUSES C HRONIC INFLAMATION TO UPPER
RESPIRATORYTRACT IRRITATION AND CHRONIC BRONCHITIS. SKIN
DERMA
TITIS.
Effects of Overexposure:COUGHING, SNEEZING, IRRITATION TO UPPER

RESPIRATORY TRACT, SORE THROAT, VOMITING, DIARRHEA. Medical Cond Aggravated by Exposure:INDIVIDUALS WITH SKIN DISORDER OR PREVIOUS HISTORY OF UPPER RESPIRATORY PROBLEMS MAY BE AT HIGHER RISK OF INFECTIONS.MAY CAUSE SKIN DERMATITIS AND CHRONIC BRONCHITIS.

First Aid:INHALATION:REMOVE TO FRESH AIR GIVE OXYGEN, PERFORM CPR IF NOT BREATHING

. EYES: FLUSH IMMEDIATELY WITH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION IMMEDIATELY. SKIN: FLUSH SKIN WITH WATER TH EN WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. GET MEDICAL ATTENTION. INGESTION: GIVE 3 OR 4 GLASSES OF EITHER MILK OR WATER, DONT NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION AT ONCE.

Extinguishing Media:NONE-FLAMABLE. USE EXTINGUSHING MEDIA PROPER TO PRIMARY SOURC

E OF FIRE

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:MAY PRODUCE TOXIC FUMES AND HAZARDOUS DECOMPOSITION PRODUCTS.

Spill Release Procedures:NEUTRALIZE WITH SODIUM CARBONATE OR BICARBONATE. SWEEP AND CONTAIN IN APPROPRIATE CONTAINER, RINSE NEUTRALIZED SOLUTIO

N TO SEWER IF PERMITTED BY STATE, FEDERAL AND LOCAL AUTHORITIES.

Neutralizing Agent:SODIUM CARBONATE OR BICARBONATE.

Handling and Storage Precautions:STORE IN A DRY COOL PLACE AWAY FROM OXIDIZING MATERIALS AND STRONG ALKALIS. USE NIOSH APPROVED ACID ORGANIC VAPOR RESPIRATOR IF NEEDED.

Other Precautions: HANDLE WITH CARE. AVOID PHYSICAL DAMAGE TO CONTAINER.

Respiratory Protection: USE ACID GAS RESPIRATOR WITH ORGANIC CARTRIDGE IF ROOM IS NOT WELL VENTILATED.
Ventilation: LOCAL EXHAUST TO KEEP BELOW TLV. ROOM SHOULD HAVE MECHANICAL VENTILATION OF 10-12 ROOM VOLUME CHANGES PER HOUR.
Protective Gloves: BUTYL RUBBER
Eye Protection: SAFETY GOGGLES.
Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER.
Work Hygienic Practices: WASH HANDS THOROUGHLY BEFORE EATING, DRINKING OR SMOKING.
Supplemental Safety and Health KEY1:C3. THIS IS A PART B OF A KIT. THIS PRODUCT CONTAINS A HAZARDOUS CHEMICAL ACCORDING TO FEDERAL HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200.

HCC:C1 Boiling Pt:B.P. Text:>212F,>100C Spec Gravity:1.134 pH:2-3 Evaporation Rate & amp; Reference:1 (WATER = 1) Solubility in Water:COMPLETELY SOLUBILE Appearance and Odor:COLORLESS TO LIGHT LIQUID, SLIGHT ODOR. Percent Volatiles by Volume:83%

========= Stability and Reactivity D

Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:INTENSE HEAT OR FIRE WILL PRODUCE CARBON MONOXIDE AND CARBON DIOXIDE.

Waste Disposal Methods:SOLUTION IS BIODEGRADABLE AND CAN BE DISPOSED OF BY INCINERATION. TREAT AND DISCHARGE OF ACCORDING TO LOCAL, STATE AND FEDERAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies)

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.