View NSN Online: https://aerobasegroup.gr/nsn/8030-01-041-1596

BAKER SEALANTS AND COATINGS CO -- CORROSION PREVENTIVE COMPOUND 8030-01-041-1596

Product ID:CORROSION PREVENTIVE COMPOUND MSDS Date:05/09/1990 FSC:8030 NIIN:01-041-1596 MSDS Number: BMQLM === Responsible Party === Company Name: BAKER SEALANTS AND COATINGS CO Address:234 SUYDAM AVE Box:B City: JERSEY CITY State:NJ ZIP:07304-3306 Country:US Info Phone Num:201-333-6986 / FAX 201-333-6955 Emergency Phone Num:201-333-6986 Preparer's Name: CHARLES FRIEDMAN CAGE:34094 === Contractor Identification === Company Name: BAKER SEALANTS AND COATINGS CO Address:234 SUYDAM AVE Box:City:JERSEY CITY State:NJ ZIP:07304-3306 Country:US Phone:201-333-6986 CAGE:34094

Ingred Name:AROMATIC CAS:75-69-4 RTECS #:PB6125000 Other REC Limits:100 PPM OSHA PEL:1000 PPM ACGIH TLV:C, 1000 PPM; 9293 EPA Rpt Qty:5000 LB S DOT Rpt Qty:5000 LBS Ozone Depleting Chemical:1

Ingred Name:TRICHLOROTRIFLUROETHANE CAS:76-13-1 RTECS #:KJ4000000 Fraction by Wt: 19% Other REC Limits:1000 PPM Ozone Depleting Chemical:1

Ingred Name:BARIUM DULFONATE CAS:21109-95-5 Fraction by Wt: 3% Other REC Limits:NONE SPECIFIED

Ingred Name:POLYMETHYLSILOXINE Fraction by Wt: 7% Other REC Limits:NONE SPECIFIED

Ingred Name:SILICONE ALKYD Fraction by Wt: 20% Other REC Limits:NONE SPECIFIED

Ingred Name:PROPELLENT FREON 12 CAS:75-71-8 RTECS #:PA8200000 Fraction by Wt: 32% Other REC Limits:1000 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ozone Depleting Chemical:1

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES/SKIN: CAN CAUSE IRRITATION. INHALE: CAN CAUSE EXCESSIVE HEADACHE, DIZZINESS, NAUSEA AND UPPER RESPIRATORY INFLAMATION.

======= Fi

First Aid:EYES: FLUSH WITH WATER. SKIN: WASH WITH SOAP AND WATER AND APPLY CREAM. INHALE: REMOVE TO FRESH AIR, APPLY ARTIFICIAL RESPIRATION IF NECESSARY. INGEST: CALL A PHYSICIAN.

Flash Point Method:TCC Flash Point:NR Lower Limits:0.5 Upper Limits:6 Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS Unusual Fire/Explosion Hazard:CONTAINER UNDER PRESSURE, KEEP AW AY FROM

SPARKS, FIRE AND OPEN FLAME.

Spill Release Procedures:LARGE SPILLS: FLUSH WITH WATER INTO RETAINING AREA. AVOID SPARKS, FIRE OR HOT METAL SURFACES. SMALL SPILLS: ABSORB ONTO AN APPROPRIATE ABSORBENT.

Handling and Storage Precautions: KEEP COOL AND AWAY FROM SOURCES OF IGNITION. USE WITH ADEQUATE VENTILATION. AVOID PROLONGED OR REPE

ATED PERSONAL CONTACT.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:WHEN CONCENTRATION IS ABOVE TIME WEIGHTED TLV USE CARTRIDGE RESPIRATOR OR GAS MASK. Ventilation:LOCAL EXHAUST: SUFFICIENT TO KEEP TLV DOWN Protective Gloves:IMPERMEABLE Eye Protection:CHEMICAL GOGGLES Supplemental Safety and Health

HCC:V2 Boiling Pt:B.P. Text:360 TO 410F Vapor Pres:0.5 DEG.F Vapor Density:4. 6 Spec Gravity:1.044 Evaporation Rate & amp; Reference:0.1 Solubility in Water:NEGLIGIBLE Appearance and Odor:LIGHT BLUE COLOR

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:AVOID HEAT, SPARKS, OPEN FLAME OR FIRE Hazardous Decomposition Products:THEMAL DECOMPOSITION MAY YIELD MONOXIDE AND CARBON DIOXIDE.

## Wa

ste Disposal Methods: INCINERATE UNDER SAFE CONDITIONS OR DISPOSE OF IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should s eek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.