

THE UNITED OIL CO INC -- DURALENE TUF-TEX "C" 80W90 -- 9150-01-035-5394

=====
Product Identification
=====

Product ID:DURALENE TUF-TEX "C" 80W90

MSDS Date:12/08/1987

FSC:9150

NIIN:01-035-5394

MSDS Number: BMTQP

=== Responsible Party ===

Company Name:THE UNITED OIL CO INC

Address:4405 E BALTIMORE ST

City:BALTIMORE

State:MD

ZIP:21224-1701

Country:US

Info Phone Num:301-342-1200

Emergency Phone Num:3

01-342-1200

CAGE:MO656

=== Contractor Identification ===

Company Name:THE UNITED OIL CO INC

Address:4405 E BALTIMORE ST

Box:City:BALTIMORE

State:MD

ZIP:21224-1701

Country:US

Phone:301-342-1200

CAGE:MO656

Company Name:UNITED OIL CO INC

Address:4405 E BALTIMORE STREET

Box:City:BALTIMORE

State:MD

ZIP:21224-1701

Country:US

Phone:301-342-1200

CAGE:7X748

=====
Composition/Information on Ingredients
=====

Ingred Name:ADDITIVES

Fraction by Wt: 6%

Other REC Limits:NONE SPECIFIED

Ingr

ed Name:REFINED MINERAL OIL
Fraction by Wt: 94%
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION-NONE EXPECTED TO 25 MG. OIL
MIST PER CUBIC METER OF AIR. PRACTICALLY NON-TOXIC BY SKIN
ABSORPTION.
Effects of Overexposure:MILD EYE IRRITATION.
Medical Cond Aggravated by Exposure:NONE SPECI
FIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALATION-NONE NORMALLY REQUIRED. SKIN-WASH WITH SOAP AND
WATER. EYE-IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST
15 MIN, IF REDNESS OR IRRITATION PERSISTS, CONTACT PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:550F,288C
Extinguishing Media:WATER FOG, CHEMICAL FOAM, DRY CHEMICAL, CARBON
DIOXIDE.
Fire
Fighting Procedures:WEAR SELF-CONTAINED BREATHING GEAR WHEN FIRE
FIGHTING IN CONFINED SPACES.
Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN SPILL. CLEAN UP USING AN OIL
ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM FIRE, SPARKS, AND
FLAME. STORE PER NFPA CLASS IIIB.
Other Precautions:

NONE

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:CONCENTRATION IN AIR DETERMINES PROTECTION REQUIREMENTS.

Ventilation:VENTILATION AS NEEDED TO MAINTAIN WORKPLACE ENVIRONMENTAL LIMITS.

Protective Gloves:RECOMMENDED

Eye Protection:RECOMMENDED

Other Protective Equipment:IF CONTACT IS UNAVOIDABLE, WEAR OIL IMPERVIOUS CLOTHES.

Work Hygienic Practices:WASH AFTER USE.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:WIDE RANGE

Vapor Pres:< 0.0001

Vapor Density:14+

Spec Gravity:0.89

Evaporation Rate & Reference:1000 X SLOWER (ETHER)

Solubility in Water:INSOLUBLE

Appearance and Odor:DARK COLORED LIQUID, STRONG ODOR.

Percent Volatiles by Volume:NIL

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:FIRE, SPARKS AND FLAMES.

Hazardous Decom

position Products:HYDROGEN SULFIDE, NITROGEN, AND CHLOROCARBONS.

=====
===== Disposal Considerations =====

Waste Disposal Methods:LOCAL, STATE AND FEDERAL REGULATIONS COVER DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

d

isclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.