Product ID:1B15H MSDS Date:11/22/1989

FSC:4730

NIIN:00-012-1049

MSDS Number: BMWNS === Responsible Party ===

Company Name: HUMISEAL DIVISION CHASE CORP Address: 26-60 BROOKLYN QUEENS EXPRESSWAY

City:WOODSIDE

State:NY ZIP:11377 Country:US

Info Phone Num:718-932-0800

Emergency Phone Num:718-932-0800

CAGE:HUMIS

=== Contractor Identification ===

Company Name: HUMISEAL DIVISION CHASE CORP Address: 26-60 BROOKLYN QUEENS EXPRESSWAY

Box:445

City:WOODSIDE

State:NY ZIP:11377 Country:US

Phone:718-932-0800

CAGE:HUMIS

======= Composition/Information on Ingredients ========

Ingred Name: TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 30-39%

Other REC Limits:NONE SPECIFIED OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: ACETONE

(SARA III) CAS:67-64-1

RTECS #:AL3150000 Fraction by Wt: 18-23%

Other REC Limits: NONE SPECIFIED

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: METHYL CHLOROFORM (1,1,1-TRICHLOROEHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000 Fraction by Wt: 8-12%

Other REC Limits:NONE SPECIFIED OSHA PEL:350 PPM/450 STEL ACGIH TLV:350 PPM/450STEL;9192

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ozone Depleting Chemical:1

Ingred Name:PROPANE

CAS:74-98-6

RTE

CS #:TX2275000

Fraction by Wt: 15-20%

Other REC Limits: NONE SPECIFIED

OSHA PEL:1000 PPM

ACGIH TLV:ASPHYXIANT; 9192

Ingred Name:BUTANE

CAS:106-97-8

RTECS #:EJ4200000 Fraction by Wt: 15-20%

Other REC Limits: NONE SPECIFIED

OSHA PEL:800 PPM

ACGIH TLV:800 PPM; 9192

============= Hazards Identification ========================

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NONE GIVEN

Effects of Ov

Medical Cond Aggravated by Exposure:NONE GIVEN
iviedical Cond Aggravated by Exposure. NONE GIVEN
======================================
First Aid:CONSULT A PHYSICIAN IMMEDIATELY, WASH SKIN WITH SOAP AND WATER, FLUSH EYES WITH WATER, INGESTION; GIVE TWO GLASSES OF WATER IF CONSCIOUNESS.
======================================
Flash Point Method:CC Flash P oint:20.0F,-6.7C Lower Limits:NA Upper Limits:NA Extinguishing Media:FOAM,CARBON DIOXIDE, DRY CHEMICALS.
Fire Fighting Procedures:FIGHT AS A FLAMMABLE LIQUID FIRE,WEAR SCBA. Unusual Fire/Explosion Hazard:VAPOR IS FLAMMABLE AND HEAVIER THAN AIR AND MAY TRAVEL TO SOURCES OF IGNITION AND IGNITE. ===================================
Spill Release Procedures:ABSORB WITH INERT MATERIAL, SAND, EARTH EVRMICULITE ETC. LARGE SPILLS MAY BE SCOOPED UP WITH NONSPARKING TOOLS, REMOVE SOURCES OF IGNITION. VENTIATE AREA. Neutralizing Agent:NA
============ Handling and Storage =============
Handling and Storage Precautions:STORE AWY FROM HEAT,SPARKS AND OPEN FLAMES. STORE AT AMBIENT TEMPERATURE. Other Precautions:KEEP CONTAINER CLOSED, USE ADEQUATE VENTILATION, AVOID CONTACT WITH EYES,SKIN AND CLOTHING.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:ORGANIC TYPE IF TVLS ARE EXCEEDED Ven

Work Hygienic Practices:PRUDENT Supplemental Safety and Health NA
========= Physical/Chemical Properties =========
HCC:F3 Boiling Pt:B.P. Text:NA Vapor Pres:NA Vapor Density:NA Spec Gravity:NA Evaporation Rate & Description Water:NEGIBLE Appearance and Odor:WATER CLEAR,LOW VISCOSITY LIQUID ,AROMATIC ODOR Percent Volatiles by Volume:NA
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:NA Hazardous Decomposition Products:CARBON MONOXIDE,CARBON DIOXIDE.
====== Disposal Considerations ==========
Waste Disposal Methods:STRICT COMPLIANCE WITH LOCAL STATE AND FEDERAL REGULATIONS.
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

tilation: EXPLOSION PROOF

particular situation.

Eye Protection: CHEMICAL GOGGLES

Protective Gloves: CHEMICAL AND PETROLEUM RESISTANT.

Other Protective Equipment:TO PREVENT CONTACT WITH WORKERS.