

GATOR SALES -- SOLVENT 140 3% AROMATICS MAX #2680950 -- 6850-00-637-6135

=====
Product Identification
=====

Product ID:SOLVENT 140 3% AROMATICS MAX #2680950

MSDS Date:04/03/1986

FSC:6850

NIIN:00-637-6135

MSDS Number: BMWTP

=== Responsible Party ===

Company Name:GATOR SALES

Address:2719 PHILLIPS HIGHWAY

City:JACKSONVILLE

State:FL

ZIP:32210

Country:US

Info Phone Num:904-399-0901

Emergency Phone Num

:904-399-0901

CAGE:GO250

=== Contractor Identification ===

Company Name:GATOR SALES

Address:2719 PHILLIPS HWY

City:JACKSONVILLE

State:FL

ZIP:32207

Country:US

Phone:904-399-0901

CAGE:GO250

Company Name:GATOR SALES INC

Address:2719 PHILLIPS HWY

Box:City:JACKSONVILLE

State:FL

ZIP:32207

Country:US

Phone:904-399-0901

CAGE:0AHD5

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC PETROLEUM DISTILATES.

CAS:64742-88-7

Fraction by Wt: 100%

Other REC Limits:NONE SP

ECIFIED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS UNKNOWN

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES:CAN CAUSE SEVERE IRRITATION,
REDNESS, TEARING,BLURRED VISION. SKIN: PROLONGED OR REPEATED
CONTACT CAN CAUSE NASAL AND RESPIRATORY IRRITATION,CENTRAL NERVOUS
SYSTEM DEFECTS.IF SWALLOWED CAN CAUSE GASTROINTESTINAL IR
RITATION,
NAUSEA, VOMITING.ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE
PNEUMONITIS.

Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS
LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:IRRITATION, REDNESS, TEARING OR BLURED VISION.
DIZZINESS, WEAKNESSS, FATIGUE, NASUEA, HEADACHE AND POSSIBLE
UNCONCIOUSNESS,AND EVEN DEATH IF OVER EXPOSED TO MATERIAL.
GASTROINTESTINAL IRRITATION, VOMI TING, DIARRHEA. ASPIRATION OF
MATERIAL IN
TO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE
FATAL.

Medical Cond Aggravated by Exposure:PREEXISTING EYE, SKIN, AND
RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS
PRODUCT.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. RESUSCITATE IF NOT
BREATHING. EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15
MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN: REMOVE
CONTAMINATED CLOTHI NG
. WASH WITH SOAP AND WATER. IF IRRITATION
PERSISTS, GET MEDICAL ADVICE. INGESTION: DO NOT INDUCE VOMITING.
GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL
ATTENTION.KEEP PERSON WARM.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:140F, 60C

Lower Limits:1

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACE

D SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR BE MOVED BY VENTILATION AND IGNITED BY HEAT,PILOT LIGHTS, OTHER FLAMES AND IGNITION SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL: WIPE/SOAK UP WITH PAPER TOWEL OR INERT ABSORBANT. PUT IN DISPOSAL CONTAINER. LARGE SPILL: EVACUATE AND VENTILATE AREA.ELIMINATE ALL IGNITION SOURCES IF POSSIBLE.STOP LEAK. DIKE TO RETAIN RUN OFF.DUMP LIQUID TO SALVAGE TANK.
Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.
Other Precautions:SURFACES THAT ARE SUFFICIENTLY HOT MAY IGNITE EVEN LIQUID PRODUCT IN THE ABSENCE OF SPARKS OR FLAME. ESTINGUISH PILOT LIGHTS, CIGARETTES AND TURN OFF OTHER SOURCES OF IGNITION PRIOR TO USE OR UNTIL VAPORS ARE GONE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL(TLV), USE NIOSH/MSHA APPROVED ORGANIC VAPOR CARTRIDGE AND DUST/MIST PRE-FILTER RESPIRATORS AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/ WARNINGS AND NIOSH-RESPIRATOR SELECTION.

Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE. LOCAL EXHAUST MAY BE REQUIRED IF WORK AREA NOT VENTED.

Protective Gloves:CHEMICAL RESISTANT,NITRILE RUBBER

Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER. INDUSTRIAL- TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED

CLOTHING OR
FOOTWEAR.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO
NOT BREATHE VAPORS OR MISTS.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:365F,185C

Vapor Pres:0.50

Vapor Density:5.4

Spec Gravity:0.78

Evaporation Rate & Reference:151.0 (ETHER = 1)

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZ
ING AGENTS

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES
OF IGNITION

Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS:,CARBON
DIOXIDE AND CARBON MONOXIDE, VARIOUS HYDROCARBONS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL
APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This i

nformation is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.