View NSN Online: https://aerobasegroup.gr/nsn/9150-00-942-9343

SOUTH SIDE ENTERPRISES CORP -- 2190 TEP LUBE LUBRICATING OIL, STEAM TURBINE -9150-00-942-9343

Product ID:2190 TEP LUBE LUBRICATING OIL, STEAM TURBINE MSDS Date:09/09/1992 FSC:9150 NIIN:00-942-9343 MSDS Number: BNRRP === Responsible Party === Company Name: SOUTH SIDE ENTERPRISES CORP Address:RT 92 Box:100 City:CHASE CITY State:VA ZIP:23924 Country:US Info Phone Num :804-279-4371 (DGSC-SSH) Emergency Phone Num: 703-448-5369 WRONG NUMBER! Preparer's Name:DGSC-SSH CAGE:48122 === Contractor Identification === Company Name: SOUTH SIDE ENTERPRISES CORP Address:RT 92 Box:100 City:CHASE CITY State:VA ZIP:23924 Country:US Phone:703-448-5369 WRONG NUMBER! CAGE:48122

======= Composition/Information on Ingredients ==========

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC CAS:64742-65-0 RTECS #:PY8038500 Other REC Limits :NONE SPECIFIED BY M. OSHA PEL:5 MG/M3 OIL MIST ACGIH TLV:5 MG/M3 (OIL MIST)

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE- ORAL:LOW TOXICITY. MAY CAUSE
VOMITING & DIARRHEA. SMALL AMOUNT ASPIRATED INTO LUNGS WILL CAUSE
LUNG INJURY. INHALATION:MIST/VAPORS/FUMES MAY CAUSE RESPIRATORY
TRACT IRRITATION. EYE:MAY CAUSE
IR RITATION. SKIN:REPEATED CONTACT
MAY CAUSE IRRITATION. CHRONIC:NONE KNOWN.
Effects of Overexposure:ORALLY MAY CAUSE VOMITING & DIARRHEA. SMALL
AMOUNT ASPIRATED INTO LUNGS WILL CAUSE LUNG INJURY. INHALATION OF
MIST/VAPORS/FUMES MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTACT

WITH EYES MAY CAUSE IRRI TATION. REPEATED SKIN CONTACT MAY CAUSEIRRITATION.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THIS MATERIAL.

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. SKIN:REMOVE EXCESS. WASH SKIN WITH SOAP & WATER. EYE:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. INHALED:REMOVE TO FRESH AIR & PROVIDE OXYGEN/CPR IF NEEDED. ORAL:DO NOT INDUCE VOMITING.GET IMMEDIATE MEDICAL ATTENTION.

Flash Point:>200F,>93C

Extinguishing Media:USE WATER FOG, CO2, FOAM, OR DRY C HEMICAL. DO NOT

USE A DIRECT STREAM OF WATER. PRODUCT MAY FLOAT & CAN BE REIGNITED. Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS. WATER OR FOAM MAY CAUSE FROTHING.

Spill Release

Procedures:STOP FLOW. RECOVER BY VACUUMING. WIPE OR MOP UP OR ABSORB WITH DIATOMACEOUS EARTH OR OTHER INERT MATERIAL. STORE IN APPROPRIATE CONTAINER FOR DISPOSAL.

Handling and Storage Precautions:STORAGE- STORE IN COOL PLACE. EXCESSIVE MISTING MAY CAUSE SLIPPERY FLOORS. PROPER FOOTWEAR REQUIRED.

Other Precautions:WASH HANDS WITH SOAP AND WATER BEFORE EATING, DRINKING, OR SMOKING. DO NOT CREATE MIST AND AVO ID INHALING MIST OR VAPORS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE NORMALLY REQUIRED. IF VAPOR OR MIST IS GENERATED, USE RESPIRATOR APPROVED BY NIOSH AS APPROPRIATE. Ventilation:GOOD GENERAL VENTILATION IS SUFFICIENT FOR MOST CONDITIONS. Protective Gloves:NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL Eye Protection:USE CHEMICAL SAFETY GOGGLES

Other Protective Equipment: EYE WASH STATION & SAFETY SHOWER. CHEMICALLY RESISTANT BOOTS AN

D APRONS RECOMMENDED.

Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

NO MSDS WAS AVAILABLE FROM MANUFACTURER. THIS MSDS WAS PREPARED BY THE PROFESSIONALS OF DGSC-SSH WITHOUT ANY WARRANTY. IT IS THE USER'S RESPONSIBILITY TO GATHER INFORMATION AND USE THE MATERIAL PROPER LY TO PROTECT EMPLOYEES AND ENVIRONMENT.

HCC:V6 Spec Gravity: