

R.H.CARLSON COMPANY,INC. -- SILICONE SYSTEMS 982 -- 8040-01-331-8046

=====  
Product Identification  
=====

Product ID:SILICONE SYSTEMS 982

MSDS Date:12/02/1991

FSC:8040

NIIN:01-331-8046

MSDS Number: BNRTT

=== Responsible Party ===

Company Name:R.H.CARLSON COMPANY,INC.

Address:41-CHESTNUT STREET

City:GREENWICH

State:CT

ZIP:06830

Country:US

Info Phone Num:203-531-5500

Emergency Phone Num:800-424-9300

CHEMTREC

CAGE:33530

=== Contractor Identification ===

Company Name:R.H.CARLSON COMPANY,INC.

Address:41-CHESTNUT STREET

Box:1687

City:GREENWICH

State:CT

ZIP:06830-5921

Country:US

Phone:203-531-5500

CAGE:33530

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NON-HAZARDOUS INGREDIENTS

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

He

alth Hazards Acute and Chronic:WARNING! MAY CAUSE IRRITATION. AVOID CONTACT WITH SKIN, EYES, AND CLOTHING, DIRECT CONTACT WITH UNCURED PRODUCT OR ITS VAPORS MAY CAUSE SLIGHT IRRITATION. INHALATION OF THE VAPORS MAY PRODUCE RESPIRATORY IRRITATION. INGESTION OF THE MATERIAL MAY PRODUCE ABDOMINAL PAIN AND DIARRHEA.

=====  
First Aid Measures  
=====

First Aid:INGESTION: IF SWALLOWED, DON'T INDUCE VOMITING. IF VOMIT OCCURS, GIVE MORE FLUID. HAVE A DOCTOR DETERMINE CONDITION OF PATIENT. VOMITING WILL PERMIT EVACUATION OF STOMACH OR INDUCTION OF VOMIT. DON'T GIVE FLUID TO UNCONSCIOUS PERSON. SKIN: FLUSH WITH WATER 15 MIN. REMOVE CONTAMINATED CLOTHES/SHOES. GET MEDICAL AID IF IRRITATION OCCURS. EYE: IMMEDIATELY FLUSH WITH WATER 15 MIN. HOLD EYELID OPEN. DON'T NEUTRALIZE. GET MEDICAL AID ASAP.

=====  
Fire Fighting Measures  
=====

Flash Point Method:CC

Flash Point:250F,121C

Lower Limits:2.6

Upper Limits:12.8

Fire Fighting Procedure

PREVENT HUMAN EXPOSURE TO FIRE/SMOKE/FUMES/PRODUCT COMBUSTION. EVACUATE NONESSENTIAL PERSONNEL. WEAR FULL FACE, SCBA & IMPERMEABLE CLOTHING. USE STANDARD FIRE FIGHTING TECHNIQUES

=====  
Accidental Release Measures  
=====

Spill Release Procedures:FOLLOW GOOD INDUSTRIAL HYGIENE. WEAR PROTECTIVE CLOTHING & SPLASH GOGGLES. SOAK UP LIQUID WITH ABSORBENT. SWEEP UP ABSORBED MATERIAL. PLACE IN A CHEMICAL WASTE DRUM FOR DISPOSAL. WASH UP AREA WITH DETERGENT & WATER, FLUSH WITH WATER. LARGE SPILLS: DIKE, PUMP INTO DRUM.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:AVOID CONTACT WITH SKIN AND EYES, USE ONLY IN A WELL VENTED AREA.

Other Precautions:CONTACT LENS WEARERS TAKE APPROPRIATE PRECAUTION. STORE IN A COOL PLACE AND KEEP AWAY FROM HEAT, SPARKS, AND FLAME.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:IF CONDITIONS GENERATE VAPOR, HANDLE MATERIAL IN OPEN/VENTED AREA. IF INADEQUATE VENTILATION

NT, USE NIOSH ORGANIC VAPOR

RESPIRATOR. IF EXPOSURE NECESITATES HIGHER PROTECTION LEVEL, A POSITIVE PRESSURE AIR SUPP LIED RESPIRATOR IS RECOMMENDED.

Ventilation:LOCAL EXHAUST IS REQUIRED AND GENERAL MECHANICAL VNET IS SUGGESTED IN CLOSED AREAS.

Protective Gloves:PLASTIC FILM OR RUBBER GLOVES SUGGESTED.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:PROTECTIVE APRON OR COVERALLS.

Work Hygienic Practices:KEEP AWAY FROM HEAT, SPARKS AND FLAME. AVOID PROLONGED VAPOR BREAT

HING AND CONTACT WITH SKIN AND EYES.

Supplemental Safety and Health

(EMERG/FIRST AID CONT'D) FLUSH AN ADDITIONAL 15 MIN IF MEDICAL ATTENTION IS NOT AVAILABLE. INHALATION: REMOVE FROM AREA. SEEK MEDICAL ATTENTION IF BREATHING IS DIFFICULT. OXYGEN MAY BE DELIVERED UPON A PHYSICIAN'S ADVICE. IF NOT BREATHING,GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH TO MOUTH.

===== Physical/Chemical Properties =====

HCC:N1

Vapor Pres:NEGLIGIBLE

Vapor Density:> 1

Sp

ec Gravity:1.05

Viscosity:PASTE

Evaporation Rate & Reference: