

NAVISTAR INTERNATIONAL CORP -- GASKET: PART NO. 83817HBR1 -- 5330-01-186-3314

=====
Product Identification
=====

Product ID:GASKET: PART NO. 83817HBR1

MSDS Date:09/28/1992

FSC:5330

NIIN:01-186-3314

MSDS Number: BNVCZ

=== Responsible Party ===

Company Name:NAVISTAR INTERNATIONAL CORP

Address:6125 URBANA ROAD

Box:600

City:SPRINGFIELD

State:OH

ZIP:45501

Country:US

Info Phone Num:708-983-3307

Emergenc

y Phone Num:708-983-3307

Preparer's Name:DGSC-SSH

CAGE:89346

=== Contractor Identification ===

Company Name:NAVISTAR INTERNATIONAL CORP., TRUCK BRANCH, OHIO

Address:6125 URBANA ROAD

Box:600

City:SPRINGFIELD

State:OH

ZIP:45501

Country:US

Phone:312-836-2000

CAGE:89346

=====
Composition/Information on Ingredients
=====

Ingred Name:ASBESTOS, CHRYSOTILE

CAS:12001-29-5

RTECS #:CI6478500

Other REC Limits:0.2 FIBERS/CC

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:2 FIBERS/CC; A1;9192

=====

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:PROLONGED OR REPEATED EXPOSURE TO DUST FROM ABRASIVE ACTIONS(EG. CUTTING, MACHINING, FILING, ETC.) MAY LEAD TO ASBESTOSIS & MESOTHELIOMA. SMOKING COMBINED WITH FIBER INHALATION GREATLY INCREASES LUNG CANCER RISK.

Explanation of Carcinogenicity:OVEREXPOSURE TO AIRBORNE CONCENTRATIONS

OF ASBESTOS MAY LEAD TO ASBESTOSIS AND MESOTHELIOMA.

Effects of Overexposure:INHALATION OF AIRBORNE DUST CONTAINING ASBESTOS FIBERS ON REPEATED EXPOSURE MAY CAUSE OR CAN LEAD TO ASBESTOSIS / MESOTHELIOMA; DUST MAY CAUSE EYE IRRITATION.

Medical Cond Aggravated by Exposure:PERSONS WITH RESPIRATORY DISEASE OR PERSONS WHO SMOKE MAY BE AT INCREASED RISK FROM EXPOSURE TO ASBESTOS CONTAINING DUST.

=====
First Aid Measures
=====

First Aid:IN

HALATION: REMOVE TO FRESH AIR. GET MEDICAL ATTENTION. EYE: PROMPTLY FLUSH WITH RUNNING WATER FOR 15 MINUTES WHILE LIFTING EYELID. GET MEDICAL ATTENTION. SKIN: PROMPTLY FLUSH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INGESTION: NOT NORMALLY A ROUTE OF ENTRY. GET MEDICAL ATTENTION AS REQUIRED.

=====
Fire Fighting Measures
=====

Flash Point:NONE

Autoignition Temp:Autoignition Temp Text:NONE

Extinguishing Media:MATERIAL IS NOT FLAMMABLE ; USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:COMBUSTION PRODUCTS OF THIS MATERIAL MAY BE TOXIC. USE A SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES INVOLVING CHEMICAL PRODUCTS.

Unusual Fire/Explosion Hazard:NONE KNOWN

=====
Accidental Release Measures
=====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION. VACUUM OR WET CLEAN IF DUST IS INVOLVED. ANY VACUUM SYS

TEM SHOULD BE EQUIPPED
WITH AN OUTLET "HEPA" FILTER TO PREVENT REINTRODUCING ASBESTOS
FIBERS TO THE ATMOSPHERE.

=====
===== Handling and Storage =====

Handling and Storage Precautions:HANDLE IN A MANNER TO MINIMIZE
FORMATION OR RETENTION OF AIRBORNE DUST. USE PROPER PERSONAL
PROTECTION FOR TASK AT HAND.

Other Precautions:AS MANUFACTURED, LOCKED-IN ASBESTOS DOES NOT PRESENT
A HAZARD. ONLY WHEN THE ITEM IS ABRADED AND DUST IS GENERATED DO
ASBESTOS FIBERS BECOME RELEASED AND AIRBORNE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:EXPOSURE TO AIRBORNE ASBESTOS SHALL NOT EXCEED
0.2 F/CC TWA. IF EXPOSURE IS LESS THAN 50 TIMES THE PEL, USE A FULL
FACE-PIECE NIOSH/MSHA APPROVED RESPIRATORS WITH A HEPA FILTER FOR
ASBESTOS. MAKE SELECTIONS I/A/W 29CFR1910.1001 & 1910.1101.

Ventilation:LOCAL EXHAUST IS RECOMMENDED IN OPERATIONS WHERE DUST IS
GENERATED SUCH AS CUTTING, GRINDING, S
CRAPPING, ETC.

Protective Gloves:USE TYPE REQUIRED FOR WORK BEING DONE.

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment:WORK CLOTHES OR COVERALLS.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE
EATING, DRINKING OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE
REUSE.

Supplemental Safety and Health

CONTAINS ASBESTOS FIBERS. AVOID CREATING DUST. CANCER AND LUNG DISEASE
HAZARD. AVOID BREATHING AIRBORNE ASBESTOS FIBERS.

=====
===== Physical/Chemical Properties =====

HCC:T6

Evaporation Rate & Reference:NONE

Solubility in Water:NOT SOLUBLE

Appearance and Odor:GASKET, NO ODOR

Percent Volatiles by Volume:NONE

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE KNOWN

Stability Condition to Avoid:NONE KNOWN

=====
===== Disposal Considerations =====

Waste Disposal Methods:DUST SHOULD BE HANDLED AS A HAZARDOUS AIR

POLLUTANT I/A/W 40CFR61 SUBPART "M" PERTAINING TO ASBESTOS. USE LANDFILLS APPROVED FOR ASBESTOS DISPOSAL. INDICATE IF ITEM UNDER CONSIDERATION FOR DISPOSAL IS "FRIABLE OR NON-FRIABLE".

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability

for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.