

RIVERSIDE MANUFACTURING CO. -- WINDSHIELD WASHER -- 6850-00-926-2275

=====
Product Identification
=====

Product ID:WINDSHIELD WASHER

MSDS Date:01/19/1992

FSC:6850

NIIN:00-926-2275

MSDS Number: BNWPZ

=== Responsible Party ===

Company Name:RIVERSIDE MANUFACTURING CO.

Address:10390 BERMUDA CT.

City:MOHAVE VALLEY

State:AZ

ZIP:86440

Country:US

Info Phone Num:602-768-1771

Emergency Phone Num:602-768-73

93

Preparer's Name:LARRY LIVELY

CAGE:DO602

=== Contractor Identification ===

Company Name:RIVERSIDE MANUFACTURING

Address:10390 BERMUDA CT.

City:MOHAVE VALLEY

State:AZ

ZIP:86440

Phone:602-768-7393

CAGE:DO602

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ALCOHOL (SARA III)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: 50%

Other REC Limits:NONE SPECIFIED

OSHA PEL:S,200PPM/250STEL

ACGIH TLV:S,200PPM/250STEL; 93

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=

==== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:REPEATED EXPOSURE BY INHALATION OR INGESTION MAY CAUSE INTERNAL POISONING OR BRAIN DISORDERS.

Effects of Overexposure:MILD SKIN IRRITATION, IRRITATION OF THE MUCOUS, NAUSEA, GIDDINESS, LIGHT-HEADED.

==== First Aid Measures =====

First Aid:SKIN & EYE: FLUSH WITH WATER FOR 15 MINUTES. INHALATION:

REMOVE TO FRESH AIR. INGESTION: GIVE LARGE AMOUNTS OF WATER OR MILK AND INDUCE VOMITING. IF UNCONSCIOUS DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.

==== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:51.8F,11.0C

Autoignition Temp:Autoignition Temp Text:725F

Lower Limits:6%

Upper Limits:36%

Extinguishing Media:WATER SPRAY / DRY POWDER / FOAM / CO2

Fire Fighting Procedures:METHANOL BURNS W/CLEAR FLAME INVISIBLE IN DAYTIME

. CONCENTRATIONS>20% IN WTR CAN BE IGNITED. WTR MAY BE INEFFECTIVE DEPENDING ON DEPTH OF METHANOL BURNING.

Unusual Fire/Explosion Hazard:FIREFIGHTERS MUST WEAR FULL FACE, POSITIVE PRESSURE, SELF CONTAINED BREATHING APPARATUS AND APPROPRIATE CLOTHING.

==== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP SPILL.

CONTAIN BY DIKING. RECOVER OR DILUTE WITH WATER TO REDUCE HAZARD.

Neutralizing Agent:WATER

=====

==== Handling and Storage =====

Handling and Storage Precautions:STORE IN ENCLOSED AND GROUNDED EQUIPMENT. NO SMOKING OR OPEN FLAME.

Other Precautions:ENSURE PROPER ELECTRICAL GROUNDING.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED.

Ventilation:LOCAL AND GENERAL.

Protective Gloves:NEOPRENE.

Eye Protection:FACE SHIELD AND SAFETY GLASSES.

Other Protective Equipment:WEAR CHEMICAL RESISTIVE CLOTHING.

Su

===== Physical/Chemical Properties =====

HCC:F5

Boiling Pt:B.P. Text:148F,64C

Melt/Freeze Pt:M.P/F.P Text:-144F,-98C

Vapor Pres:96

Vapor Density:1.105

Spec Gravity:0.792 (WATER=1)

Evaporation Rate & Reference:2.1

Solubility in Water:100%

Appearance and Odor:BLUE & ODORLESS

Percent Volatiles by Volume:100%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS,

STRONG ACIDS, STRONG BASES, MAY BE CORROSIVE TO LEAD
AND ALUMINUM.

Stability Condition to Avoid:DO NOT EXPOSE TO OPEN FLAME

Hazardous Decomposition Products:FORMALDEHYDE AND CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH ALL LOCAL, STATE, AND
FEDERAL REGULATION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Depart
ment

of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.