View NSN Online: https://aerobasegroup.gr/nsn/1560-01-247-4365

Product ID:BP HEAT OIL NO. 2 MSDS Date:08/05/1988 FSC:9140 NIIN:01-247-4365 **MSDS Number: BPBQD** === Responsible Party === Company Name: B P OIL COMPANY Address:200 PUBLIC SQUARE Box:6989 City:CLEVELAND State:OH ZIP:44114-2375 Country:US Info Phone Num:216-586-6499/800-424-9300(CHEMTREC) **Emergency Phone Num:80** 0-321-8642/800-362-8059(OH ONLY) Preparer's Name: RIGNEY CAGE:0MJ97 === Contractor Identification === Company Name: B P OIL COMPANY Address:200 PUBLIC SQUARE Box:6989 City:CLEVELAND State:OH ZIP:44114-2375 Country:US Phone:800-321-8642/800-362-8059(OH ONLY) CAGE:0MJ97

Ingred Name:ALIPHATIC PETROLEUM DISTILLATES CAS:68476-30-2 Fraction by Wt: 99.9% Other REC Limits:NONE RECOMMENDED

============ Hazards Identification

LD50 LC50 Mixture:LD 50 ORAL RABBIT IS 38 GM/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS. ASPIRATION OF OIL INTO LUNGS AFTER INGESTION MAY CAUSE PNEUMONITIS WHICH MAY BE FATAL. CHRONIC: ALLERGIC SKIN REACTION. PROLONGED OR MASSIVE SKIN CONTACT MAY CAUSE POISONING. PROLONGED INHALATION MAY CAUSE CHA NGES IN THE LIVER, KIDNEY AND BONE MARROW. Explanation of Carcinogenicity: PRODUCTS OF SIMILAR COMPOSITION HAVE PRODUCED CANCER IN LABORATORY ANIMALS AND HAVE BEEN POSITIVE IN MUTAGENIC TESTS. Effects of Overexposure: EYE/SKIN: MODERATELY IRRITATING, REDNESS. INHALATION: HEADACHE, DIZZINESS, NAUSEA, STUPOR, CONVULSIONS, OR LOSS OF CONSCIOUSNESS, AND DEATH. INGESTION: DIGESTIVE TRACT IRRITATION, NAUSEA, VOMITING, DI ARRHEA. SYMPTOMS SIMILAR TO INHALATION. Medical Cond Ag

gravated by Exposure:PRE-EXISTING RESPIRATORY, KIDNEY, CENTRAL NERVOUS SYSTEM OR SKIN DISEASES MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

First Aid:EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS, SEE DOCTOR. SKIN: WIPE EXCESS OIL OFF WITH A DRY CLOTH. WASH WITH SOAP AND WATER WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. INHALATION: REMOVE VICTIM TOFRESH AIR. GIVE

OXYGEN/CPR IF NEEDED. SEE DOCTOR. INGESTION: DO NOT INDUCE VOMITING. SEE DOCTOR IMMEDIATELY.

Flash Point Method:TCC Flash Point:130F,54C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:0.7 Upper Limits:5.0 Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. WATER STREAM MAY SPLASH AND SPREAD FLAMING LIQUIDS. Fire Fighting Procedures:FIREFIGHTERS WEAR SELF-CONTAINED BREATHING APP

EXPOSED CONTAINERS. Unusual Fire/Explosion Hazard:FIRE EXPOSED CONTAINERS MAY EXPLODE.
HEATING INCREASES FIRE HAZARD OF MATERIAL. THERMAL DECOMPOSITION MAY PRODUCE IRRITATING OR TOXIC SUBSTANCES.
======================================
Spill Release Procedures:REMOVE PERSONNEL. ELIMINATE IGNITION SOURCES. VENTILATE AREA. WEAR PROTECTIVE CLOTHING AND EQUIPMENT. STOP LEAK IF IT CAN BE DO NE SAFELY. CONTAIN SPILL. ABSORB IN INERT MATERIAL AND PLACE IN APPROPIAT E DISPOSAL CONTAINER. WASH AREA WITH SOAP & WATER.
======================================
 Handling and Storage Precautions:STORE IN CLOSED CONTAINERS OR TANKS IN WELL VENTILATED AREA. KEEP AWAY FROM EXCESSIVE HEAT, IGNITION SOURCES OR OXIDIZERS. DO NOT CUT OR WELD CONTAINR Other Precautions:PROTECT CONTAINERS FROM PHYSICAL DAMAGE. USE NON-SPARKING TOOLS AND EXPLOSION-PROOF EQUIPMENT. PREVENT STATIC ELECTRIC SPARKS. PROCEDURES FOR SLOW INITIAL LOADING RATE MUST BE FOLLOWED. NO SMOKING IN AREAS OF USE.
======================================
Respiratory Protection:NONE NORMALLY REQUIRED. NIOSH/MSHA-APPROVED RESPIRATOR OR SCBA AS APPROPIATE FOR EXPOSURE OF CONCERN. Ventilation:EXPLOSION-PROOF MECHANICAL (GENERAL) VENTILATION. Protective Gloves:NEOPRENE OR NITRILE RUBBER GLOVES. Eye Protection:CHEMICAL SAFETY GOGGLES. Other
Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO MINIMIZE EXPOSURE FROM PROLONGED OR REPEATED CONTACT. EYE BATH AND SAFETY SHOWER.
Work Hygienic Practices:DO NOT WEAR OIL CONTAMINATED CLOTHING. DO NOT PUT OILY RAGS INTO POCKETS. WASH AFTER HANDLING AND BEFORE EATING. Supplemental Safety and Health
DO NOT USE IN PORTABLE KEROSENE HEATERS DESIGNED FOR K-1, OR IN UNVENTED HEATERS. EMPTY CONTAINERS MAY CONTAIN TOXIC, FLAMMABLE/COMBUSTIBLE OR EXPLOSIVE RESIDUE OR VAPORS.

=

HCC:F4 Boiling Pt:B.P. Text:320F,160C Melt/Freeze Pt:M.P/F.P Text:-15F,-26C Vapor Pres:0.4 Vapor Density:4.7 Spec Gravity:0.84-0.89 pH:7 Evaporation Rate & amp; Reference:0.04 (BUTYL ACETATE = 1) Solubility in Water:INSOLUBLE. Appearance and Odor:WATER WHITE TO CLEAR YELLOW, OILY LIQUID WITH MILD PETROLEUM ODOR. Percent Volatiles by Volume:100

Stability In dicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, THICK BLACK SMOKE AND UNDETERMINED HYDROCARBON COMPOUNDS DURING COMBUSTION.

Waste Disposal Methods:CONTACT YOUR LOCAL ENVIRONMENTAL OFFICER. DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULAT

IONS. CONTAMINATED ABSORBENT MATERIAL MAY BE DISPOSED OF IN APPROVED CHEMICAL WASTE LANDFILL S. RCRA HAZARDOUS WASTE NUMBER D001.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should s eek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.