

J.W.HARRIS CO.INC. -- BARE WIRE 347 -- 3439-00-163-4360

=====
Product Identification
=====

Product ID:BARE WIRE 347

MSDS Date:06/01/1992

FSC:3439

NIIN:00-163-4360

MSDS Number: BPBRX

=== Responsible Party ===

Company Name:J.W.HARRIS CO.INC.

Address:10030 DEERFIELD ROAD

City:CINCINNATI

State:OH

ZIP:45242

Country:US

Info Phone Num:513-891-2000

Emergency Phone Num:513-891-2000

CAGE:27911

=== Contract

or Identification ===

Company Name:J. W. HARRIS CO INC & HARRIS WELCO, DIVISION/J.W. HARRIS
CO

Address:1051 YORK RD

Box:City:KINGS MOUNTAIN

State:NC

ZIP:28086

Country:US

Phone:704-739-6421

CAGE:34920

Company Name:J. W. HARRIS CO., INC.

Address:10930 DEERFIELD ROAD

Box:City:CINCINNATI

State:OH

ZIP:45242-4110

Country:US

Phone:513-891-2000

CAGE:27911

=====
Composition/Information on Ingredients
=====

Ingred Name:IRON

CAS:7439-89-6

RTECS #:NO4565500

Fraction by Wt: BALENCE

Ot

her REC Limits:NONE
OSHA PEL:10MG/M3(FE203)
ACGIH TLV:5MG/M3(FE203)

Ingred Name:CHROMIUM (SARA III)
CAS:7440-47-3
RTECS #:GB4200000
Fraction by Wt: 19-21.5%
Other REC Limits:NONE
OSHA PEL:1 MG/M3
ACGIH TLV:0.5 MG/M3; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:NICKEL (SARA III)
CAS:7440-02-0
RTECS #:QR5950000
Fraction by Wt: 9-11%
Other REC Limits:NONE
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9192

Ingred Name:MANGANESE (SARA III)
CAS:7439-96-5
RTECS #:OO9275000
Fraction by Wt: 1.0-2.5%
Other REC Limits:NONE
OSHA PEL:(C) 5 MG/M3 DUST
ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:SILICON
CAS:7440-21-3
RTECS #:VW0400000
Fraction by Wt: 0.3-1.0%
Other REC Limits:NONE
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:MOLYBDENUM
CAS:7439-98-7
RTECS #:QA4680000
Fraction by Wt: 0.75%
Other REC Limits:NONE
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3; 9293

Ingred Name:COPPER (SARA III)
CAS:7440-50-8
RTECS #:GL5325000
Fraction by Wt: 0.75%
Other REC Limits:NONE
OSHA PEL:0.1MG/M3

FUME/1 DUST
ACGIH TLV:0.2MG/M3 FUME; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:GRAPHITE, SYNTHETIC
CAS:7440-44-0
RTECS #:FF5250100
Fraction by Wt: 0.08%
Other REC Limits:NONE
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:2 MG/M3 TDUST; 9293

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:ACUTE:METALLIC TASTE,NAUSEA,TIGHTNES
S

OF CHEST,FEVER,DIZZINESS,DRYNESS,IRRITATION OF EYES,NOSE,THROAT.
CHRONIC: EXCESSIVE LEVELS MAY CAUSE BRONCHIAL ASTHMA,LUNG
FIBROSIS,PNEUMOCONIOSIS. LONG TERM EXPO SURE TO IRON FUMES MAY
PRODUCE SIDEROSIS. ARC RAYS MAY INJURE EYE & BURN SKIN. ELECTRIC
SHOCK CAN KILL.

Explanation of Carcinogenicity:CHROMIUM, NICKEL AND SOME OF THEIR
COMPOUNDS ARE LISTED AS CARCINOGENS BY NTP & IARC. SEE INDIVIDUAL
REPORTS FOR DATA.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical C

ond Aggravated by Exposure:INDIVIDUALS WITH IMPAIRED
PULMONAARY FUNCTIONS OR ILLNESS MAY HAVE SYMPTOMS EXACERBATED BY
FUME IRRITANTS,

=====
===== First Aid Measures =====
=====

First Aid:REMOVE FROM DUST AND FUME EXPOSURE. IF BREATHING HAS STOPPED,
PERFORM ARTIFICIAL RESPIRATION. SUMMON MEDICAL AID IMMEDIATELY.

=====
===== Fire Fighting Measures =====
=====

Extinguishing Media:SUPPLIER DID NOT ADDRESS THIS FIELD.

Fire Fighting Proce

dures:SUPPLIER DID NOT ADDRESS THIS FIELD.

Unusual Fire/Explosion Hazard:WELDING ARCS, OPEN FLAME AND SPARKS CAN IGNITE COMBUSTIBLES. SEE ANSI/ASC Z49.1-1983 SECTION 6.

===== Accidental Release Measures =====

Spill Release Procedures:"NOT APPLICABLE"

Neutralizing Agent:NO INFORMATION GIVEN ON MSDS BY SUPPLIER

===== Handling and Storage =====

Handling and Storage Precautions:NO INFORMATION GIVEN ON MSDS BY SUPPLIER

Other P

recautions:READ AND UNDERSTAND THE MANUFACTURER'S INSTRUCTIONS AND THE PRECAUTIONARY LABEL ON THE PRODUCT. SEE AMSI STANDARD Z49.1 AND 29CFR1910 FOR DETAILS ON MANY PRECAUTIONS. TRAIN EMPLOYEE TO KEEP HIS HEAD O UT OF FUMES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE RESPIRABLE FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR WHEBN WELDING IN CONFINED SPACES OR WHERE LOCAL EXHAUST OT VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.

Ventilation:USE ENOUGH VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE AT OPERATOR'S BREATHING ZONE AND THE GENERAL AREA BELOW TLV

Protective Gloves:WELDER'S GLOVES.

Eye Protection:HELMET OR FACE SHIELD WITH FILTER LENS.

Other Protective Equipment:MAY ALSO INCLUDE ARM PROTECTOR, APRON, HAT, SHOULDER PROTECTION. SEE SUPP DATA.

Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE EATING,SMOKEING, USING SANITARY FACILITIES.

Supplemental Safety and Health

PROVIDE SCREENS AND FLASH

GOGGLES TO PROTECT OTHER INDIVIDUALS FROM

BEING EXPOSED TO THE RADIATION FROM THE ELECTRIC ARC.

===== Physical/Chemical Properties =====

HCC:N1

Solubility in Water:INSOLUBLE

Appearance and Odor:WELDING ROD.NO ODOR. 0.062 INCH DIAMETER BY 36 INCHES LONG.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:WELDING & BRAZING FUMES CANNOT BE CLASSIFIED SIMPLY. COMP

POSITION AND QUANTITY DEPEND ON BASE METAL,
FILLER METAL AND USE

===== Disposal Considerations =====

Waste Disposal Methods:"NOT APPLICABLE" HMIS: DISPOSE I/A/W ALL
FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.