View NSN Online: https://aerobasegroup.gr/nsn/6750-01-354-7466

## 

Product ID:173 3013 RAPID FIXER, PART B

MSDS Date:01/15/1990

FSC:6750

NIIN:01-354-7466

MSDS Number: BPCGP === Responsible Party ===

Company Name: EASTMAN KODAK CO.

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Country:US

Info Phone Num:716-724-4501/PACK=JOHN 716-588-3559

**Emergency Pho** 

ne Num:716-722-5151(72)/FAX 716-724-9656

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

======= Composition/Information on Ingredients ========

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000 Fraction by Wt: 65 - 74%

Other REC Limits: NONE RECOMMENDED

Ingred Name: ALUMINUM SULFATE (SARA III)

CAS:10043-01-

RTECS #:BD1700000 Fraction by Wt: 15 - 20%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: SULFURIC ACID (SARA III)

CAS:7664-93-9

RTECS #:WS5600000 Fraction by Wt: 11%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

============= Hazards Identification =======================

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS 500 - 5000 MG/KG

Rou

tes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE- INHALATION:LOW HAZARD FOR

RECOMMENDED HANDLING. EYES:MAY CAUSE SEVERE IRRITATION, BURNS AND BLINDNESS. SKIN:CONTACT CAUSES SEVERE BURNS AND IRRITATION.

ORAL:HARMFUL & BURNS MOUTH, THROAT, ESOPH AGUS AND STOMACH.

CHRONIC- NONE KNOWN.

Effects of Overexposure:INHALATION HAS LOW HAZARD FOR RECOMMENDED HANDLING. MAY CAUSE SEVERE EYE IRR

ITATION, BURNS AND BLINDNESS.

SKIN CONTACT CAUSES SEVERE BURNS AND IRRITATION. HARMFUL & BURNS MOUTH, THROAT, ESOPHAGUS AND STOMACH IF SWALLOWED.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THIS MATERIAL.

First Aid:GET MEDICAL ATTENTION IMMEDIATELY. EYE/SKIN:IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MINUTES. HOLD EYELIDS OPEN. INHALED:REMOVE TO FRESH AIR.

ORAL:DO NOT INDUCE VOMITING. IF CONSCIOUS, DRINK WATER /MILK. CALL A PHYSICIAN IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. Flash Point:NONE Extinguishing Media: EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE Fire Fighting Procedures: WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:NONE ====== Accidental Rele ase Measures ========= Spill Release Procedures: AVOID SKIN CONTACT. WEAR SUITABLE PROTECTIVE EQUIPMENTS. VENTILATE AREA. NEUTRALIZE WITH BAKING SODA. FLUSH TO SEWER WITH PLENTY OF WATER. WASH CONTAMINATED AREA WITH WATER. FEDERAL, STATE AND LOCAL R EGULATIONS TAKE PRECEDENCE. Neutralizing Agent: SODIUM BICARBONATE ========== Handling and Storage =============== Handling and Storage Precautions: STORAGE- AVOID CONTACT WITH CAUSTIC. Other Precautions:KEEP THIS AND ALL CHEMICALS OUT OF REACH OF CHILDREN. THIS PRODUCT FOR INDUSTRIAL USE ONLY. AVOID BREATHING VAPORS OR MISTS. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY

AFTER HANDLING.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: NON REQUIRED UNDER NORMAL CONDITIONS. IF HIGH VAPOR OR MIST CONCENTRATIONS EXPECTED, USE NIOSH-APPROVED RESPIRATOR FOR ACID MISTS. WEAR SUPPLIED-AIR RESPIRATOR PROTECTION IN CONFINED OR

ENCLOSED SPACE S, IF NEEDED.

Ventilation: GOOD GENERAL VENTILATION IS SUFFICIENT FOR MOST CONDITIONS (10 ROOM VOLUMES PER HOUR).

Protective Gloves: IMPERVIOUS

Eye Protection: GOGGLES/FACE SHIELD

Other Protective Equipment: ROUTINE USE OF ACID TYPE CLEANSER & GLOVES WILL MINIMIZE ALLERGIC SKIN REACTION. HAVE EYE WASH STATION & SHOWER NEARBY.

Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Su

pplemental Safety and Health SOLUTION NUMBER 4415

======== Physical/Chemical Properties ===========

HCC:C1

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:18 @ 20C Vapor Density: 0.6 Spec Gravity:1.30

pH: 1.0

Solubility in Water: COMPLETE

Appearance and Odor:CLEAR, WATER-WHITE SOLUTION; SLIGHT SULFUR DIOXIDE

ODOR.

Percent Volatiles by Volume: 71

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES ALKALI
Stability Co
ndition to Avoid:EXCESSIVE HEAT

Hazardous Decomposition Products: NONE

======= Disposal Considerations ============

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants t his information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.