

MONTANA REFINING CO -- FUEL OIL NO 1 -- 9140-00-242-6751

=====
Product Identification
=====

Product ID:FUEL OIL NO 1

MSDS Date:06/27/1991

FSC:9140

NIIN:00-242-6751

MSDS Number: BPFSG

=== Responsible Party ===

Company Name:MONTANA REFINING CO

Address:1900 10TH ST

City:BLACK EAGLE

State:MT

ZIP:59414-1037

Country:US

Info Phone Num:406-761-4100/800-424-9300(CHEMTREC)

Emergency Phone Num:406-761-4100/

800-424-9300(CHEMTREC)

CAGE:6E335

=== Contractor Identification ===

Company Name:MONTANA REFINING CO

Address:1900 10TH ST

Box:City:GREAT FALLS

State:MT

ZIP:59414-1099

Country:US

Phone:406-761-4100/800-424-9300(CHEMTREC)

CAGE:6E335

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC PETROLEUM SOLVENT/KEROSENE

CAS:8008-20-6

RTECS #:OA5500000

Fraction by Wt: 95 - 99%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:500 PPM (MFR)

ACGIH TLV:300 PPM (MFR)

Ingred Nam

e:NAPHTHALENE (SARA III)
CAS:91-20-3
RTECS #:QJ0525000
Fraction by Wt: 1 - 5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 PPM/15 STEL
ACGIH TLV:10 PPM/15 STEL; 9293
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE-IRRITATION OF EYES,SKIN & MUCOUS
MEMBRANES,DIZZINESS,HEADACHES,RESPIR
ATORY ARREST,COUGHING,IRREGULAR
HEARTBEAT,MENTAL CONFUSION,VOMITING,BLURRED VISION,FLUSHING OF
FACE,BLURRED SPEECH,DIFFICULTY IN
SWALLOWING,WEAKNESS,INSOMNIA,PSYCHOSIS,PAIN IN LIMBS,COMA &
CONVULSIONS.CHRONIC-POSSIBLE CANCER,LIVER,KIDNEY DAMAGE.
Effects of Overexposure:IRRITATION OF EYES, SKIN & MUCOUS MEMBRANES,
DIZZINESS, HEADACHES, RESPIRATORY ARREST, COUGHING, IRREGULAR
HEARTBEAT, MENTAL CONFUSION, VOMITING, BLURRED VISION, FLUSHING OF
FACE, BLURRED SPEECH, DIFF
ICULTY IN SWALLOWING, WEAKNESS,
INSOMNIA, PSYCHOSIS, PAIN IN LIMBS, COMA & CONVULSIONS.
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN
DISORDERS OR EYE PROBLEMS OR IMPAIRED LIVER, KIDNEY OR RESPIRATORY
FUNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THE SUBSTANCE.

=====
===== First Aid Measures =====

First Aid:CALL A PHYSICIAN IN ALL CASES.EYES:IMMEDIATELY FLUSH WITH
WATER FOR 15 MINUTES,HOLDING EYELIDS OPEN.SKIN:WASH WITH
SOAP &
WATER.INHALED:REMOVE TO FRESH AIR & PROVIDE CPR/OXYGEN IF
NECESSARY.ORAL:DO NOT INDUCE VOMITING.CALL A PHYSICIAN
IMMEDIATELY.IF CONSCIOUS,DRINK WATER TO DILUTE.

=====
===== Fire Fighting Measures =====

Flash Point Method:TOC
Flash Point:110F,43C MIN
Autoignition Temp:Autoignition Temp Text:444F
Lower Limits:0.7%
Upper Limits:5.0%
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL AND HALON.
USE WATER TO KEEP FIRE-EXPOSED CONTAINERS CO

OL.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:FUMES, SMOKE, CARBON MONOXIDE, CARBON DIOXIDE IS FORMED. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL GREAT DISTANCE TO AN IGNITION SOURCE & FLASH BACK.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENTS.ELIMINATE ALL

SOURCES OF IGNITION.USE EXPLOSION-PROOF TOOLS.SHUT OFF FUEL SOURCE.DIKE SPILL.PREVENT LIQUID FROM ENTERING SEWERS/WATERWAYS.RECOVER FREE LIQUID.ADD SAND,EARTH OR OTHER ABSORBENT MATERIAL.TRANSFER TOCONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-STORE IN COOL,VENTILATED PLACE AWAY FROM HEAT,FLAME & OXIDIZERS.GROUND ALL EQUIPMENTS & STORAGE CONTAINERS.

Other Precautions:"EMPTY" CONTAINERS RETAIN RESIDUE AND CAN BE

DANGEROUS.DO NOT PRESSURIZE,CUT,WELD,BRAZE,SOLDER,DRILL,GRIND OR EXPOSE SUCH CONTAINERS TO HEAT,FLAME,SPARKS.THEY MAY EXPLODE AND CAUSE INJURY/DEATH.AVOID REPEATED OR PROLONGED CONTACT WITH SKIN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS OR ORGANIC VAPOR RESPIRATOR OR SUPPLIED-AIR RESPIRATOR, IF VAPOR CONCENTRATIONS EXCEED EXPOSURE LIMITS. USE IN WELL

VENTILATED AREA.

Ventilation:LOCAL/MECHANICAL (GENERAL) VENTILATION - EXPLOSION PROOF, WELL GROUNDED EQUIPMENTS

Protective Gloves:RUBBER

Eye Protection:CHEMICAL SPLASH GOGGLES & FACE SHIELD

Other Protective Equipment:IMPERVIOUS CLOTHING TO AVOID SKIN AND EYE CONTACT. EYE WASH STATION & SAFETY SHOWER.

Work Hygienic Practices:AVOID CONTACT WITH EYES, SKIN OR CLOTHING. WASH HANDS AFTER USING PRODUCT. AVOID BREATHING VAPORS OR MISTS.

Supplemental Safety and Health

=====

Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:300F,149C

Vapor Pres:5 @ 100F

Vapor Density:4.5

Spec Gravity:0.8

Solubility in Water:INSOLUBLE

Appearance and Odor:CLEAR TO YELLOW LIQUID - CHARACTERISTIC HYDROCARBON
ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT, SPARKS, OPEN FLAMES AND OTHER
SOURCES OF IGNITION

Hazardous Decom

position Products:FUMES, SMOKE, CARBON MONOXIDE, CARBON
DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:TREATMENT, STORAGE, TRANSPORTATION AND DISPOSAL
MUST BE IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL
LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no ma

nner whatsoever,

expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.