View NSN Online: https://aerobasegroup.gr/nsn/8010-00-721-9751

LHB INDUSTRIES -- SO SURE ALUMINUM 17178 14-160

MSDS Safety Information

FSC: 8010

NIIN: 00-721-9751 MSDS Date: 04/16/1992 MSDS Num: BPFZG

Product ID: SO SURE ALUMINUM 17178 14-160

MFN: 03

Responsible Party Cage: 0FTT5

Name: LHB INDUSTRIES

Address: 8833 FLEISCHER PLACE

City: ST. LOUIS MO 631

34

Info Phone Number: 314-522-3141

Emergency Phone Number: 800-424-9300 CHEMTREC/ 314-522-3141

Preparer's Name: RUDOLF OPPENHEIM

Review Ind: Y Published: Y

Preparer Co. when other than Responsible Party Co.

Cage: 0FTT5

Name: LHB INDUSTRIES

Address: 8833 FLEISCHER PLACE

City: ST. LOUIS MO 63134

Contractor Summary

Cage: 0FTT5

Name: LHB INDUSTRIES

Address: 8833 FLEISCHER PLACE

City: ST. LOUIS MO 63134 Phone: 314-522-3141

Item Description Information

Item Manager: GSA Item Name: ENAMEL

Specification Number: A-A-665D

Unit of Issue: PT UI Container Qty: 0

Ingredients

Cas: 8030-30-6

RTECS #: DE3030000

Name: VM&P NAPHTHA

% Wt: 5.28

Other REC Limits: NONE SPECIFIED

OSHA PEL: 300 PPM ACGIH TLV: 300 PPM

Cas: 108-88-3

RTECS #: XS5250000

Name: TOLUENE (SARA III)

% Wt: 26.62

Other REC Limits: NONE SPECIFIED OSHA PEL: 200 PPM/150 STEL ACGIH TLV: 50 PPM; 9293 EPA Rpt Qty: 1000 LBS DOT Rpt Qty: 1000 LBS

Cas: 67-64-1

RTECS #: AL3150000

Name: ACETONE (SARA III)

% Wt: 30.97 Other REC L

imits: NONE SPECIFIED OSHA PEL: 1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Rpt Qty: 5000 LBS DOT Rpt Qty: 5000 LBS

Cas: 74-98-6

RTECS #: TX2275000 Name: PROPANE

% Wt: 16.72

Other REC Limits: NONE SPECIFIED

OSHA PEL: 1000 PPM ACGIH TLV: 1000 PPM

Cas: 75-28-5

RTECS #: TZ4300000 Name: ISOBUTANE

% Wt: 4.11

Other REC Limits: NONE SPECIFIED OSHA PEL: NOT ESTABLISHED

ACGIH TLV: 800 PPM

Cas: 106-97-8 RTECS #: E J4200000

Name: N-BUTANE

% Wt: 6.58

Other REC Limits: NONE SPECIFIED

OSHA PEL: 800 PPM ACGIH TLV: 800 PPM

RTECS #: 9999999VO Name: VOC: 671 G/L

Other REC Limits: NONE SPECIFIED

Health Hazards Data

Route Of Entry Inds - Inhalation: YES

Skin: YES Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO OSHA: NO

Effects of Exposure: CONCENTRATING & amp; INHALIN

G MAY BE HARMFUL/FATAL.

REPEATED & DOUGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS: PERMANENT BRAIN & PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS: PERMANENT BRAIN & PROLONGED SYS DAMAGE. IN CONFINED AREAS VAPOR IN HIGH CONC ARE ANESTHETIC. IR RIT TO SKIN & PROLONGED TRACT. LIGHT HEADEDNESS, STAGGERING, GIDDINESS, NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION.

Signs And Symptions Of Overexposure: IRRITATION TO EYES, THROAT AND RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA AND VOMITING.

Medical Cond Aggravated By Exposure: RESPIRATORY AI

LMENTS.

First Aid: FOR CONTACT WITH SKIN OR CLOTHES, WASH WITH SOAP & LOTHER; WASH CLOTHES BEFORE REUSE. FOR CONTACT WITH EYES, FLUSH WITH WATER FOR 15 MINUTES & LOTHER PHYSICIAN/OPHTHAMOLOGIST IMMEDIATELY. IF SWALLOWED, DO NOT INDUCE VOMITING. GET IMMEDIATEMEDICAL AID. IF INHALED, REMOVE TO FRESH AIR AND GIVE ARTIFICIAL RESPIRATION IF NECESSARY AND GET MED AID. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

Handling and Disposal

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA. MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE & DESCRIPTION OF STATE & DISPOSAL REGULATIONS. DO NOT PUNCTURE, INCINERATE OR STORE ABOVE 120F. EXPOSURE TO HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE BURSTING. DISCARD EMPTY CAN IN TRASH PICK-UP. DON'T PLACE IN HOME TRASHCOMPACTOR.

Handling

And Storage Precautions: KEEP OUT OF REACH OF CHILDREN!

CAUTION-CONTENTS UNDER PRESSURE. DO NOT STORE ABOVE 120F. AVOID BREATHING SPRAY, MIST OR VAPOR.

Other Precautions: AVOID CONTACT WITH EYES AND SKIN. USE WITH GOOD VENTILATION.
READ ENTIRE LABEL BEFORE USING. FOLLOW ALL LABEL DIRECTIONS. INTENTIONAL
MISUSE BY DELIBERATELY CONCENTRATING & amp; INHALING OR SWALLOWING CONT ENTS
MAY BE HARMFUL OR FATAL.

Fire and Explosion Hazard In

formation

Flash Point Text: NR

Autoignition Temp Text: 874 F

Lower Limits: 1.8 Upper Limits: 9.5

Extinguishing Media: CO2, DRY CHEMICAL, FOAM, SAND, WATER SPRAY. AVOID

SPREADING ANY BURNING LIQUID WITH WATER SPRAY.

Fire Fighting Procedures: WATER MAY BE INEFFECTIVE, USE TO KEEP FIRE EXPOSED CONTAINER COOL. WEAR SCBA. USE SHIELDING TO PROTECT PERSONNEL AGAINST BURSTING, RUPTURING, VENTING OF CNTNRS.

Unusual Fire/Explosion Hazard: DON'

T SPRAY NEAR OPEN FLAME. AT ELEVATED

TEMPERATURES (OVER 120F) CONTAINERS MAY VENT RUPTURE OR BURST. AEROSOL CONTAINERS; DO NOT EXPOSE TO TEMPS ABOVE 120F.

Control Measures

Respiratory Protection: NONE BELOW TLV. USE NIOSH/MSHA APPROVED MASK ABOVE TLV. Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL (GENERAL): ACCEPTABLE AT POINT OF MIST OR SPRAY RELEASE.

Protective Gloves: TO PROTECT SKIN.

Eye Protection: CHEMICAL SPLASH GOGGLES.

Other Protective Equipment: IMPERVIOUS CLOTHING TO PROTECT SKIN. EYE WASH STATION.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DO NOT EAT, DRINK OR SMOKE WHILE USING PRODUCT.

Physical/Chemical Properties

HCC: V3

Vapor Pres: 60 @ 68F Vapor Density: >1.5

Spec Gravity: 0.848 (WATER=1) Solubility in Water: INSOLUBLE

App

| Reactivity Data |
|--|
| Stability Indicator: YES Stability Condition To Avoid: EXTREME HEAT. Hazardous Decomposition Products: CARBON MONOXIDE, AND POSSIBLE HYDROGEN CHLORIDE. Hazardous Polymerization Indicator: NO |
| Toxicological Information |
| ==== |
| Ecological Information |
| MSDS Transport Information |
| Regulatory Information |
| |
| Transportation Information |
| Responsible Party Cage: 0FTT5 Trans ID NO: 83198 Product ID: SO SURE ALUMINUM 17178 14-160 MSDS Prepared Date: 04/16/1992 Review Date: 09/08/1992 MFN: 3 Multiple KIT Number: 0 Review IND: Y Unit Of Issue: PT Container QTY: 0 |
| Detail DOT Information |
| |

earance and Odor: ALUMINUM / PAINT

DOT PSN Code: DTJ

Symbols: D

DOT Proper Shipping Name: CONSUMER COMMODITY

Hazard Class: ORM-D

Label: NONE

Non Bulk Pack: 156,306

Bulk Pack: NONE

Max Qty Pass: 30KGGROSS Max Qty Cargo: 30KGGROSS

Vessel Stow Req: A

Detail IMO Information

IMO PSN Code: AKH

IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT?

IMDG Page Number: SEE 9022

UN Number: 19

50

UN Hazard Class: 9? IMO Packaging Group: -Subsidiary Risk Label: -EMS Number: 2-13

Detail IATA Information

IATA PSN Code: ALS IATA UN ID Num: 1950

IATA Proper Shipping Name: AEROSOLS, FLAMMABLE IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)

IATA UN Class: 2.1

IATA Label: FLAMMABLE GAS Packing Note Passenger: 203

Max Quant Pass: 75KG Max Quant Cargo: 150KG Packaging Note Car

go: 203

Detail AFI Information

AFI PSN Code: ALS

AFI Proper Shipping Name: AEROSOLS, NONFLAMMABLE, N.O.S.

AFI PSN Modifier: CONTAINING SUBSTANCES IN CLASS 8, PACKING GROUP I OR II

AFI Hazard Class: FORB

Back Pack Reference: FORBIDDEN

HAZCOM Label

Product ID: SO SURE ALUMINU

M 17178 14-160 Cage: 0FTT5

Company Name: LHB INDUSTRIES Street: 8833 FLEISCHER PLACE

City: ST. LOUIS MO Zipcode: 63134

Health Emergency Phone: 800-424-9300 CHEMTREC/ 314-522-3141

Label Required IND: Y

Date Of Label Review: 12/16/1998

Status Code: C

Label Date: 12/16/1998 Origination Code: G

Hazard And Precautions: CONCENTRATING & amp; INHALING MAY BE HARMFUL/FATAL.

REPEATED & amp; PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS: PERMANENT

BRAIN & amp: NERVOUS SYS DAMAGE. IN CONFINED AREAS VAPOR

IN HIGH CONC ARE

ANESTHETIC. IR RIT TO SKIN & DESP TRACT. LIGHT HEADEDNESS, STAGGERING, GIDDINESS, NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION. IRRITATION TO EYES, THROAT AND RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA AN D VOMITING.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense.

The United States of America i

n no manner whatsoever expressly or implied

warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify

and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.