

MAPCO ALASKA PETROLEUM INC -- NO. 2 FUEL OIL (-15) -- 9140-00-247-4365

=====  
Product Identification  
=====

Product ID:NO. 2 FUEL OIL (-15)

MSDS Date:05/28/1992

FSC:9140

NIIN:00-247-4365

MSDS Number: BPKKZ

=== Responsible Party ===

Company Name:MAPCO ALASKA PETROLEUM INC

Address:1076 OCEAN DOCK RD

City:ANCHORAGE

State:AK

ZIP:99705

Country:US

Info Phone Num:907-456-2424

Emergency Phone Num:907-488-0

037,907-456-2424

CAGE:3X619

=== Contractor Identification ===

Company Name:MAPCO ALASKA PETROLEUM INC (H&H LANE)

Address:1076 OCEAN DOCK RD

Box:City:ANCHORAGE FORMERLY IN NORTH POLE, AK

State:AK

ZIP:99705

Country:US

Phone:907-488-0037

CAGE:3X619

=====  
Composition/Information on Ingredients  
=====

Ingred Name:FUEL OIL NO. 2

Other REC Limits:NONE SPECIFIED

Ingred Name:BENZENE (SARA III)

CAS:71-43-2

RTECS #:CY1400000

Fraction by Wt: 0.14%

Other REC Limits:NONE SPECIFIED

OSHA PE

L:1PPM/5STEL;1910.1028  
ACGIH TLV:10 PPM; A2; 9293  
EPA Rpt Qty:10 LBS  
DOT Rpt Qty:10 LBS

Ingred Name:NAPHTHELENE (SARA III)  
CAS:91-20-3  
RTECS #:QJ0525000  
Fraction by Wt: 0.55%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:10 PPM/15 STEL  
ACGIH TLV:10 PPM/15STEL 9293  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

Ingred Name:1,2,4 TRIMETHYLBENZENE (SARA III)  
CAS:95-63-6  
RTECS #:DC3325000  
Fraction by Wt: 0.01%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:25 PPM  
ACGIH TLV:25 PPM 9293

Ingred Name:TOLUENE  
(SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 0.26%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P-ISOMERS) (SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 0.24%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150 STEL 93  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III)  
CAS:100-41-4  
RTECS #:DA0700000  
Fraction b

y Wt: 0.04%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM/125 STEL  
ACGIH TLV:100 PPM/125 STEL;93  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: PROLONGED  
CONTACT MAY RESULT IN IRRITATION AND DERMATITIS. INHALATION: HIGH  
CONCENTRATIONS MAY CAUSE NOSE, THROA  
T AND RESPIRATORY IRRITATION,  
DIZZINESS, AND POSSIBLY UNCONSCIOUSNESS.  
Explanation of Carcinogenicity:NIOSH FINDINGS SUGGEST "POTENTIAL  
OCCUPATIONAL CARCINOGENIC HAZARD EXISTS IN HUMAN EXPOSURE TO DIESEL  
EXHAUST."  
Effects of Overexposure:EYES: IRRITATION. SKIN: IRRITATION, DERMATITIS.  
INHALATION: NOSE, THROAT AND RESPIRATORY IRRITATION, DIZZINESS,  
UNCONSCIOUSNESS. INGESTION: NAUSEA, VOMITING, DIARRHEA.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. GET MEDICAL  
ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH AREA WITH SOAP  
AND WATER. INHALATION: MOVE TO FRESH AIR. IF NOT BREATHING GIVE  
CPR. IF BREATHING DIFFICULT GIVE OXYGEN. GET MEDICAL ATTENTION.  
INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point Method:PMCC  
Flash  
Point:100F,38C  
Lower Limits:0.9  
Upper Limits:6.0  
Extinguishing Media:FOAM, WATER FOG, CARBON DIOXIDE, OR DRY CHEMICAL.  
Fire Fighting Procedures:USE WATER TO KEEP FIRE EXPOSED CONTAINERS  
COOL. IF SPILL HAS NOT IGNITED, USE WATER SPRAY TO DISPERSE VAPORS  
AND PROVIDE PROTECTION FOR MEN TRYING TO STOP LEAK.  
Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND MAY  
TRAVEL ALONG GROUND A LONG DISTANCE TO AN IGNITION SOURCE AND  
BACKFLASH.

=====  
===== Accidental Release

Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. STOP LEAK. CONTAIN SPILL BY DIKING IF POSSIBLE.VENTILATE AREA. KEEP PRODUCT OUT OF SEWERS AND WATERWAYS. ABSORB ON VERMICULITE, SAND, CLAY, EARTH OR OTHER ABSORBENT AND TRANSFER TO HOOD OR SHOVEL INTO CONTAINERS FOR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT HANDLE OR STORE NEAR FLAME, HEAT, SPARKS, OR STRONG OXIDANTS.STORAGE AREA SHOULD BE WELL VENTILATED. AVOID BREATHING VAPORS.

Other Precautions:STORE AS NFPA CLASS II LIQUID.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN CONFINED AREAS USE FULL FACE MASK EQUIPPED WITH HYDROCARBON VAPOR CANISTER OR SELF-CONTAINED BREATHING APPARATUS.

Ventilation:PROVIDE SUFFICIENT MECHANICAL/LOCAL EXHAUST VENTILATION TO KEEP BELOW RECOMMENDED TLV/PEL AND EXPLOSIVE LIMITS.

Protective Gloves:CHEMICAL RESISTANT.

Eye Protection:CHEMICAL SPLASH GOGGLES OR FACE SHIELD.

Other Protective Equipment:CHEMICAL RESISTANT APRON IN CASE OF POSSIBLE ANTICIPATED SKIN CONTACT.

Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:300F,149C

Vapor Pres:1-2

Vapor

Density:8

Spec Gravity:0.842

Evaporation Rate & Reference:0.04 (N-BUTYLACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR, WATER WHITE TO LIGHT STRAW LIQUID. DIESEL FUEL ODOR.

Percent Volatiles by Volume:100%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS LIKE CHLORINE, HYPOCHLORITES, CONCENTRATED OXYGEN.

Stability Condition to Avoid:HEAT, SPARKS, FLAMES, IGNITION SOURCES.

Haza

rdous Decomposition Products:FUMES, SMOKE, AND CARBON MONOXIDE IN  
CASE OF INCOMPLETE COMBUSTION.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:CONTACT YOUR LOCAL ENVIRONMENTAL OFFICER.  
DISPOSE OF WASTE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the

Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.