View NSN Online: https://aerobasegroup.gr/nsn/5330-00-197-8490

RM ENGINEERED PRODUCTS INC -- RM 303 -- 5330-00-197-8490

Product ID:RM 303 MSDS Date:09/01/1991

FSC:5330

NIIN:00-197-8490

MSDS Number: BPQRD === Responsible Party ===

Company Name: RM ENGINEERED PRODUCTS INC

Address:4854 O HEAR AVE

Box:5205

City: NORTH CHARLESTON

State:SC ZIP:29406 Country:US

Info Phone Num:803-744-6261

Emergency Phone Num:803-744-6261

Preparer's N

ame:E.K. HASSON

CAGE:0DCP7

=== Contractor Identification ===

Company Name: R M ENGINEERED PRODUCTS, INC.

Address:4854 O'HEAR AVENUE Box:City:NORTH CHARLESTON

State:SC ZIP:29405 Country:US

Phone:843-744-6261

CAGE:10009

Company Name: RM ENGINEERED PRODUCTS INC

Address:4854 O HEAR AVE Box:City:NORTH CHARLESTON

State:SC ZIP:29406 Country:US

Phone:803-744-6261

CAGE:0DCP7

======= Composition/Information on Ingredients ========

Ingred Name: ASBESTOS, CHRYSOTILE

CAS:12001-29-5 RTECS #:CI6478 500

Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:2 FIBERS/CC; A1;9293

Ingred Name: GRAPHITE, SYNTHETIC

CAS:7440-44-0

RTECS #:FF5250100

Other REC Limits: NONE RECOMMENDED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:2 MG/M3 TDUST; 9293

Ingred Name:ZINC (SARA III)

CAS:7440-66-6

RTECS #:ZG8600000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:10 MG ZNO/M3

ACGIH TLV:10 MG ZNO/M3; 9293

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

========== Hazards Identification ===========

===

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Health Hazards Acute and Chronic:ACUTE:MINOR EYS/SKIN IRRITATION.

INGESTION- IRRITATION OF GI TRACT. INHALATION-IRRITATION OF RESPIRATORY TRACT. CHRONIC: ASBESTOSIS, LUNG CANCER, &

MESOTHELIOMA, ALL OF WHICH ARE DISABLING AND FATAL D ISEASES OF THE LUNG. INHALATION AND INGESTION OF ASBESTOS FIBERS MAY CAUSE CANCER

OF THE BOWEL.

Explanation of Carcinogenicity:A

SBESTOS IS A KNOWN HUMAN CARCINOGEN.


Effects of Overexposure:INHALATION: FATIGUE AND SHORTNESS OF BREATH THAT GETS WORSE WITH TIME AND EVENTUALLY BECOMES DISABLING. EYES:

IRRITATION. SKIN: IRRITATION. INGESTION: MILD STOMACH DISTRESS.

DIARRHEA, VOMITING, AND NA USEA.

Medical Cond Aggravated by Exposure: ASTHMA, EMPHYSEMA, AND TUBERCULOSIS ARE ALL GENERALLY AGGRAVATED BY EXPOSURE TO ASBESTOS FIBERS.

First Aid:IN



Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures: EVACUATE NON-ESSENTIAL PERSONNEL. WEAR FIRE

FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard: COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

======== Accidental Release Measures ============

Spill Release Procedures: VACUUM THE MATERIAL WITH A HEPA FILTERED VACUUM. THE EQUIPMENT SHALL BE USED & EMPTIED SO AS TO MINIMIZE THE RE-ENTRY OF ASBESTOS INTO THE WORKPLACE. OTHERWISE, WET THE MATERIAL W

ITH WATER & SURFACTAN T AND THEN SHOVEL OR MOP UP CONTAMINATION.

============ Handling and Storage ===============

Handling and Storage Precautions:ITEM IS NONFRIABLE & WILL NOT SHED FIBERS IN NORMAL USE AND STORAGE. USED ITEMS SHALL BE WETTED BEFORE, DURING & AFTER DISASSEMBLY.

Other Precautions:IF IT IS NECESSARY TO CUT OR IMPACT THE ITEM WHILE INSTALLING IT, WEAR A RESPIRATOR AND PROTECTIVE CLOTHING. USED ITEMS SHALL BE IDENTIFIED AND DISPOSED OF IN ACC ORDANCE WITH ALL

LOCAL, STATE AND FEDE RAL REGULATIONS.

====== Exposure Controls/Personal Protection ========

Respiratory Protection:WEAR A NIOSH/MSHA APPROVED HEPA RESPIRATOR IF REQUIRED. WEAR SELF-CONTAINED BREATHING APPARATUS IF REQUIRED FOR HIGH LEVELS OF CONTAMINATES.

Ventilation:LOCAL EXHAUST SUFFICIENT TO ENTRAIN ALL PARTICULATE EMISSIONS. HEPA FILTER REQUIRED. NO LEAKS ON PRESSURE SIDE OF FAN.

Protective Gloves: COTTON OR LEATHER

Eye Protection: SAFETY GLASS

ES OR GOGGLES

Other Protective Equipment:USE COVERALLS OR DISPOSABLE CLOTHING.
Work Hygienic Practices:WET WORK TO THE DEGREE POSSIBLE. WASH HANDS
AFTER HANDLING ITEM. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health

======== Physical/Chemical Properties ===========

HCC:T6

Solubility in Water: INSOLUBLE

Appearance and Odor: GREY SOLID, NO ODOR

Percent Volatiles by Volume:0

======== Stability and Reactivity Data =========

Stabi

lity Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS, AND STRONG ALKALIS Stability Condition to Avoid:ACCUMULATIONS OF DUST

Hazardous Decomposition Products:OXIDES OF CARBON, AND OTHER POSSIBLE TOXIC DECOMPOSITION FUMES.

======= Disposal Considerations ===========

Waste Disposal Methods:WET THE MATERIAL WITH WATER AND SURFACTANT. PLACE IN 6 MIL THICK POLYETHYLENE PLASTIC BAG. PLACE THESE BAGS INTO ANOTHER POLY BAG OR A SAFE PLA

CE UNTIL IT CAN BE SHIPPED TO AN

APPROVED DISPOSAL SITE. IDENTIFY WITH ASBESTOS CANCER WARNING LABEL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.