

KANSAS PAINT AND COLOR -- 22W10 WHITE LUSTERLESS;PART C OF 3 PARTS --
1730-00-079-2931

===== Product Identification =====

Product ID:22W10 WHITE LUSTERLESS;PART C OF 3 PARTS

MSDS Date:08/20/1990

FSC:1730

NIIN:00-079-2931

Kit Part:Y

MSDS Number: BPRBW

=== Responsible Party ===

Company Name:KANSAS PAINT AND COLOR

Address:132 N. MOSLEY ST.

City:WICHITA

State:KS

ZIP:67202

Country:US

Info Phone Num:316

-264-6353

Emergency Phone Num:(800)424-9300

Chemtrec Ind/Phone:(800)424-9300

CAGE:GO379

=== Contractor Identification ===

Company Name:KANSAS PAINT & COLOR COMPANY

Address:132 NORTH MOSLEY

Box:City:WICHITA

State:KS

ZIP:67202

Phone:(316) 264-6353

CAGE:68338

Company Name:KANSAS PAINT AND COLOR

Address:132 N MOSLEY ST

City:WICHITA

State:KS

ZIP:67202

Country:US

Phone:316-264-6353

CAGE:GO379

Company Name:WECKWORTH MFG INC (316-263-3286)

CAGE:9J595

===== Composition/Information on Ingredient

S =====

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 15%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 1%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:435 PPM/150STEL;9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:MINERAL SPIRITS
CAS:64742-88-7
Fraction by Wt: 35%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:500 PPM

Ingred Name:TOTAL VOLATILE ORGANIC COMPOUNDS(INCLUDING THOSE PREVIOUSLY LISTED)
RTECS #:9999999VO
Fraction by Wt: 46%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:SKIN AND EYE IRRITATION.
CHRONIC:DERMATITIS MAY DEVELOP FROM S

KIN IRRITATION. EYE

IRRITATION. MANUFACTURER FURTHER STATES THAT PROLONGED, REPEATED INHALATION MAY CAUSE DELAYED INJURIES.

Explanation of Carcinogenicity: THERE ARE NO INGREDIENTS AT 0.1% OR GREATER IN THIS ITEM WHICH ARE CONFIRMED OR SUSPECTED CARCINOGENS.

Effects of Overexposure: EYE: TEARING. SKIN: REDNESS, DRYNESS, POSSIBLE BLISTERING. INHAL: DIZZINESS, HEADACHE, DROWSINESS. MAY PRODUCE ANESTHETIC OR OTHER CENTRAL NERVOUS SYSTEM EFFECTS.

Medical Cond Aggravated by Exposure: INTENTIONAL MISUSE BY CONCENTRATING

AND INHALING CONTENTS MAY CAUSE PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE OR DEATH.

=====
===== First Aid Measures =====

First Aid: SKIN: REMOVE CONTAMINATED CLOTHING; WASH WITH WATER. GET MEDICAL HELP. EYES: FLUSH WITH WATER. GET MEDICAL HELP. INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN FOR DIFFICULTY IN BREATHING. RESCUCITATE BY MOUTH IF NOT BREATHING. GET MEDICAL HELP. INGEST: DO NOT INDUCE VOMITING; ASPIRATION HAZARD. SEEK MEDICAL HELP IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point: 102F, 39C

Lower Limits: 0.8

Extinguishing Media: FOAM, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures: MANUFACTURER SUGGESTS THE USE OF A SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard: MANUFACTURER WARNS THAT THIS MATERIAL CAN BE IGNITED UNDER ALMOST ALL AMBIENT TEMPERATURE CONDITIONS.

=====
===== Accidental Release Measures =====

==

Spill Release Procedures: CONFINE THE SPILL QUICKLY. VENTILATE THE AREA; ELIMINATE SOURCES OF IGNITION. ABSORB WITH AN OIL ADSORBANT; SCOOP UP FOR DISPOSAL.

Neutralizing Agent: NONE APPLICABLE.

=====
===== Handling and Storage =====

Handling and Storage Precautions: KEEP CONTAINERS CLOSED WHEN NOT IN USE. KEEP AWAY FROM FLAMES, HEAT, SPARKS AND OXIDIZERS. GROUND CONTAINERS IAW NFPA STANDARDS TO AVOID STATIC BUILDUP.

Other Precautions: NONE.

=====

= Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH DUST AND VAPOR RESPIRATOR IS RECOMMENDED, ESPECIALLY IN CONFINED AREAS.

Ventilation:MANUFACTURER SUGGEST LOCAL EXHAUST >60FPM OR MECHANICAL VENTILATION.

Protective Gloves:CHEMICAL RESISTANT GLOVES

Eye Protection:USE A FACE SHIELD.

Other Protective Equipment:MANUFACTURER SUGGEST CHEMICALLY RESISTANT APRON OVER CLOTHING.

Work Hygienic Practices:AVOID PROLONGED/REPEATED CONTACT.LAUNDER CONTAMINATED

CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING.

Supplemental Safety and Health

KEY1:F4.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:307F,153C

Vapor Pres:3.4

Vapor Density:>1

Spec Gravity:1.19

Solubility in Water:NEGLIGIBLE

Appearance and Odor:ALIPHATIC,OPAQUE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAMES, STATIC

DISCHARGE.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, wa

arrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.