

GERARD PACKING AND BELTING CORP -- MILA7021C -- 5330-00-599-4521

=====  
Product Identification  
=====

Product ID:MILA7021C

MSDS Date:01/25/1993

FSC:5330

NIIN:00-599-4521

MSDS Number: BPVBV

=== Responsible Party ===

Company Name:GERARD PACKING AND BELTING CORP

Address:24 MIDLAND AVE

City:HICKSVILLE

State:NY

ZIP:11801

Country:US

Info Phone Num:516-935-2400

Emergency Phone Num:516-935-2400

Preparer's N

ame:HMIS TECHNICIAN

CAGE:2G277

=== Contractor Identification ===

Company Name:GERARD PACKING AND BELTING CORP

Address:24 MIDLAND AVENUE

Box:City:HICKSVILLE

State:NY

ZIP:11801

Country:US

Phone:516-935-2400

CAGE:2G277

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ASBESTOS, CHRYSOTILE

CAS:12001-29-5

RTECS #:CI6478500

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:2 FIBERS/CC; A1;9293

Ingred Name:RUBBER

Other REC Limits:NONE RECOMMENDED

====

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Hazards Acute and Chronic:ACUTE:MINOR EYS/SKIN IRRITATION.  
INGESTION- IRRITATION OF GI TRACT. INHALATION-IRRITATION OF  
RESPIRATORY TRACT. CHRONIC: ASBESTOSIS, LUNG CANCER, &  
MESOTHELIOMA, ALL OF WHICH ARE DISABLING AND FATAL D ISEASES OF THE  
LUNG. INHALATION AND INGESTION OF ASBESTOS FIBERS MAY CA  
USE CANCER  
OF THE BOWEL.  
Explanation of Carcinogenicity:ASBESTOS IS A KNOWN HUMAN CARCINOGEN.  
Effects of Overexposure:INHALATION: FATIGUE AND SHORTNESS OF BREATH  
THAT GETS WORSE WITH TIME AND EVENTUALLY BECOMES DISABLING. EYES:  
IRRITATION. SKIN: IRRITATION. INGESTION: MILD STOMACH DISTRESS.  
DIARRHEA, VOMITING, AND NA USEA.  
Medical Cond Aggravated by Exposure:ASTHMA, EMPHYSEMA, AND TUBERCULOSIS  
ARE ALL GENERALLY AGGRAVATED BY EXPOSURE TO ASBESTOS FIBERS.

=====  
== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. SEE DOCTOR. EYES: RINSE  
THOROUGHLY WITH WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: WASH  
THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEE DOCTOR.  
INGESTION: DIL UTE WITH WATER. DO NOT INDUCE VOMITING.SEE DOCTOR.

=====  
===== Fire Fighting Measures =====

Flash Point:NOT REQUIRED  
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY  
CHEMICAL.  
Fir  
e Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A  
FULL FACED SELF CONTAINED BREATHING APPARATUS.  
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE  
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:VACUUM THE MATERIAL WITH A HEPA FILTERED  
VACUUM. THE EQUIPMENT SHALL BE USED & EMPTIED SO AS TO MINIMIZE THE  
RE-ENTRY OF ASBESTOS INTO THE WORKPLACE. OTHERWISE,

WET THE  
MATERIAL WITH WATER & SURFACTANT AND THEN SHOVEL OR MOP UP  
CONTAMINATION.

===== Handling and Storage =====

Handling and Storage Precautions:ITEM IS NONFRIABLE & WILL NOT SHED  
FIBERS IN NORMAL USE AND STORAGE. USED ITEMS SHALL BE WETTED  
BEFORE, DURING & AFTER DISASSEMBLY.

Other Precautions:IF IT IS NECESSARY TO CUT OR IMPACT THE ITEM WHILE  
INSTALLING IT, WEAR A RESPIRATOR AND PROTECTIVE CLOTHING. USED  
ITEMS SHALL BE IDENTIFIED  
AND DISPOSED OF IN ACCORDANCE WITH ALL  
LOCAL, STATE AND FEDERAL REGULATIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A NIOSH/MSHA APPROVED HEPA RESPIRATOR IF  
REQUIRED. WEAR SELF-CONTAINED BREATHING APPARATUS IF REQUIRED FOR  
HIGH LEVELS OF CONTAMINATES.

Ventilation:LOCAL EXHAUST SUFFICIENT TO ENTRAIN ALL PARTICULATE  
EMISSIONS. HEPA FILTER REQUIRED. NO LEAKS ON PRESSURE SIDE OF FAN.

Protective Gloves:COTTON OR LEATHER

Eye

Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:USE COVERALLS OR DISPOSABLE CLOTHING.

Work Hygienic Practices:WET WORK TO THE DEGREE POSSIBLE. WASH HANDS  
AFTER HANDLING ITEM. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

MSDS GENERATED BY HMIS TECHNICIAN. WHEN HMIS IS ABLE TO OBTAIN AN MSDS  
FROM MANUFACTURER, THIS RECORD WILL BE UPDATED. INGREDIENTS ARE  
FROM DLSC TIR PART M OR PARTSMASER TECHNICAL CHARACTERISTICS AND  
NAME.

===== Physical/Chemical Properties =====

HCC:T6

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK, RUBBER AND ASBESTOS SHEET

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS, AND STRONG ALKALIS

Stability Condition to Avoid:ACCUMULATIONS OF DUST

Hazardous Decomposition Products:ASBESTOS DUST

===== Disposal Considerat

ions =====

Waste Disposal Methods:WET THE MATERIAL WITH WATER AND SURFACTANT.  
PLACE IN 6 MIL THICK POLYETHYLENE PLASTIC BAG. PLACE THESE BAGS  
INTO ANOTHER POLY BAG OR A SAFE PLACE UNTIL IT CAN BE SHIPPED TO AN  
APPROVED DISPOSAL SITE. IDENTIFY WITH ASBESTOS CANCER WARNING  
LABEL.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America i  
n no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.