

AMERICAL BRAIDING AND MFR CORP -- 340, 340BIL; PACKING MATERIAL -- 5330-00-224-0868  
===== Product Identification =====

Product ID:340, 340BIL; PACKING MATERIAL

MSDS Date:03/01/1991

FSC:5330

NIIN:00-224-0868

MSDS Number: BPVMX

=== Responsible Party ===

Company Name:AMERICAL BRAIDING AND MFR CORP

Address:247 OLD TAVERN ROAD

City:HOWELL

State:NJ

ZIP:07731

Country:US

Info Phone Num:908-938-6333

Emerge

ncy Phone Num:908-938-6333

CAGE:KO672

=== Contractor Identification ===

Company Name:AMERICAL BRAIDING AND MFR CORP

Address:247 OLD TAVERN ROAD

Box:City:HOWELL

State:NJ

ZIP:07731

Country:US

Phone:908-938-6333

CAGE:KO672

Company Name:AMERICAN BRAIDING AND MFG CORP

Address:247 OLD TAVERN ROAD

Box:City:HOWELL

State:NJ

ZIP:07731

Country:US

Phone:732-938-6333 ...FAX 6377

CAGE:4R345

===== Composition/Information on Ingredients =====

Ingred Name:ASBESTOS, CHRYSOTILE

CAS:12001-29-5

RTECS #:CI6478500  
OSHA PEL:0.2 FIBERS/CC  
ACGIH TLV:2 FIBERS/CC; A1;9192

Ingrid Name:POLYTETRAFLUOROETHYLENE (PTFE, TEFLON)  
Other REC Limits:NONE RECOMMENDED

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Hazards Acute and Chronic:ACUTE: NO ACUTE EFFECTS ARE KNOWN;  
CHRONIC: DUST FROM ABRASIVE ACTIONS(EG. CUTTING, MACHINING, FILING,  
ETC.) MAY CONTAIN ASBESTOS FIBERS. CHRONIC OVEREXPOSURE TO AIRBORNE  
FIBERS MAY LEAD TO ASBESTOSIS & MESOTHELIOMA. SMOKING COMBINED  
W/FIBER INHALATION GREATLY INCREASES LUNG CANCER RISK!  
Explanation of Carcinogenicity:ASBESTOS, CHRYSOTILE IS LISTED BY NTP  
AND IARC AS A CARCINOGEN, AND IS REGULATED BY OSHA.  
Effects of Overexposure:INHALATION/SKIN: N/K; EYE: POTENTIAL IRRITATION  
FROM AIRBORNE DUST; INGEST: N/K.  
Medical Cond Aggravated by Exposure:RESPIRATORY DISEASES.

=====  
First Aid Measures  
=====

First Aid:INHAL: REMOVE TO FRESH AIR. OBTAIN MEDICAL ADVICE; SKIN: WASH  
EXPOSED AREA WITH SOAP & WATER; EYE: FLOOD W/ WATER. IF IRRITATION  
OCCURS, GET MEDICAL ATTN; INGEST: CONSULT A PHYSICIAN; OTHER:  
CHANGE CLOTHING AS REQUIRED TO AVOID CARRYING DUST PARTICLES INTO  
OTHER AREAS

=====  
Fire Fighting Measures  
=====

Flash Point:NONE  
Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.  
Fire Fighting Procedures:COMBUSTION PRODUCTS OF THIS MATERIAL MAY BE  
TOXIC. USE A SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES  
INVOLVING CHEMICAL PRODUCTS.  
Unusual Fire/Explosion Hazard:SOME OIL MAY WEEP FROM FINISHED PRODUCT  
IN FIRE AND CATCH FIRE.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION. VACUUM OR WET  
CLEAN IF DUST IS INVOLVED. VACUUM SYSTEM SHOULD BE EQUIPPED W/ AN  
OUTLET "HEPA" FILTER

TO PREVENT REINTRODUCING ASBESTOS FIBERS TO THE ATMOSPHERE.

==== Handling and Storage =====

Handling and Storage Precautions:HANDLE IN A MANNER TO MINIMIZE FORMATION OR RETENTION OF AIRBORNE DUST. USE PROPER PERSONAL PROTECTION FOR TASK AT HAND. CHECK W/YOUR SAFETY OFFICE!!!  
Other Precautions:AS MANUFACTURED, LOCKED-IN ASBESTOS DOES NOT PRESENT A HAZARD. ONLY WHEN THE ITEM IS SUBJECTED TO ABRASIVE ACTIONS & DUST IS GENERATED, THEN ASBESTOS FIBERS MAY BE RELEASED & BECOME AIRBORNE.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURES EXCEED ESTABLISHED LIMITS, A NIOSH APPROVED RESPIRATOR FOR ASBESTOS SHOULD BE USED. CONSULT YOUR SAFETY OFFICE/IH PERSONNEL FOR GUIDANCE FOR THE TASK AT HAND.  
Ventilation:LOCAL EXHAUST IS RECOMMENDED IN SITUATIONS WHERE DUST IS GENERATED BY ABRASIVE ACTIONS, ABRASION OR OTHER MEANS.  
Protective Gloves:AS REQUIRED FOR TASK AT HAND.  
Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES  
Other Protective Equipment:AS REQUIRED FOR TASK AT HAND, AND THE GUIDANCE SET FORTH BY YOUR SAFETY OFFICE OR IH PERSONNEL  
Work Hygienic Practices:DONOT INHALE DUST CREATED BY ABRASING ACTIONS. USE FULL PROTECTION AGAINST AIRBORNE FIBERS. AVOID CREATING AIRBORNE DUST  
Supplemental Safety and Health

==== Physical/Chemical Properties =====

HCC:T6  
Spec Gravity:1.5  
Evaporation Rate & Reference:NONE  
Solubility in Water:INSOLUBLE  
Appearance and Odor:WHITE TO GREYISH SHINY ROPE.  
Percent Volatiles by Volume:NONE

==== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
NONE KNOWN  
Stability Condition to Avoid:TEMPERATURES ABOVE 600F

==== Disposal Considerations =====

Waste Disposal Methods:DUST SHOULD BE HANDLED AS A HAZARDOUS AIR POLLUTANT I/A/W 40CFR61 SUBPART "M" PERTAINING TO ASBESTOS. USE LANDFILL

LS APPROVED FOR ASBESTOS DISPOSAL. NOTE IF ITEM UNDER  
CONSIDERATION FOR DISPOSAL IS "FRIABLE OR NON-FRIABLE".

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional  
advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.