View NSN Online: https://aerobasegroup.gr/nsn/8010-01-060-7176

Product ID: EPON (R) RESIN 828 MSDS Date:11/03/1989 FSC:8010 NIIN:01-060-7176 Kit Part:Y MSDS Number: BQDNW === Responsible Party === Company Name: SHELL CHEMICAL COMPANY A DIV. OF SHELL OIL CO. Address:1 SHELL PLAZA Box:2463 **City:HOUSTON** State:TX ZIP:77001 Country:US Info Phon e Num:713-241-4819 Emergency Phone Num:713-473-9461 Preparer's Name: J C WILLETT CAGE:86961 === Contractor Identification === Company Name: SHELL CHEMICAL COMPANY A DIV. OF SHELL OIL CO. Address:1 SHELL PLAZA Box:2463 City:HOUSTON State:TX ZIP:77001 Country:US Phone:713-473-9461 CAGE:86961

Ingred Name:BISPHENOL A/EPICHLOROHYDRIN EPOXY RESIN CAS:25068-38-6 RTECS #:KC2100000 Fraction by Wt: 100% Other REC Limits:NONE SPECIFIED

=

LD50 LC50 Mixture:ACUTE ORAL LD50: 11.4 G/KG (RAT) Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE: MODERATELY IRRITATING TO EYES. CONTACT WITH PRODUCT AT ELEVATED TEMPERATURES CAN RESULT IN THERMAL BURNS. SKIN: MODERATELY IRRITATING, SENSITIZATION. CONTACT W/PRODUCT AT ELEVATED TEMPERATURES CA N RESULT IN THERMAL BURNS. INHALATION: NOT LIKELY TO BE INHALATION HAZARD. IN GESTION: LOW

ORDER OF ACUTE ORAL TOXICITY.

Effects of Overexposure: IRRITATION AS NOTED. SKIN SENSITIZATION (ALLERGY) MAY BE EVIDENCED BY RASHES, ESPECIALLY HIVES. Medical Cond Aggravated by Exposure: PREEXISITING SKIN & EYE DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. PREEXISTING SKIN/LUNG ALLERGIES MAY INCREASE CHANCE OF DEVELOPING INCREASED ALLERGY SYMPTOMS FROM EXPOSURE TO PRODUCT.

First Aid:

EYE:FLUSH W/WATER 15 MIN,HOLD EYELIDS OPEN. GET MED AID. IF HOT PRODUCT,IMMED FLUSH W/COOL WATER 15 MIN. GET MED AID IMMED. SKIN:REMOVE CONTAM CLOTHES/SHOES.WIPE FROM SKIN. FLUSH W/WATER. WASH W/SOAP & WATER.IF IRRIT,GET MED AID.DESTROY CONTAM LEATHER ARTICLES.INHAL:REMOVE TO FRESH AIR,GIVE OXYGEN IF BREATHING DIFFICULT.GET MED AID.INGEST:DONT INDUCE VOMIT. NO TREATMNT UNLESS LRG QTY. GET MED AID.

Fla

sh Point Method:PMCC
Flash Point:480F,249C
Extinguishing Media:USE WATER FOG, FOAM, DRY CHEMICAL OR CO2.
Fire Fighting Procedures:MAT'L WILL NOT BURN UNLESS PREHEATED. DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL BUNKER GEAR, INCLUDING A POSITIVE PRESSURE NIOSH SCBA. COOL CNTNRS W/WATER.
Unusual Fire/Explosion Hazard:>300F W/AIR-SLOW OXIDATIVE DECOMP. >500F-POLYMERIZATION. ALIPHATIC POLYMINES CAN PRODUCE EXOTHERMIC REACTIONS. FUMES FROM THERMAL/CHEM DECOMPOSITN MAY BE TOXIC

==

Spill Release Procedures: MAY BURN-NOT READILY IGNITABLE. USE CAUTION WHEN CLEANING LRG SPILL. LRG: WEAR RSPRTR/PROTECT CLOTHES. STOP LEAK IF SAFE. DIKE, CONTAIN. REMOVE W/VACUUM TRUCK/PUMP TO STORAGE/SALVAGE TANK. SOAK UP W/A BSORBENT. FLUSH W/WTR. SMALL: TAKE UP W/ABSORBENT.

Handling and Storage Precautions: STORE IN COOL, DRY PLACE. KEEP FROM

OPEN FLAME, HIGH TEMP. CNTNRS (EMPTY) RETAIN RESIDUE. HANDLE IN ACCORD W/HZD POTENTIAL. AVOID EYE/SKIN CONTACT. Other Precautions:DONT BREATHE. WASH W/SOAP & WATER BEFORE EATING, DRINKING, SMOKING, APPLYING COSMETICS USING TOILET FACILITIES. WASH CONTAM CLOTHING BEFORE REUSE. IF RESIN HANDLED, SHIPPED, STORED IN BULK, RECOMM PUM P TEMP 180F MAX. PREVENT THERMAL BURNS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:USE A NIOSH APPRO VED RESPIRATOR AS REQUIRED TO PREVENT OVEREXPOSURE. IN ACCORD WITH 20 CFR 1910.134, USE EITHER AN ATMOSPHERE SUPPLY RESPIRATOR OR AN AIR PURIFYING RESPIRATOR FOR ORGANIC VAPORS. Supplemental Safety and Health

Supplemental Salety and Realth

HCC:V5 Boiling Pt:B.P. Text:>500F,>260C Vapor Pres:0.03 @ 77C Spec Gravity:1.17 (WATER=1) Solubility in Water:NEGLIGIBLE Appearance and Odor:VERY LIGHT YELLOW, VERY VISCOUS LIQUID.

Stability Indicator/Materials to Avoid:YES REACT VIGOROUSLY W/OXIDIZERS, STRONG LEWIS/MINERAL ACIDS, MINERAL/ORGANIC BASES(ESP PRIMARY/SECONDARY ALIPHATIC AMINES). Hazardous Decomposition Products:THERMAL:CO,ALDEHYDE,ACID,ORGANIC SUBSTANCES.REACTIONS W/CURING AGENTS:HEAT.RUNAWAY CURE REACTN MAY CHAR,EMIT TOXIC VAPOR

Waste Disposal Methods: DISPOSE OF PROPERLY. IF THIS PRODU

CT BECOMES A

WASTE IT WOULD NOT BE A HAZARDOUS WASTE BY RCRA CRITERIA (40 CFR 261). DISPOSE IN COMPLIANCE WITH LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should s eek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.