

PFIZER INC ROERIG DIV -- PRECIPITATED CALCIUM CARBONATE -- 8520-01-303-6439

=====
Product Identification
=====

Product ID:PRECIPITATED CALCIUM CARBONATE

MSDS Date:09/20/1990

FSC:8520

NIIN:01-303-6439

MSDS Number: BQDSH

=== Responsible Party ===

Company Name:PFIZER INC ROERIG DIV

Address:235 E 42ND STREET

City:NEW YORK

State:NY

ZIP:10017

Country:US

Info Phone Num:413-743-0591

Emergency Phone Num:80

0-424-9300(CHEMTREC)/413-743-0598

Preparer's Name:M. G. LARSON

CAGE:1L435

=== Contractor Identification ===

Company Name:PFIZER INC ROERIG DIV

Address:235 E 42 ST

Box:City:NEW YORK

State:NY

ZIP:10017-5703

Country:US

CAGE:1L435

=====
Composition/Information on Ingredients
=====

Ingred Name:CALCIUM CARBONATE (SARA 313)

CAS:471-34-1

RTECS #:FF9335000

Other REC Limits:*5 MG/M3 TWA RESP

OSHA PEL:15 MG/M3 TDUST*

ACGIH TLV:10 MG/M3 TDUST

=====
Hazards Identificatio

n =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ABRASSIVENESS MAY CAUSE EYE AND SKIN
IRRITATION

===== First Aid Measures =====

First Aid:EYE: FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES.
IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION. SKIN: WASH FROM
SKIN WITH MILD SOAP AND WATER. INHALATION: REMOVE FROM THE EXPOS
URE
AREA. INGESTION: INGESTION SHOULD NOT CAUSE ANY SIGNIFICANT HEALTH
PROBLEMS. IF A LARGE AMOUNT IS INGESTED AND IF CONSCIOUS, GIVE
LARGE QUANTITIES OF WATER TO INDUCE VOMITING. GET MEDICAL
ATTENTION.

===== Fire Fighting Measures =====

Extinguishing Media:NON-FLAMMABLE. AS APPROPRIATE FOR SURROUNDING
COMBUSTIBLES.
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

=====

Spill Release Procedures:THOSE INVOLVED IN CLEAN-UP OF SPILLS-USE RESP
PROTECTION FOR AIRBORNE DUST. VACUUM/SCOOP UP SPILLED MATL FOR
RECOVERY/DISPOSAL, AVOIDING DUSTING CONDITIONS & USING GOOD VENT.
WETTING SPILL WITH A WATE R SPRAY MAY HELP TO KEEP AIRBORNE DUST
LEVELS DOWN

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURE LIMITS ARE EXCEEDED, A NIOSH
APPROVED DUST RESPIRATOR SHOULD BE USED.
Ventilation:ADEQUA
TE EXHST VENT TO MEET TLV REQUIREMENTS. A EXHST
FILTER SYSTEM MAY BE REQUIRED TO AVOID ENVIRONMENTAL CONTAMINATION
Protective Gloves:LEATHER OR RUBBER GLOVES
Eye Protection:SAFETY GLASSES OR DUST-TIGHT GOGGLES
Work Hygienic Practices:AN EYEWASH STATION SHOULD BE AVAILABLE TO THE
AREA OF USE.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Spec Gravity:(H2O=1): 2.71
Solubility in Water:INSOLUBLE
Appearance and Odor:WHITE POWDER, NO ODO

R

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
REACTS WITH ACID TO LIBERATE CARBON DIOXIDE GAS.

===== Disposal Considerations =====

Waste Disposal Methods: CALCIUM CARBONATE IS NOT CONSIDERED TO BE A RCRA HAZARDOUS WASTE AND MAY BE DISPOSED IN A SITE SUITABLE FOR INDUSTRIAL WASTES. REFER TO ANY LOCAL, STATE OR FEDERAL REGULATIONS FOR SPECIFIC DISPOSAL INFORMATION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.