POWER-SONIC CORP -- RECHARGEABLE BATTERY -- 6140-01-294-6528

Product ID:RECHARGEABLE BATTERY MSDS Date:01/14/1990 FSC:6140 NIIN:01-294-6528 MSDS Number: BQFGC === Responsible Party === Company Name: POWER-SONIC CORP Address:3106 SPRING ST Box:5242 City:REDWOOD CITY State:CA ZIP:94063-3929 Country:US Info Phone Num:415-364-5001 Emergency Phone Num:415-364-5001 CAGE :56309 === Contractor Identification === Company Name: BATTERY OUTLET INC Address:1608 CAMPOSTELLA RD Box:City:CHESAPEAKE State:VA ZIP:23324 Country:US Phone:757-545-4442 CAGE:0FGN2 Company Name: POWER-SONIC CORP Address:3106 SPRING ST Box:5242 City:REDWOOD CITY State:CA ZIP:94063-3929 Country:US Phone:650-364-5001 CAGE:56309 Company Name: TNR TECHNICAL INC Address:301 CENTRAL PARK DR Box:City:SANFORD State:FL ZIP:32771 Country:US Phone:407-321-3011 CAGE:1HJ92

======= Composition/Informatio

n on Ingredients ========

Ingred Name:SULFURIC ACID (SARA III) CAS:7664-93-9 RTECS #:WS5600000 Fraction by Wt: 17% % Other REC Limits:NONE SPECIFIED OSHA PEL:1 MG/M3 ACGIH TLV:1 MG/M3; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:LEAD (SARA III) CAS:7439-92-1 RTECS #:OF7525000 Fraction by Wt: 60% % Other REC Limits:NONE SPECIFIED OSHA PEL:0.05 MG/M3;1910.1025 ACGIH TLV:0.15 MG/M3;DUST 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:LEAD OXIDE CAS:1314-41-6 RTECS #:OG542 5000 Fraction by Wt: 20% % Other REC Limits:NONE SPECIFIED

LD50 LC50 Mixture:NOT SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EXPOSURE OCCURS ONLY IF BATTERY CASING IS BROKEN. ACUTE:SULFURIC ACID MAY CAUSE IRRITATION OF EYES, NOSE AND THROAT, MAY DAMAGE EYES OR CAUSE SEVERE BURNS OF EYES AND SKIN

CHRONIC: REPEATED CONTACT C AUSES IRRITATION AND SKIN BURNS. CHRONIC:TEETH EROSION, INFLAMMATION OF THE NOSE, THROAT AND BRONCHIAL TUBES.

Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA. Effects of Overexposure:INHALED: NASAL AND RESPIRATORY IRRITATION FROM SULFUR OXIDE FUMES. CONTACT WITH SKIN OR EYES: BURNS, SKIN IRRITATION AND EYE DAMAGE. SKIN:IRRITATION AND BURNS. INGESTION: STOMACH IRRITAT ION, BURNS, BL OODY STOOLS. Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. FLUSH AREA WITH WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: REMOVE PATIENT TO F RESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION: DRINK LARGE QUANTITIES OF WATER OR MILK, FOLL OWED

BY MILK OF MAGNESIA. GET MEDICAL ATTENTION.

Extinguishing Media:WATER SPRAY, FOAM, DRY CHEMICAL. Fire Fighting Procedures:THE NON-CONDUCTIVE POLYSTYRENE CASING IS NON-FLAMMABLE.

Unusual Fire/Explosion Hazard:KEEP AWAY FROM OPEN FLAMES AND SPARKS. IMPROPER CHARGING AND IGNITION OF RESULTING GASES CAN CAUSE EXPLOSION, PARTICULARLY IN GAS TIGHT ENCLOSURES.

=================== Accidental Release Measures ==

Spill Release Procedures: THE ELECTROLYTE, SULFURIC ACID, IS IMMOBILIZED AND SEALED WITHIN A CLOSED SYSTEM AND IS NON-SPILLABLE. IF CASE IS CRACKED AVOID CONTACT WITH SPILLED ELECTROLYTE. WRAP ENTIRE BATTERY TIGHTLY IN POLYETH YLENE BAGS FOR PROPER DISPOSAL. Neutralizing Agent: 10% SODIUM BICARBONATE SOLUTION.

Handling and Storage Precautions: AVOID PHYSICAL DAMAGE. ADHERE TO PROPER CHARGING PROC

EDURES.

Other Precautions: DO NOT OVERCHARGE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE NORMALLY REQUIRED. Ventilation:GENERAL (MECHANICAL) SHOULD BE SUFFICIENT. Protective Gloves:RUBBER IF HANDLING DAMAGED BATTERY. Eye Protection:GOGGLES IF HANDLING DAMAGED BATTERY Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health PROTECT AGAINST CRACKING OF CASE MATERIAL. ADHERE TO PROPER CHARGING PROCEDURES.

HCC:Z4

Appearance and Odor:RECTANGULAR/SQUARE IN SHAPE. ORANGE IN COLOR. NO ODOR.

Stability Indicator/Materials to Avoid:YES SOLVENTS MAY DISSOLVE CASE MATERIAL. Stability Condition to Avoid:SEVERE OVERCHARGING, PHYSICAL DAMA GE.

Hazardous Decomposition Products:SULFURIC ACID ON DECOMPOSITION WILL PRODUCE TOXIC SULFUR DIOXIDE.

Conditions to Avoid Polymerization: WILL NOT OCCUR.

Waste Disposal Methods:SEND FOR RECLAMATION OR DISPOSE OF ALL WASTES IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Transport Information:49CFR 173.159 (D): A NON-SPILLABLE WET ELECTRIC

STORAGE BATTERY IS EXCEPTED FROM ALL OTHER REQUIREMENTS OF THIS SUBCHAPTER IF: 1.THE BATTERY IS PROTECTED AGAINST SHORT CIRCUIT; 2. FOR BATTERIES MANUF ACTURED AFTER SEPTEMBER 30,1995, THE BATTERY AND THE OUTER PACKAGING MUST BE PLAINLY AND DURABLY MARKED "NONSPILLABLE" OR "NONSPILLABLE BATTERY". 3. THE BATTERY MUST BE CAPABLE OF WITHSTANDING THE FO LLOWING TWO TESTS WITHOUT LEAKAGE OF BATTERY FLUID FROM THE BATTERY: (I) VIBRATION TEST; (II) PRESSURE DIFFERENTIAL

TEST. PER MFR THESE BATTERIES CONFORM TO THE ABOVE REGULATIONS & IATA SPEC PROV A67 AND ARE, THEREFORE, NOT REGULATED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek compe tent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.