

RALMIKE'S TOOL-A-RAMA -- B1C0018;EDM OIL -- 9150-01-042-6495

=====
Product Identification
=====

Product ID:B1C0018;EDM OIL
MSDS Date:08/08/1989
FSC:9150
NIIN:01-042-6495
MSDS Number: BQMJG
=== Responsible Party ===
Company Name:RALMIKE'S TOOL-A-RAMA
Address:4405 S. CLINTON AVE.
Box:361
City:SOUTH PLAINFIELD
State:NJ
ZIP:07080-6680
Country:US
Info Phone Num:201-561-6680
Emergency Phone Num:201-561-6680
Preparer's Name:DAVE TOWNSHEND
CAGE:51142
=== Contractor Identification ===
Company Name:RALMIKE'S TOOL-A-RAMA
CAGE:51142

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM OIL;PETROLEUM BASED LUBRICATING OIL
CAS:64741-89-5
RTECS #:PY8041500
Other REC Limits:5MG/M3 OIL MIST

=====
Hazards Identification
=====

LD50 LC50 Mixture:LD50 ORAL>5G/KG;LD50 DERMAL>3.16G/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MANUFACTURER STATES THAT MATERIEL HAS
LOW ORDER OF ORAL AND DERMAL TOXICITY.INGEST:ASPIRATION HAZARD;LUNG
DAMAGE MAY RESULT FROM VOMITING THIS MATERIEL.SKIN:DRYING ACTION
MAY CAUSE IRRITATION AND DERM ATITIS.
Explanation of Carcinogenicity:NO DATA.
Effects of Overexposure:SKIN:DRYING,IRRITATION,DERMATITIS.
Medical Cond Aggravated by Exposure:MANUFACTURER STATES UNKNOWN.

=====

= First Aid Measures =====

First Aid:EYE:FLUSH WITH CLEAN WATER FOR 15 MINUTES.IF IRRITATION PERSISTS,CALL PHYSICIAN.SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH A MILD SOAP AND WATER.INHAL:NOT ENCOUNTERED IN NORMAL SERVICE. HOT-REMOVE FROM EXPOSURE;CALL PHYSICIAN.RESUSCITATE OR GIVE OXYGEN IF NEEDED.MISTS-REMOVE FROM EXPOSURE.DO NOT REENTER UNTIL MIST SUBSIDES.INGEST:DO NOT INDUCE VOMITING!CALL PHYSICIAN.

===== Fire Fighting Measures =
=====

Flash Point Method:COC

Flash Point:280F,138C

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:FOAM,WATER SPRAY(FOG),DRY CHEMICAL,CARBON DIOXIDE,VAPORIZING LIQUID TYPE EXTINGUISHER.

Fire Fighting Procedures:USE A SCBA.USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.WATER SPRAY OR FOAM MAY CAUSE FROTHING;FROTH MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURE.

Unusual Fire/Explosion Hazard:DECOMPOSITION PRODUCTS MAY BE TOXIC.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB WITH SAND OR INERT MATERIEL.SWEEP OR SCOOP UP INTO AN APPROPRIATE CONTAINER FOR DISPOSAL.PREVENT SEEPAGE INTO WATERWAYS BY DIKING OR IMPOUNDING.SPILLS INTO WATERWAYS MUST BE REPORTED.

Neutralizing Agent:NONE.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED.DO NOT HANDLE NEAR HEAT,SPARKS,FLAMES OR STRONG OXIDANTS.

Other Precautions:DO NOT

SURIZE,HEAT,CUT,BRAZE,WELD OR SOLDER NEAR

EMPTY CONTAINERS,THEY MAY EXPLODE.DO NOT CLEAN CONTAINERS FOR REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY NEEDED.IN ENCLOSED SPACE,USE SUPPLIED AIR RESPIRATOR.FOR MISTS,USE APPROPRIATE CAN OR CARTRIDGE TYPE RESPIRATOR.

Ventilation:USE LOCAL EXHAUST TO CAPTURE VAPOR,MIST,FUMES.PROVIDE >60CFM HOOD VELOCITY FOR ENCLOSED SPACE.

Protective Gloves:CHAMICALLY RESISTANT

Eye

Protection:SPLASH GOGGLES,FACE SHIELD.

Other Protective Equipment:CHEMCIALLY RESISTANT APRON,IMPERVIOUS CLOTHING.HMIS SUGGEST HAVING A SOURCE OF CLEAN WATER AVAILABLE.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

PRODUCT IS REMOVED READILY WITH A WATERLESS HAND CLEANER FOLLOWED BY WASHING WITH SOAP AND WATER.

===== Physical/Chemical Propertie

s =====

HCC:V6

Vapor Pres:8

Spec Gravity: