

GEO.PFAU'SONS CO,INC. -- PEACOCK EWS LARD OIL -- 9150-00-231-6699

===== Product Identification =====

Product ID:PEACOCK EWS LARD OIL

MSDS Date:02/01/1997

FSC:9150

NIIN:00-231-6699

MSDS Number: BQSWN

=== Responsible Party ===

Company Name:GEO.PFAU'SONS CO,INC.

Address:800 WALL STREET

Box:7

City:JEFFERSONVILLE

State:IN

ZIP:47130-3619

Country:US

Info Phone Num:812-283-6697

Emergency Phone Num:812-283-6697

Preparer's Name:NOT PROVIDED

CAGE:2W231

=== Contractor Identification ===

Company Name:DYNATECH SCIENTIFIC INC

Address:1401 27TH ST

Box:640164

City:KENNER

State:LA

ZIP:70064

Country:US

Phone:504-465-9604

CAGE:0VL27

Company Name:GEO.PFAU'S SONS CO,INC.

Address:800 WALL STREET

Box:7

City:JEFFERSONVILLE

State:IN

ZIP:47130-3619

Country:US

Phone:812-283-6697

CAGE:2W231

Company Name:SDB CONSULTANTS LTD

Address:401 WHITNEY AVE SUITE 120

Box:City:GRETNA

State:LA

ZIP:70056

Country:US

Phone:504-366

-9105
Contract Num:SP0450-00-M-C678
CAGE:0PGK2
Company Name:UNI-KEM INTERNATIONAL
Address:1001 HARIMAW COURT EAST
Box:City:METAIRIE
State:LA
ZIP:70001
Country:US
Phone:504-835-7600/FAX:504-835-7608
CAGE:4S446

=====
Composition/Information on Ingredients
=====

Ingred Name:NON-HAZARDOUS LARD OIL
CAS:8016-28-2
= Wt:100.
Other REC Limits:NONE KNOWN
OSHA PEL:NONE KNOWN
ACGIH TLV:NONE KNOWN

=====
Hazards Identification
=====

LD50 LC50 Mixture:NOT
PROVIDED
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN CONTACT: AMBIENT - SLIGHT SKIN
IRRITATION MAY OCCUR. EYE CONTACT: AMBIENT - SLIGHT EYE IRRITATION
MAY OCCUR. ELEVATED TEMPERATURE - VAPOR MAY CAUSE IRRITATION.
OIL-TYPE BURNS MAY OCCUR. INHALATION: AMBIENT - NONE ANTICIPATED.
ELEVATED TEMPERATURE - MAY PRODUCE VARIOUS CARBON OXIDES WHICH
CAUSE IRRITATION TO THE RESPIRATORY TRACT. INGESTION: NOT EXPECTED
TO BE ACUTELY TOXIC - MAY HAVE A LAXATIVE EFFECTS.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:SKIN CONTACT: AMBIENT - SLIGHT SKIN IRRITATION
MAY OCCUR. EYE CONTACT: AMBIENT - SLIGHT EYE IRRITATION MAY OCCUR.
ELEVATED TEMPERATURE - VAPOR MAY CAUSE IRRITATION. OIL-TYPE BURNS
MAY OCCUR. INHALATION: ELEVATED TEMPERATURE - MAY PRODUCE VARIOUS
CARBON OXIDES WHICH CAUSE IRRITATION TO THE RESPIRATORY TRACT.
INGESTION: MAY HAV

E A LAXATIVE EFFECTS.

Medical Cond Aggravated by Exposure:NONE KNOWN.

===== First Aid Measures =====

First Aid:INHALATION: MOVE SUBJECT TO FRESH AIR AND CONSULT A PHYSICIAN IF IRRITATION PERSISTS. INGESTION: NOT ANTICIPATED TO BE TOXIC - MAY HAVE A LAXATIVE EFFECT - CONSULT PHYSICIAN. SKIN: WHEN MOLTEN OR HEAT ED, WILL CAUSE OIL-TYPE BURNS. TREAT AS SUCH. WASH AFFECTED SKIN AREAS WITH SOAP AND WATER. EYES: FLUSH EYES WITH WATER AND CONSULT PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:~260.C, 500.F

Lower Limits:NOT APPLICAB

Upper Limits:NOT APPLICAB

Extinguishing Media:USE NO WATER. TREAT AS AN OIL FIRE. USE CARBON DIOXIDE, FOAMITE, SAND OR SODIUM BICARBONATE.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF CONTAINED BREATHING APPARATUS AND PROTECTIVE GEAR TO PREVENT CONTACT WITH SKIN AND EYES.

Unusual Fire/Explosion Hazard:COMBUSTION GENERATES TOXIC FUMES CONTAINING CARBON OXIDES.

===== Accidental Release Measures =====

Spill Release Procedures:SPILL AREA MAY BE SLICK OR SLIPPERY. CONTAIN SPILLS IMMEDIATELY WITH INERT MATERIAL (SAND, EARTH, ETC). MATERIAL CAN BE REMOVED FROM THE GROUND BY PUMP, SHOVEL AND/OR ABSORPTION. CHECK LOCAL, STATE AND FEDERAL REGULATIONS AS TO DISPOSAL. KEEP SPILLS AND CLEANING RUNOFF OUT OF OPEN BODIES OF WATER AND SEWERS. MATERIAL IS BIODEGRADABLE, PRODUCING A HIGH B.O.D. WHEN EMULSIFIED IN WATER.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:MAINTAIN TEMPERATURE AT A MAXIMUM 50C FOR STORAGE. AVOID STORAGE AND TRANSFER FACILITIES CONSTRUCTED OF COPPER, COPPER ALLOYS AND ELEMENTS 24 THROUGH 30 (CR, MN, FE, CO, NI, CU, ZN).

Other Precautions:NOT PROVIDED

===== Exposure Controls/Personal Protection =====

Respiratory

Protection:NEEDED ONLY AT ELEVATED TEMPERATURES OR UNDER
CONDITIONS OF MISTING. USE AN OSHA OR NIOSH APPROVED RESPIRATOR.
LOCAL EXHAUST NOT NEEDED AT AMBIENT TEMPERATURE. GENERAL MECHANICAL
VENTILATION IS RECOMMENDED.

Ventilation:WITH USE OF PRODUCT AT AMBIENT TEMPERATURE, USE GENERAL
PURPOSE VENTILATION. LOCAL EXHAUST RECOMMENDED AT ELEVATED
TEMPERATURES OR IN PRESENCE OF MIST/ FUMES.

Protective Gloves:NOT REQUIRED. OIL RESISTANT THERMAL PROTECTION AT
ELEVATED TEMPERATURES.

Eye Protection:SAFETY GLASSES OR FACE SHIELD MAY BE DESIRED AT AMBIENT
TEMPERATURE.

Other Protective Equipment:NONE AT AMBIENT-NORMAL OIL-RESISTANT THERMAL
PROTECTION WHEN HEATED.

Work Hygienic Practices:NOT PROVIDED

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:V6

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:NOT AVAILABLE

Melt/Freeze Pt:=7.2C, 45.F

M.P/F.P Text:POUR POINT

Vapor Pres:>10 MMHG@ 264C

Vapor Density:

>1

Spec Gravity:0.905 - 0.915

Viscosity:190-210 SUS @ 100F

Evaporation Rate & Reference: