View NSN Online: https://aerobasegroup.gr/nsn/6520-01-327-4843

MINNESOTA MINING AND MFG CO -- SOF-LEX XT FINISHING AND POSLISHING DISCS

6520-01-327-4843

Product ID:SOF-LEX XT FINISHING AND POSLISHING DISCS

MSDS Date:04/16/1992

FSC:6520

NIIN:01-327-4843

MSDS Number: BQWPY === Responsible Party ===

Company Name: MINNESOTA MINING AND MFG CO

Address:3M CTR 224-2S-25

City:ST. PAUL

State:MN

ZIP:55144-1000

Country:US Info Phone N

um:612-733-1341/612-733-1110

Emergency Phone Num:612-733-1341

CAGE:76381

=== Contractor Identification ===

Company Name: MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

======= Composition/Information on Ingredients ========

Ingred Name: POLYESTER FILM

Fraction by Wt: 33 - 90%

Other REC Limits: NONE RECOMMENDED

Ingred Name: ALUMINUM OXIDE GRIT AND BINDER

Fraction

by Wt: 10 - 67% Other REC Limits:NONE RECOMMENDED
=========== Hazards Identification =============
LD50 LC50 Mixture:LD50 (ORAL RAT) NOT KNOWN Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE- MECHANICAL EYE AND SKIN IRRITATION. NONVOLATILE. NO ADVERSE EFFECTS EXPECTED IF INHALED. INGESTION IS UNLIKELY. CHRONIC- UNKNOWN. Effects of Overexposure:EYE AND SKIN IRRITATION, RE DNESS, ITCHING,
SCRATCHING OF THE CORNEA AND TEARING Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THIS MATERIAL.
======================================
First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYE:FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:WASH WITH SOAP AND WATER. INHALED/INGESTED:NOT RELEVANT
======================================
Extinguishing Media:WATER Fire Fighting Procedures:WEAR NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:NONE
========== Accidental Release Measures ==========
Spill Release Procedures:PLACE IN AN APPROVED METAL CONTAINER AND SEAL Neutralizing Agent:NOT RELEVANT
=========== Handling and Storage ============
Handling and Storage Precautions:STORE IN SEALED CONTAINERS. Other Precautions:WASH THOROUGHLY AFTER HANDLING MATERIAL.

===

Respiratory Protection:NONE NORMALLY REQUIRED. Ventilation:ADEQUATE Protective Gloves:NONE REQUIRED Eye Protection:AVOID EYE CONTACT
Other Protective Equipment:EYE WASH STATION Work Hygienic Practices:WASH HANDS BEFORE EATING OR DRINKING. Supplemental Safety and Health
========= Physical/Chemical Properties ==========
HCC:N1 Melt/Freeze Pt:M.P/F.P Text:NOT KNOWN Spec Gravity:NOT KNOWN Viscosity:NOT RELEVANT Ev
aporation Rate & Discountier Reference: NOT RELEVANT Solubility in Water: NOT KNOWN Appearance and Odor: SOLID ABRASIVE DISCS 3/8", 1/2" IN DIAMETER, YELLOW TO RED-BROWN COLOR
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES NONE
Stability Condition to Avoid:EXCESSIVE HEAT Hazardous Decomposition Products:NOT KNOWN
======= Disposal Considerations ==========
Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOC AL, STATE AND FEDERAL REGULATIONS. RECOMMENDED METHOD IS BY SANITARY LANDFILL.
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department

===== Exposure Controls/Personal Protection ========

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume

responsibility for the suitability of this information to their particular situation.