

ASPEN PAINTS -- STAIN, OIL, SEMI TRANSPARENT, WOOD EXT. DK -- 8010-00-926-9130

=====
Product Identification
=====

Product ID:STAIN, OIL, SEMI TRANSPARENT, WOOD EXT. DK

MSDS Date:03/01/1993

FSC:8010

NIIN:00-926-9130

MSDS Number: BQYJG

=== Responsible Party ===

Company Name:ASPEN PAINTS

Address:1128 SW SPOKANE ST.

City:SEATTLE

State:WA

ZIP:98134

Country:US

Info Phone Num:206-682-4603

Emergency Phone

Num:800-424-9300(CHEMTREC)

Preparer's Name:D. KIER

CAGE:0AL09

=== Contractor Identification ===

Company Name:ASPEN PAINTS

Address:1128 SW SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Phone:800-424-9300 CHEMTREC

CAGE:0AL09

=====
Composition/Information on Ingredients
=====

Ingred Name:S K SOLVENT, MINERAL SPIRITS MIXTURE, SOLVENT 390

CAS:8052-41-3

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name:BENZENE

CA

S:71-43-2
RTECS #:CY1400000
Other REC Limits:< 10 PPM
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: VAPOR CAUSE NASAL &
RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA,
HEADACHE, UNCONSCIOUSNESS, ASPHIXIATION. SKIN: DEFATTING/DRYING SKIN
RESULT IN DERMATITIS
. EYES: SEVERE IRRITATION, REDNESS, TEARING,
BLURRED VISION. INGESTION: GASTROINTESTINAL IRRITATION, NAUSEA,
VOMITING, & DIARRHEA.
Effects of Overexposure:ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE
CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. REPORTS HAVE ASSOCIATED
REPEATED & PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENT WITH
PERMANENT BRAIN & NERVOUS SY STEM DAMAGE. INTENTIONAL MISUSE BY
DELIBERATELY CONCENTRATING & INHALING THE CONTENTS MAY BE HARMFUL
OR FATAL.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE VICTIM FROM FUTHER EXPOSURE & RESTORE
BREATHING, IF REQUIRED. EYE CONTACT: FLUSH EYES WITH WATER FOR AT
LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. SKIN CONTACT: WASH
CONTAMINATE D SKIN WITH MILD SOAP & WATER. INGESTION: DO NOT
INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point
:112F,44C
Lower Limits:0.8
Upper Limits:5.0
Extinguishing Media:DRY CHEMICAL, CO2, FOAM, WATER FOG.
Fire Fighting Procedures:DON'T ENTER CONFINED FIRE SPACE W/O ADEQUATE
PROTECTIVE CLOTHING & APPROVED SCBA. EXCLUDE AIR. DO NOT USE WATER
EXCEPT AS FOG.USE WATER TO COOL HEATED CONTAINER
Unusual Fire/Explosion Hazard:CAUTION-FLAMMABLE. AVOID EXCESSIVE HEAT,
OPEN FLAMES & ALL IGNITION SOURCES. VAPOR FORMS AN EXPLOSIVE
MIXTURE WITH AIR BETWEEN UPPER & LOWER FLAMMABLE LIMITS.

=====

===== Accidental Release Measures =====

Spill Release Procedures: ABSORB SPILL WITH ABSORBENT MATERIAL & PLACE MATERIAL INTO A CLOSED CONTAINER. LARGE SPILL, DIKE AREA TO PREVENT THIS MATERIAL FROM ENTERING WATERWAYS. WEAR PROTECTIVE EQUIPMENT DURING CLEANUP. NOTIFY APPROP. ENVIRONMENTAL AGENCY(IES) IF OVER 220LBS

===== Handling and Storage =====

Handling and Storage Precautions: "FLAMMABLE LIQUID" STORE IN COOL, DRY, WELL-VENTILATED AREA, & AWAY FROM ALL HEAT SOURCES. GROUND CONTAINERS WHEN POURING & LIMIT STATIC BUILDUP.

Other Precautions: EMPTY CONTAINERS MAY BE HAZARDOUS FROM RESIDUES OF PRODUCT & VAPOR. DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: A CANISTER-TYPE RESPIRATOR MUST BE WORN TO PREVENT THE INHALATION OF VAPOR OR SPRAY MISTS WHEN TLV, PEL IS EXCEEDED.

D.

Ventilation: GENERAL VENTILATION. LOCAL VENTIL. REQUIRED CERTAIN CASES TO KEEP EXPOSURE LEVEL BELOW THE LIMITS.

Protective Gloves: CHEMICAL-RESIST. NITRILE, NEOPRENE, RUBBER.

Eye Protection: WEAR FACE SHIELD OR CHEMICAL GOGGLES.

Other Protective Equipment: WEAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT. EYE WASH STATION/SAFETY SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices: LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. USE GOOD PERSONAL HYGIENE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 301 TO 402F

Vapor Pres: >70 @ 38 C

Vapor Density: 4.8

Spec Gravity: 0.94

Viscosity: 10"-25" #4FC

Evaporation Rate & Reference: < N-BUTYL ACETATE

Solubility in Water: NEGLIGIBLE

Appearance and Odor: THIN LIQUID, MILD ODOR

Percent Volatiles by Volume: 27-29

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS, LEWIS

OR MINERAL ACIDS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT, OPEN FLAME & ALL
IGNITION SOURCES.

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE ARE
PRODUCED ON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:IF NOT POSSIBLE TO RECLAIM, THEN MATERIAL &
CONTAINERS SHOULD BE TREATED AS HAZARDOUS WASTE BASED ON THE
CHARACTERISTIC OF IGNITABILITY AS DEFINED UNDER FEDERAL RCRA
REGULAT. COMPLY WITH
LOCAL, STATE AND FEDERAL REGULATIONS FOR
DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.