

RICOH COMPANY LTD -- 4325 SAVIN BLACK TONER TYPE L2 (RICOH P/N 8 -- 6850-01-346-8259
===== Product Identification =====

Product ID:4325 SAVIN BLACK TONER TYPE L2 (RICOH P/N 8

MSDS Date:07/17/1991

FSC:6850

NIIN:01-346-8259

MSDS Number: BRGPH

=== Responsible Party ===

Company Name:RICOH COMPANY LTD

Address:5 DIEDRICK PLACE

City:WEST CALDWELL

State:NJ

ZIP:07006

Country:US

Info Phone Num:201-882-2000

Emergency Phone Num:800-336-6737

CAGE:FO993

=== Contractor Identification ===

Company Name:RICOH CO LTD

Address:5 DEDRICK PL

Box:City:CALDWELL

State:NJ

ZIP:07006-6304

Country:US

Phone:973-882-2000 / 800-336-6737

CAGE:2Z665

Company Name:RICOH COMPANY LTD

Address:1-3-6 NAKAMAGOME OTA-KU

City:TOKYO

Phone:03-777-8111

CAGE:FO993

Company Name:SAVIN CORP.

Address:9 WEST BROAD STREET

Box:12070

City:STAMFORD

State:CT

ZIP:06904-2270

Country:US

Phone:203-967-5000

CAGE:29382

===== Composition/Info

Information on Ingredients =====

Ingredient Name: CARBON BLACK
CAS: 1333-86-4
RTECS #: FF5800000
Fraction by Wt: 3.0%
OSHA PEL: 3.5 MG/M3
ACGIH TLV: 3.5 MG/M3; 9192

Ingredient Name: ACRYLIC POLYMER
CAS: 25608-63-7
Fraction by Wt: 4.0%
Other REC Limits: NONE SPECIFIED

Ingredient Name: WAX (POLYETHYLENE)
CAS: 9002-88-4
Fraction by Wt: 9.0%
Other REC Limits: NONE RECOMMENDED

Ingredient Name: HYDROTREATED LIGHT PETROLEUM DISTILLATE
CAS: 64742-47-8
Fraction by Wt: 35.0%
Other REC Limits: NONE RECOMMENDED

Ingredient Name: HYDROTREATED HEAVY NAPHTHA
CAS: 64742-48-9
Fraction by Wt: 49.0%
Other REC Limits: NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture: ACUTE ORAL TOXICITY >5000 MG/KG
Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO
Health Hazards Acute and Chronic: ACUTE: INHALATION- IRRITATION OF
RESPIRATORY TRACT, CNS EFFECTS. EYES- IRRITATION. SKIN- IRRITATION.
INGESTION- STOMACH DISTRESS. CHRONIC: CANCER.
Explanation of Carcinogenicity: THERE IS INADEQUATE EVIDENCE FOR CARBON
BLACK TO BE LISTED AS A CARCINOGEN.
Effects of Overexposure: INHALATION: COUGHING, DIZZINESS, HEADACHES.
EYES: REDNESS, BURNING SENSATION, TEARING. SKIN: REDNESS, RASH,
BURNING SENSATION. INGESTION- NAUSEA, VOMITING, CNS EFFECTS.
Medical Conditions Aggravated by Exposure: PEOPLE WITH A SKIN DISORDER SHOULD
USE CAUTION WHEN HANDLING OR USING THIS PRODUCT.

===== First Aid Measures =====

=====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING & LAUNDRER BEFORE REUSE.
WASH SKIN WITH SOAP AND WATER. INHALATION:REMOVE TO FRESH AIR &
RESTORE BREATHING IF NECESSARY. GET MEDICAL ATTENTION.
EYE:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING
EYELIDS OPEN. GET MEDICAL ATTENTION. INGESTION:GET IMMEDIATE
MEDICAL ATTENTION. DO NOT INDUCE VOMITING. NOTHING BY MOUTH IF
UNCONSCIOUS.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:>144F,>62C
Lower Limits:0.6
Upper Limits:7.0
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER
FOG.
Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE
EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL
NEARBY CONTAINERS EXPOSED TO FIRE AND DISPERSE VAPORS.
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental R
elease Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES, VENTILLATE AREA.
WEAR PEROTECTIVE EQUIPMENT. ABSORB MATERIAL WITH CLAY, VERMICULITE,
OR SIMILAR ABSORBENT MATERIAL. PLACE IN DISPOSAL CONTAINERS.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, VENTILATED WORK AREA.
KEEP CONTAINERS CLOSED WHEN NOT IN USE. KEEP AWAY FROM ALL IGNITION
SOURCES. KEEP
AWAY FROM CHILDREN.
Other Precautions:EMPTY CONTAINERS CONTAIN RESIDUE AND CAN BE
DANGEROUS. DO NOT APPLY PRESSURE OR EXPOSE CONTAINERS TO SOURCES OF
IGNITION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED. USE NIOSH APPROVED
RESPIRATOR, AIR-SUPPLIED OR FILTERING TYPE WITH ORGANIC VAPOR
CARTRIDGES ARE RECOMMENDED WHEN PEL/TLV IS EXCEEDED.
Ventilation:USE ADEQUATE MECHANICAL VENTILATION. USE EXPLOSION PROOF
E

QUIPMENT.

Protective Gloves:NONE NORMALLY REQUIRED.

Eye Protection:SAFETY GLASSES OR SPLASH GOGGLES

Other Protective Equipment:EYE WASH STATION.

Work Hygienic Practices:USE GOOD CHEMICAL HYGIENE PRACTICES. AVOID
PROLONGED AND/OR REPEATED CONTACT. AVOID BREATHING VAPORS.

Supplemental Safety and Health
FOR USE WITH CLASS II COPIER.

===== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:B.P. Text:349F,176C

Vapor Pres:1

Spec Gravity:0.80

Evaporation Rate & R

eference:0.04 (N-BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE,