

CROWN INDUSTRIAL PRODUCTS CO -- DRY FILM LUBRICANT 6075N -- 9150-01-148-7155

=====
Product Identification
=====

Product ID: DRY FILM LUBRICANT 6075N

MSDS Date: 02/25/1993

FSC: 9150

NIIN: 01-148-7155

MSDS Number: BSDGK

=== Responsible Party ===

Company Name: CROWN INDUSTRIAL PRODUCTS CO

Address: HWY 47 N

Box: 350

City: HEBRON

State: IL

ZIP: 60034

Country: US

Info Phone Num: 815-648-2424 / FAX 815-648-4090

Eme

rgency Phone Num: 815-648-2424

Preparer's Name: PETER M. JANKOWSKI

CAGE: 92381

=== Contractor Identification ===

Company Name: CROWN INDUSTRIAL PRODUCTS CO

Address: HWY 47 N

Box: 350

City: HEBRON

State: IL

ZIP: 60034

Country: US

Phone: 815-648-2424

CAGE: 92381

Company Name: GOVERNMENT PROCUREMENT SPECIALISTS INC

Address: 5845 OAKBROOK PKY

Box: City: NORCROSS

State: GA

ZIP: 30093

Country: US

Phone: 404-416-0761

CAGE: 0K2Y0

Company Name: MILNUCORP INC

Address: 3220-A INDUSTRIAL WAY

Box: City: SNELLVILLE

State: GA

ZIP: 30039

Country:US
Phone:404-524-3181 / FAX: 770-736-5094
CAGE:0RY69

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOBUTANE
CAS:75-28-5
RTECS #:TZ4300000
Fraction by Wt: 11-30%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 11-30%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9293

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT805
0000
Fraction by Wt: 1-10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:ACETONE (SARA III)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 51-70%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:750PPM/1000 STEL
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Reports of Carcinogenicity:NTP:NO IARC:

NO OSHA:NO

Health Hazards Acute and Chronic:EYE CONTACT: LIQUID SPLASHED INTO EYES CAN RESULT IN DISCOMFORT, PAIN AND IRRITATION. SKIN CONTACT: PROLONGED AND REPEATED CONTACT CAN CAUSE IRRITATION AND DERMATITIS. INHALATION: MAY CAUSE IRRITATION OF THE RESPIRATORY SYSTEM, DIZZINESS, NAUSEA, LIGHT HEADNESS AND HEADACHES. INGESTION: IF ASPIRATED, CHEMICAL PNEUMONIA

Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.

Effects of Overexposure:EYES: IRRITATION. SKIN: MIL

D IRRITATION ON

PROLONGED CONTACT. INHALATION: DIZZINESS, LIGHT HEADEDNESS, IRRITATION OF THE RESPIRATORY SYSTEM. INGESTION: MAY CAUSE CHEMICAL PNEUMONIA IF ASPIRATED INTO L UNGS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES OR UNTIL IRRITATION SUBSIDES. SKIN: REMOVE ALL CONTAMINATED CLOTHING. WASH SKIN WITH SOAP AND WATER. INHALATION: REMOVE FROM EXPOSURE IMMEDIATELY. IF BREATHING IS IRREGULAR OR STOPPED, BEGIN ARTIFICIAL RESPIRATION AND ADMINISTER OXYGEN. INGESTION: DRINK LARGE AMOUNTS OF WATER. DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:AEROSOL

Lower Limits:1.5

Upper Limits:12

Extinguishing Media:CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:FIREFIGHTERS SHOULD USE A SELF-CONTAINED POSITIVE PRESSURE BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:TREAT AS CYLINDERS OF COMPRESSED GAS.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. REMOVE ALL SOURCES OF IGNITION. CLEAN UP WITH INERT MATERIAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:AEROSOL CONTAINERS: DO NOT STORE IN DIRECT SUNLIGHT, NEAR OPEN FLAMES, OR AT TEMP

TEMPERATURES EXCEEDING

120F. DO NOT SMOKE WHILE SPRAYING.

Other Precautions:USE ONLY AS DIRECTED. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING VAPORS AND INHALING CONTENTS CAN BE HARMFUL OR FATAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATORY PROTECTION PROGRAM SHOULD BE IN ACCORDANCE WITH 29 CFR 1910.134.

Ventilation:LOCAL EXHAUST IS ADEQUATE.

Protective Gloves:POLYETHYLENE OR NEOPRENE.

Eye Protection:SAFETY GLASSES.

Other

Protective Equipment:PROTECTIVE CLOTHING AND EQUIPMENT.

Work Hygienic Practices:WASH SKIN WITH SOAP AND WATER.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:135F,57C

Vapor Pres:65-75 PSIG

Vapor Density:>1 (AIR=1)

Spec Gravity:0.76

Evaporation Rate & Reference: