

VALVOLINE OIL CO SUBSIDIARY OF ASHLAND OIL INC. -- CAM 2 80 W 90 GO -- 9150-01-313-2191

=====  
Product Identification  
=====

Product ID:CAM 2 80 W 90 GO

MSDS Date:04/24/1990

FSC:9150

NIIN:01-313-2191

MSDS Number: BSDTS

=== Responsible Party ===

Company Name:VALVOLINE OIL CO SUBSIDIARY OF ASHLAND OIL INC.

Address:200 E MAIN ST

Box:14000

City:LEXINGTON

State:KY

ZIP:40512

Country:US

Info Phone Num:606-

264-7000

Emergency Phone Num:800-ASHLAND/800-274-5263

CAGE:72527

=== Contractor Identification ===

Company Name:BUDGET OIL CO

CAGE:8P476

Company Name:VALVOLINE OIL CO

Address:3499 BLAZER PKY

Box:14000

City:LEXINGTON

State:KY

ZIP:40512

Country:US

Phone:606-357-7206 / 800-274-5263

CAGE:72527

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM OIL

Fraction by Wt: 85- 100%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MI

ST)

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS UNKNOWN.  
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE AND CHRONIC- TOXICOLOGICAL  
TESTING INDICATES THAT SIMILAR PRODUCTS ARE NOT HAZARDOUS AS  
DEFINED BY OSHA (29 CFR 1910.1200).  
Effects of Overexposure:MAY CAUSE EYE, SKIN, RESPIRATORY TRACT  
IRRITATION.  
Medical Cond Aggravated  
by Exposure:NONE KNOWN.

=====  
===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALATION:REMOVE TO  
FRESH AIR. PROVIDE CPR IF NEEDED. EYES:FLUSH WITH WATER FOR 15  
MINUTES, HOLDING EYELIDS OPEN. SKIN:REMOVE EXCESS. WASH SKIN WITH  
SOAP & WATER . INGESTION:DO NOT INDUCE VOMITING. KEEP PERSON WARM &  
QUIET. GET MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point:>300F,>14  
9C  
Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.  
WATER/FOAM MAY CAUSE FROTHING. COOL FIRE EXPOSED CONTAINERS WITH  
WATER SPRAY.  
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A  
FULL FACED SELF CONTAINED BREATHING APPARATUS. DO NOT SPRAY WATER  
INTO CONTAINERS OF HOT, BURNING LIQUID.  
Unusual Fire/Explosion Hazard:CONTAINERS MAY RUPTURE DUE TO PRESSURE  
BUILD UP.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:ABSORB SPILLS WITH NON-FLAMMABLE ABSORBENT  
MATERIAL SUCH AS EARTH, SAND OR VERMICULITE. SWEEP UP AND TRANSFER  
TO A CONTAINER FOR PROPER DISPOSAL. CLEAN AREA WITH APPROPRIATE  
CLEANER.  
Neutralizing Agent:NOT RELEVANT

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN DRY PLACE AWAY FROM STRONG  
OXIDANTS. DO NOT USE CUTTING OR WELDING TORCH ON THIS CONTAINER  
(EVEN EMPTY).  
Other Precautions:DO NOT GET IN E

YES, ON SKIN OR ON CLOTHING. WASH  
THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.  
Ventilation:NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.  
Protective Gloves:NOT NORMALLY REQUIRED.  
Eye Protection:NOT NORMALLY REQUIRED.  
Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS AND LEGS.  
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND  
RECOMMENDED PROCEDURE  
DURES. DO NOT WEAR CONTAMINATED CLOTHING OR  
FOOTWEAR.  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6  
NRC/State Lic Num:NOT RELEVANT  
Vapor Density:>1  
Spec Gravity:0.902  
Evaporation Rate & Reference: