

LASTING PAINTS, INCORPORATED -- A/S TT-E-508C TYPE I & II, FS22-300 -- 8010-00-286-7839

=====
Product Identification
=====

Product ID:A/S TT-E-508C TYPE I & II, FS22-300

MSDS Date:08/08/1988

FSC:8010

NIIN:00-286-7839

MSDS Number: BSFNW

=== Responsible Party ===

Company Name:LASTING PAINTS, INCORPORATED

Address:200 SOUTH FRANKLINTOWN ROAD

City:BALTIMORE

State:MD

ZIP:21223

Country:US

Info Phone Num

:410-947-6300

Emergency Phone Num:410-947-6306

CAGE:GO423

=== Contractor Identification ===

Company Name:LASTING PAINTS INC.

Address:200 S FRANKLINTOWN RD

Box:City:BALTIMORE

State:MD

ZIP:21223-2038

Country:US

CAGE:35178

Company Name:LASTING PAINTS, INC.

Address:200 S FRANKLINTOWN ROAD

City:BALTIMORE

State:MD

ZIP:21223

Country:US

Phone:410-947-6300/800-368-2205

CAGE:GO423

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC DISTILLATE (STODDARD) (VAPOR PRES

SURE 10.0 MM HG)

(LEL 1.0)

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 24.5%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:100 PPM

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Health Hazards Acute and Chronic:INHALATION: IRRITATION OF THE

RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY FOLLOWING STEPS; HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION OR COMA. SKIN OR EYE CONTACT:

PRIMA RY IRRITATION OR SENSITIZER.

REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH

Effects of Overexposure:PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

Medical Cond Aggravated by Exposure:INHALATION BY PERSONS WITH

RESPIRATORY PROBLEMS COULD HAVE THE CONDITION ADDITIONALLY AGGRAVATED.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. TREAT SYMPTOMATICALL

Y. CONSULT A PHYSICIAN. SPLASH (EYES): FLUSH

IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES.

CONSULT A PHYSICIA N. SPLASH (SKIN): WASH AFFECTED AREA W/SOAP & WATER. CONSULT A PHYSICIAN. INGESTION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN OR POISON CONTROL IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point:110F,43C

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG, US

E ANY CLASS B

APPROVED FIRE EXTINGUISHER.

Fire Fighting Procedures:WATER TO COOL CONTAINERS TO PREVENT PRESSURE BUILDUP/EXPLOSION. USE FULL PROTECTIVE EQUIP INCLUDING SCBA FOR PROTECTION. WATER INEFFECTIVE, IF USED, FOG NOZZLES

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FM ALL HEAT TYPES. CLOSED CNTNRS EXPLODE EXPOSED TO EXTREME HEAT. APPLICATION TO HOT SURFACE REQUIRES SPECIAL PRECAUTION

=====
===== Accidental Release Measures =====

=====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION & PROVIDE VENTILATION. USE SCOOP ON LARGE SPILLS & ABSORBENT MATERIAL ON SMALL SPILLS. AVOID BREATHING VAPOR & USE RESPIRATORY PROTECTION. FLUSH AREA WITH WATER. HOLD CLEAN-UP MATERIALS FOR PROPER DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions: STORE AWAY FROM ALL HEAT TYPES. WELL VENTED AREA. DON'T STORE ABOVE 100F. KEEP CLOSURE TIGHT & CONTAINER

UPRIGHT TO PREVENT LEAKAGE. DON'T GET IN EYES

Other Precautions: DON'T PUNCTURE, DRAG, OR SLIDE CONTAINERS. AVOID SKIN CONTACT. PREVENT REPEATED/PROLONGED BREATHING OF VAPOR/SPRAY MIST. DRUMS SHOULD BE GROUNDED WHEN POURING. RESTRICT FREEFALL OF LIQUID TO A FEW INCHES TO AVOID GENERATION STATIC CHARGE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: UNRESTRICTED VENTILATION: MECHANICAL FILTER TO REMOVE SOLID PARTICLES. RESTRICTED

VENTILATION: USE

CHEMICAL/MECHANICAL FILTER TO REMOVE BOTH VAPOR & SOLIDS. NO VENTILATION: USE AIR LINE TYPE RESPIRATOR.

Ventilation: DESIGNED/MAINTAINED TO PROVIDE VOLUME/PATTERN TO PREVENT CONCENTRATION IN EXCESS OF TLV. REMOVE DECOMPOSITION PRODUCTS *

Protective Gloves: USE NEOPRENE OR OTHER IMPERVIOUS TYPE

Eye Protection: USE GOGGLES OR SIDE SHIELD SPECTACLES

Other Protective Equipment: HAVE EYE WASH STATION AND SAFETY SHOWERS AVAILABLE. REMOVE & WASH CONTAMINATED CLOTHING BEFORE REUSE.

Work Hygienic Practices: WASH HANDS BEFORE EATING, SMOKING, DRINKING OR USING WASHROOM. SMOKE IN DESIGNATED AREAS ONLY.

Supplemental Safety and Health

* DURING WELDING OR BURNING OF THIS PRODUCT.

===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 323 TO 390F

Vapor Density: > AIR

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 44.27

===== Stability and Reactivity Data =====

Stability In

icator/Materials to Avoid: YES

OXIDIZING AGENTS

Stability Condition to Avoid: HEAT AND OPEN FLAME

Hazardous Decomposition Products: CARBON MONOXIDE AND OTHER ORGANIC MATERIALS MAY BE FORMED DURING COMBUSTION.

Conditions to Avoid Polymerization: HEAT AND OPEN FLAME

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSAL SHOULD BE DONE IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS. BEFORE ATTEMPTING CLEAN-UP, REFER TO HAZARD CAUTION INFORMATION IN OTHER SECTIONS OF THE SHEET.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.