

FISKE BROS REFINING CO -- LUBRIPLATE NO. 630-AA, 630-A, 630-2, 630-AA-W, 630-AAA --
9150-01-109-8726

=====
===== Product Identification =====

Product ID:LUBRIPLATE NO. 630-AA, 630-A, 630-2, 630-AA-W, 630-AAA

MSDS Date:05/01/1987

FSC:9150

NIIN:01-109-8726

MSDS Number: BSFSB

=== Responsible Party ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Info Phone Num:201-589-9150

Emergency Phone Num:201-589-9150

Preparer's Name:ROBERT J. SIBILIA

CAGE:73219

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

=====
===== Composition/Information on Ingredients =====

Ingred Name:NON HAZARDOUS INGREDIENT

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50

LC50 Mixture:TLV: 5 MG/M3 OIL MIST

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE IRRITATION. THIS PRODUCT HAS A LOW ORDER OF ACUTE ORAL TOXICITY, BUT MINUTE AMOUNTS ASPIRATED IN TO THE LUNGS DURING INGESTION MAY CAUSEMILD TO SEVERE PULMONARY INJURY.

Explanation of Carcinogenicity:NO
T CARCINOGENIC.

Effects of Overexposure:HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. AS A PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS AND FUMES SHOULD BE MINIMIZED.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE-FLUSH WITH CLEAR WATER FOR 15 MIN OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS, CONSULT PHYSICIAN. SKIN-REMOVE CONTAMINATED CLOTHING & WASH WITH SOAP & WATER. IF INJECTED BY HIGH PRESSURE UNDER SKIN, CONTACT PHYSICIAN IMMEDIATELY. INHALATION-IF OVERCOME BY VAPOR FROM HOT PRODUCT, REMOVE FROM EXPOSURE & CALL PHYSICIAN. INGESTION-CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:400F,204C

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE OR WATER SPRAY (FOG).

Fire Fighting Procedure

s:COOL EXPOSED CONTAINERS WITH WATER. USE AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED OR CONFINED SPACES.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND, OR WELD, AS THEY MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE, WASH REMAINDER WITH SUITABLE PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCT OUT OF SEW

ERS & WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED
OR MAY ENTER SEWERS & WATER COURSES.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN
USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG
OXIDANTS.

Other Precautions:REMOVE OIL-SOAKED CLOTHING AND LAUNDER BEFORE REUSE.
CLEANSE SKIN THOROUGHLY AFTER CONTACT.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED.

Ventilation:LOCAL EXHAUST-USE TO CAPTURE FUMES AND VAPORS.

Protective Gloves:USE OIL-RESISTANT GLOVES, IF NEEDED.

Eye Protection:IF CHANCE OF EYE CONTACT, WEAR GOGGLES.

Other Protective Equipment:USE OIL-RESISTANT APRON, IF NEEDED.

Work Hygienic Practices:LAUNDER CLOTHING BEFORE REUSE.

Supplemental Safety and Health

NONE

=====
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>550F,>288C

Melt/Freeze P

t:M.P/F.P Text:SEMI-SOLID

Vapor Pres:5

Spec Gravity:0.94-0.95

Evaporation Rate & Reference: