View NSN Online: https://aerobasegroup.com/nsn/8010-01-019-1776

## WELLBORN PAINT MFG CO -- TT-P-1952B YELLOW P/C 184601 -- 8010-01-019-1776

Product ID:TT-P-1952B YELLOW P/C 184601

MSDS Date:04/28/1988

FSC:8010

NIIN:01-019-1776

MSDS Number: BSGGF === Responsible Party ===

Company Name: WELLBORN PAINT MFG CO

Address:215 ROSSMOOR RD

City:ALBUQUERQUE

State:NM ZIP:87012 Country:US

Info Phone Num:505-877-5050 Emergency Phone Num:505-877-5050/505-843-2551

**CAGE:WELLB** 

=== Contractor Identification ===

Company Name: WELLBORN PAINT MFG CO

Address:215 ROSSMOOR RD

City:ALBUQUERQUE

State:NM ZIP:87012 Country:US

Phone:505-877-5050

**CAGE:WELLB** 

======= Composition/Information on Ingredients ========

Ingred Name:FORMALDEHYDE (SARA III) (VAPOR PRESSURE 17.00 MM HG @ 68F)

CAS:50-00-0

RTECS #:LP8925000 Fraction by Wt: TRACE

Other REC Limits: NONE SPECIFIED

ACGIH TLV:2 PPM EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name:L

EAD (AS PB) (SARA III)

CAS:7439-92-1

RTECS #:OF7525000 Fraction by Wt: 10.3%

Other REC Limits: NONE SPECIFIED

ACGIH TLV:0.15 MG/M3

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: CHROMIUM (AS CR) (SARA III)

CAS:7440-47-3

RTECS #:GB4200000 Fraction by Wt: 2.4%

Other REC Limits: NONE SPECIFIED

ACGIH TLV:0.05 MG/M3

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: SILICA-CRYSTALLINE

CAS:112945-52-5 RTECS #:VV7310000 Fraction by Wt: 8.6%

Other REC Limits: NONE SPECIFIED

ACGIH TLV:0.1 MG/M3

Ingred Name:C

ALCIUM CARBONATE (NUISANCE DUST)

CAS:1317-65-3

RTECS #:EV9580000 Fraction by Wt: 34.5%

Other REC Limits: NONE SPECIFIED

ACGIH TLV:10 MG/M3

Ingred Name: AMMONIUM

CAS:1336-21-6

RTECS #:BQ9625000 Fraction by Wt: TRACE

Other REC Limits: NONE SPECIFIED

ACGIH TLV:25 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:ETHYLENE GLYCOL (SARA III) (VAPOR PRESSURE .10 MM HG @

68F) (LEL 3.2) CAS:107-21-1

RTECS #:KW2975000 Fraction by Wt: 2.2%

Other REC Limits: NONE SPECIFIED

ACGIH TLV:100 PPM

EPA R

pt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: TEXANOL (VAPOR PRESSURE 1.00 MM HG @ 68F) (LEL 0.6)

CAS:25265-77-4 RTECS #:UF6000000 Fraction by Wt: 0.7%

Other REC Limits: NONE SPECIFIED

========== Hazards Identification ==============

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:INHALATION: VAPOR OR MIST MAY IRRITATE
EYES, NOSE, THROAT, MUCOUS MEMBRANES PRODUCING DIZZINESS,

HEADACHES, NAUSEA IN POORLY VENTILATED AREAS. SKIN:

PROLONGED/REPEATED: SKIN IRRITATION. EYE: IRRITATIO N.

Explanation of Carcinogenicity:FORMALDEHYDE AND CHROMIUM ARE SUSPECTED CARCINOGENS.

Effects of Overexposure: CHRONIC: INHALATION MAY HAVE AN EFFECT ON CENTRAL NERVOUS SYSTEM. MAY CAUSE DIZZINESS OR NARCOSIS. EXCESSIVE CHRONIC, LONG TERM EXPOSURE TO LEAD MAY CAUSE METALLIC TASTE IN MOUTH, LOSS OF APPETITE, IN DIGESTION, NAUSEA, SLEEPLESSNESS, WEAKNESS, STUPOR, COMA, ENCEPHALOPATHY.

First Aid:INHALATION: REMOVE TO FRESH AIR. CONSULT PHYSICIAN. SPLASH (EYES): FLUSH WITH WATER FOR 15 MIN. SPLASH (SKIN): WASH WITH SOAP AND WATER. REMOVE & WASH CLOTHING. INGESTION: IF VICTIM IS CONSCIOUS, GIVE 529 GLASSES OF WATER TO DRINK. DO NOT INDUCE VOMITING. CALL A PHYSICIAN.

Flash Point: NOT REGULATED

Extinguishing Media:NON COMBUSTIBLE

Fire Fighting Procedures:LATEX COA

TINGS WILL NOT BURN. THEY MAY SPATTER

IF TEMP EXCEEDS BOILING POINT. DRY FILMS ARE CAPABLE OF BURNING. Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE

FROM HEAT AND OPEN FLAME.

======= Accidental Release Measures ==========

Spill Release Procedures:DIKE AND CONTAIN SPILL WITH INERT MATERIAL & TRANSFER THE LIQUID TO CONTAINERS FOR RECOVERY AND DISPOSAL. KEEP SPILL OUT OF SE

id Polymerization:HIGH TEMPERAT	URES OR HIGH HUMIDITIES
---------------------------------	-------------------------

======= Disposal Considerations ===========

Waste Disposal Methods:INCINERATE OR LANDFILL AND CONTAMINATED DIKING MATERIAL, ACORDING TO LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrant

s this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.