View NSN Online: https://aerobasegroup.gr/nsn/6850-01-381-4427

Product ID:SKYSOL 200,FS 200

MSDS Date:10/13/1994

FSC:6850

NIIN:01-381-4427

MSDS Number: BSGMV === Responsible Party ===

Company Name: INLAND TECHNOLOGY INC

Address:401 EAST 27TH STREET

City:TACOMA State:WA ZIP:98421 Country:US

Info Phone Num:800-552-3100/206-383-1177/838-9889

Emergency Phone Num:800-2

55-3924 CAGE:0K209

=== Contractor Identification === Address:401 E 27TH STREET

Box:City:TACOMA

State:WA

ZIP:98421-1203 Country:US

Phone: 800-552-3100/253-383-1177

CAGE:0K209

======= Composition/Information on Ingredients ========

Ingred Name: MINERAL SPIRITS/C12-C13 PARAFFINIC HYDROCARBONS

CAS:64475-85-0 RTECS #:PY8240000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name: D-LIMONENE

CAS:5989-27-5


Other REC Limits: NONE RECOMMENDE

D
========= Hazards Identification ==========
LD50 LC50 Mixture:TLV; 5 MG/M3 AS OIL MIST Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY TRACT. ACUTE- MISTS MAY CAUSE RESPIRATORY TRACT IRRITATION. EYE CONTACT MAY CAUSE IRRITATION. LOW ORDER ORAL AND DERMAL TOXICITY. CHRONIC- PROLONGED OR REPEATED SK IN EXPOSURE CAN LEAD TO MILD IRRITATION, DEFATTING AND DERMATITIS. Explanation of Carcinogenicity:NONE Effects of Overexposure:EYES, SKIN, RESPIRATORY TRACT IRRITATION Medical Cond Aggravated by Exposure:SKIN CONTACT MAY AGGAVATE EXISTING DERMATITIS.
======================================
First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN.
SKIN:WASH WITH SOAP & WATER. ORAL:DO NOT INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE LUNGS. GET IMMEDIATE MEDICAL ATTENTION.
======================================
Flash Point Method:PMCC Flash Point:144F,62C Lower Limits:0.6% Upper Limits:7% Futio ruiching Medic:FOAM DRY CHEMICAL WATER CREAK OR CARRON PLOYIDE
Extinguishing Media:FOAM, DRY CHEMICAL, WATER SPRAY OR CARBON DIOXIDE. Fire Fighting Procedures:WEAR AIR-SUPPLIED BREATHING EQUIPMENT AND FU LL
PROTECTIVE GEAR FOR ENCLOSED OR CONFINED SPACES OR AS OTHERWISE NEEDED.
Unusual Fire/Explosion Hazard:NONE KNOWN. ===================================

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES OF IGNITION. VENTILATE AREA. CONTAIN SPILL. PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND, EARTH/USE PUMP (EXPLOSION PROOF). GROUND ALL HANDLING EQUIPMENTS. PREVENT LIQUID FROM

Neutralizing A

ENTERING SEWERS.



NRC/State Lic Num: NOT RELEVANT

Boiling Pt:B.P. Text:340F,171C

Vapor Pres:4 Spec Gravity:0.78

Evaporation Rate & Dr.; Reference: