

CIBA-GEIGY CORP REN PLASTICS DIV -- RP3265 HARDENER -- 8030-01-229-2659

=====  
Product Identification  
=====

Product ID:RP3265 HARDENER  
MSDS Date:05/31/1989  
FSC:8030  
NIIN:01-229-2659  
Kit Part:Y  
MSDS Number: BTRXP  
=== Responsible Party ===  
Company Name:CIBA-GEIGY CORP REN PLASTICS DIV  
Address:4917 DAWN AVE  
City:EAST LANSING  
State:MI  
ZIP:48823-5605  
Country:US  
Info Phone Num:517-351-5900 / FAX 517-351-9003  
Emergency Phone Num:517-351-5900  
Preparer's Name:PETER HENIGE  
CAGE:02684  
=== Contractor Identification ===  
Company Name:CIBA SPECIALTY CHEMICALS CORPORATION  
Address:4917 DAWN AVE  
Box:City:EAST LANSING  
State:MI  
ZIP:48823-5691  
Country:US  
Phone:517-351-5900  
CAGE:02684

=====  
Composition/Information on Ingredients  
=====

Ingred Name:M-XYLENE (M-DIMETHYLBENZENE) (SARA III)  
CAS:108-38-3  
RTECS #:ZE2275000  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM/150

STEL;9394  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:FIBROUS GLASS

CAS:65997-17-3

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 RDUST Z-3

ACGIH TLV:10 MG/M3(250F,>121C

Lower Limits:NOT GIVEN

Upper Limits:NOT GIVEN

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND  
FULL FACE-PIECE SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE  
PRODUCTION OF H

AZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SPILLAGE BY ABSORBEINT IN ABSORBENT  
MATERIAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:CAUSES SKIN AND EYE IRRITATION. AVOID  
CONTACT WITH EYES, SKIN AND CLOTHING. WASH THOROUGHLY AFTER  
HANDLING.

Other Precautions:NUISANCE DUST MAY BE GENERA  
TED WHEN SANDING OR SAWING  
CURED MATERIAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED ORGANIC VAPOR CARTRIDGE  
RESPIRATOR WHEN VAPOR/MIST EXPOSURE IS LIKELY.

Ventilation:GENERAL MECHANICAL AND LOCAL EXHAUST IN ACCORDANCE WITH  
ACGIH RECOMMENDATIONS.

Protective Gloves:IMPERMEABLE

Eye Protection:SPLASH-PROOF GOGGLES.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH WITH SOAP AND WA

TER AFTER HANDLING PRODUCT  
AND BEFORE EATING DRINKING OR SMOKING.

Supplemental Safety and Health  
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:400F,204C

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vapor Pres:6.7

Vapor Density:NOT GIVEN

Spec Gravity:1.5 - 1.7

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:SLIGHT

Appearance and Odor:TAN OPAQUE LIQUID, WITH PETROLEUM ODOR

Percent Volatiles by Volume:N

IL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS, ACIDS AND BASES

Stability Condition to Avoid:EXCESSIVE HEAT FOR PROLONGED PERIODS OF  
TIME.

Hazardous Decomposition Products:TOXIC MATERIALS SUCH AS CARBON  
DIOXIDE, CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING  
ENVIRONMENT. DISCARD ANY PRODUCT, RE  
SIDUE, DISPOSAL CONTAINER OR  
LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to v

erify and  
assume responsibility for the suitability of this information to their  
particular situation.