Product ID:H8-010 MSDS Date:12/06/1993

FSC:8010

NIIN:01-344-5102

MSDS Number: BTTDC === Responsible Party ===

Company Name: CRAWFORD LABS, INC

Address:4165 S EMERALD AVE

City:CHICAGO

State:IL ZIP:60609 Country:US

Info Phone Num:312-376-7132

Emergency Phone Num:312-376-7132 800-424-9300(CHEMTREC)

CAGE:5V430 === Contr

actor Identification ===

Company Name: CRAWFORD LABORATORIES, INC

Address:4165 SOUTH EMERALD AVENUE

Box:City:CHICAGO

State:IL ZIP:60609 Country:US

Phone:312-376-7132

CAGE:5V430

====== Composition/Information on Ingredients ========

Ingred Name: NAPHTHA, LIGHT AROMATIC

CAS:64742-95-6 Fraction by Wt: 5.3%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:100 PPM (NAPTHA) ACGIH TLV:400 PPM (NAPTHA)

Ingred Name:1,2,4-TRIMETHYLBENZENE (SARA III)

CAS:95-63-6

RTECS #:DC3325000

Fraction by Wt:

2.6%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:25 PPM

ACGIH TLV:25 PPM; 9394

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7 RTECS #:XR2275000 Fraction by Wt: 19%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9394

Ingred Name: SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7 RTECS #:VV7330000 Fraction by Wt: 4.4%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:SEE TABLE Z-3

ACGIH TLV:0.1 MG/M3 RDUST;9394

Ingred Name: VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4 RTECS #:Ol61800

00

Fraction by Wt: 10%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:300 PPM ACGIH TLV:300 PPM; 9394

Ingred Name: VOLATILE ORGANIC COMPOUNDS


RTECS #:9999999VO Fraction by Wt: 56.1%

Other REC Limits: NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:EYES:MAY CAUSE IRRITATION,POSSSIBLE

DAMAGE.SKIN:MAY CAUSE IRRITATIO



Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED PLACE.KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions:USE CAUTION WHEN USING WITH HIGH HEAT;VAPORS CAN FORM EXPLOSIVE MIXTURES WITH AI

R. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN ENCLOSED SPACES USE A NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS. Ventilation:LOCAL VENTILATION AT THE WORKSITE;MECHANICAL(GENERAL) VENTILATION TO MAINTAIN TLV/PEL. Protective Gloves: RUBBER Eye Protection: SAFETY GOGGLES. Other Protective Equipment: PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER. Work Hygienic Practices: USE REASON ABLE CARE IN HANDLING THIS PRODUCT.WASH HANDS AFTER USE AND BEFORE EATING. Supplemental Safety and Health NONE ======== Physical/Chemical Properties =========== HCC:F4 Boiling Pt:B.P. Text:308F-396F Vapor Density:>1 Spec Gravity: 1.65 Viscosity:87 KU Evaporation Rate & Reference: 0.13 (N-BUTYL ACETATE=1) Solubility in Water:SLIGHT Appearance and Odor:LIQUID;GRAY;SOLVENT ODOR. Percent Volatiles by Volume:34.2 ======== Stability and Reactivity Data ======= ====== Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS AND ALKALIES. Stability Condition to Avoid:HIGH HEAT, SOURCES OF IGNITION. Hazardous Decomposition Products: CARBON DIOXIDE, CARBON MONOXIDE

======== Disposal Considerations =============

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elemen

ts of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.