

HENRY W W CO -- #208 WET SURFACE PLASTIC ROOF CEMENT -- 8030-01-013-0627

=====  
Product Identification  
=====

Product ID:#208 WET SURFACE PLASTIC ROOF CEMENT

MSDS Date:09/21/1987

FSC:8030

NIIN:01-013-0627

MSDS Number: BTTJL

=== Responsible Party ===

Company Name:HENRY W W CO

Address:5608 SOTO ST

City:HUNTINGTON PARK

State:CA

ZIP:90255-2629

Country:US

Info Phone Num:213-583-4961 / FAX 213-582-8451

Em

ergency Phone Num:213-583-4961

Preparer's Name:GEORGE MARCINA

CAGE:11761

=== Contractor Identification ===

Company Name:HENRY W W CO

Box:3001

City:LANCASTER

State:PA

ZIP:17604

Country:US

Phone:717-396-2328;717-396-2935

CAGE:11761

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA, LIGHT ALIPHATIC (PETROLEUM) (THIS MATERIAL  
CONTAINS UP TO 5 VOL.% BENZENE AND 20 VOL.% N-HEXANE)

CAS:64742-89-8

Fraction by Wt: 15-20%

Other REC Limits:NONE RECOMMENDED

Ingr

ed Name:ASBESTOS (FRIABLE) (SARA III)  
CAS:1332-21-4  
RTECS #:CI6425000  
Fraction by Wt: 5-10%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:SEE 1910.1001  
ACGIH TLV:0.2 - 2 FIBER/CC; 94  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Hazards Acute and Chronic:NONE SPECIFIED BY MANUFACTURER.  
Explanation of Carcinogenicity:CONTAINS A [1332-21-4] WHICH IS LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.  
Effects of Overexposure:VAPORS ABOVE TLV MAY ASPHYXIATE. FRESH AIR USUALLY RESULT IN COMPLETE RECOVERY IF NORMAL RESPIRATION HAS NOT STOPPED.

=====  
===== First Aid Measures =====

First Aid:REMOVE PERSON TO FRESH AIR. ARTIFICIAL RESPIRATION IF NEEDED.  
WASH SKIN WITH SOAP AND WATER. WASH EYE WITH WATER FOR AT LEAST 15 MINUTES. DO NOT INDUCE VOMITING!! CALL PHYSICIAN!!

=====  
===== Fire Fighting Measures =====

Flash Point:120F,49C  
Lower Limits:1  
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL.  
Fire Fighting Procedures:NONE  
Unusual Fire/Explosion Hazard:NONE

=====  
===== Accidental Release Measures =====

Spill Release Procedures:EXTINGUISH ALL SOURCES OF IGNITION IN THE AREA. CLEAN UP SPILLS AS SOON AS POSSIBLE.

=====  
===== Handling and Storage =====

Handli

ng and Storage Precautions:STORE AWAY FROM HEAT AND SOURCES OF IGNITION.

Other Precautions:NONE.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY NEEDED.

Ventilation:USE SUPPLIED AIR SYSTEM IF VAPOR CONCENTRATION EXCEEDS TLV.

Protective Gloves:ONLY TO PREVENT SOILED & STICKY HANDS.

Eye Protection:NONE NORMALLY NEEDED.

Other Protective Equipment:NONE.

Work Hygienic Practices:CLEAN SKIN WITH SOAP AND WATERLESS CLEANER.

FLUSH EYES WITH WATER. DO NOT USE SOLVENTS.

Supplemental Safety and Health

NONE.

=====  
===== Physical/Chemical Properties =====

HCC:T7

Boiling Pt:B.P. Text:310-400F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume:30

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:SMOKE AND OXIDES OF CARBON.

=====  
===== Disposal Considerations =====

Waste Disposal Methods:ABSORB SPILLED MATERIAL WITH CLAY. DIATOMACEOUS EARTH OR OTHER NON-FLAMMABLE ABSORBENT MATERIAL.

=====  
Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United Stat

es of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.