## S.C. JOHNSON WAX -- FREEDOM SPEED STRIPPER -- 7930-01-380-8514

Product ID:FREEDOM SPEED STRIPPER MSDS Date:06/14/1994 FSC:7930 NIIN:01-380-8514 MSDS Number: BVGWL === Responsible Party === Company Name:S.C. JOHNSON WAX City:RACINE State:WI ZIP:53403-5011 Country:US Info Phone Num:414-631-2777 Emergency Phone Num:800-228-5635 EXT 092 Preparer's Name:TERRY A MEYERS

CAGE:GO050 === Contractor Identification === Company Name: S C JOHNSON & SON INC/PROF WAX DIV Address:1525 HOWE ST City:RACINE State:WI ZIP:53403 Country:US Phone:800-725-6737/414-886-1480 INTNL# CAGE:0U826 Company Name:S.C. JOHNSON WAX CORP. Address:1525 HOWE ST City:RACINE State:WI ZIP:53403-2237 Phone:414-631-2488 CAGE:GO050

Ingred Name:MONOETHANOLAMINE CAS:141-43-5 RTECS #:KJ5775000 Fraction by Wt: 6-10% Other REC Limits: NONE RECOMMENDED OSHA PEL:3 PPM; STEL 6 PPM ACGIH TLV:3 PPM; STEL 6 PPM

Ingred Name:SODIUM XYLENE SULFONATE CAS:1300-72-7 Fraction by Wt: 3-8% Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHYLENE GLYCOL PHENYL ETHER CAS:122-99-6 RTECS #:KM0350000 Fraction by Wt: 10-15% Other REC Limits:DOW TLV: 25 PPM

Ingred Name:BUTYL PROPASOL CAS:5131-66-8 RTECS #:UA7700000 Fraction by Wt: 1-6% Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM SILICATE CAS:1344-09-8 Fraction by Wt: 1-4% Other REC Limi ts:NONE RECOMMENDED

Ingred Name:POLYOXYETHYLENE PHENYL ETHER PHOSPHATE CAS:39464-70-5 Fraction by Wt: 1-3% Other REC Limits:NONE RECOMMENDED

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 60-70% Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC AS PACKAGED, MINUS H2O: BUTYL PROPASOL 0.26 LBS/GAL (THEORETICAL VOC) RTECS #:9999999VO Other REC Limits:NONE RECOMMENDED

Health Hazards Acute and Chronic:DIR

ECT CONTACT OF PRODUCT WITH EYES CAN CAUSE SEVERE IRRITATION AND DAMAGE. DIRECT CONTACT OF PRODUCT WITH SKIN CAN CAUSE IRRITATION. IF TAKEN INTERNALLY, PRODUCT MAY CAUSE CORROSIVE DAMAGE TO MOUTH, THROAT, OR STOMACH. Medical Cond Aggravated by Exposure:CHRONIC RESP DISORDERS (ASTHMA,CHRONIC BRONCHITITS,EMPHYXEMA,ETC) MAY BE ADVERSELY AFFECTED BY EXPOSURE TO ANY VAPOR OR AIRBORNE PARTICLE.PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO IRRITTN

First Aid:IF EYE CONTACT OCCURS, FLUSH EYES WITH WATER FOR 15-20 MIN, THEN GET PROMPT MEDICAL AID. IF PRODUCT IS SWALLOWED, DO NOT INDUCE VOMITING. SEEK MEDICAL AID AT ONCE. IF PRODUCT IS SWALLOWED, DRINK LARGE QUANTITIES OF WATER OR MILK AND SEEK MEDICAL AID.

Flash Point:NONE Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG Fire Fighting Procedures:NORMAL F IRE FIGHTING PROCEDURES MAY BE USED. COOL & USE CAUTION WHEN APPROACHING OR HANDLING FIRE EXPOSED CONTAINERS. Unusual Fire/Explosion Hazard:CORROSIVE MATERIAL. VAPOR MAY ACCUMULATE

IN CONFINED SPACES (E.G., PITS, SUMPS, SEWERS) AND INADEQUATELY VENTILATED AREAS.

Spill Release Procedures:DIKE LRG SPILLS. ABSORB WITH OIL-DRI OR SIMILAR INERT MATERIAL. SWEEP OR SCRAPE UP AND CONTAINERIZE. RINSE AFFECTED AR EA THOROUGHLY WITH WATER. WEAR/USE APPROPRIATE PROTECTIVE EQUIPMENT.

Handling and Storage Precautions:WARNING: CONTAINS ALKALI DETERGENT.
CAN CAUSE EYE DAMAGE. AVOID CONTACT WITH EYES,SKIN & CLOTHING.
HARMFUL IF SWALLOWED. KEEP OUT OF REACH OF CHILDREN
Other Precautions:WHEN HANDLING CONCENTRATE, WEAR EYE PROTECTION &
RUBBER GLOVES. PRODUCT RESIDUE MAY REMAIN ON/IN EMPTY CONTAINERS.
ALL PRECAUTIONS FOR HAND

## LING THE PRODUCT MUST BE USED IN HANDLING THE EMPTY CONTAINER S & RESIDUE. KEEP FROM FREEZING.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER NORMAL USE CONDITIONS.

Ventilation: GENERAL ROOM VENTILATIONS ADEQUATE.

Protective Gloves: RUBBER OR NEOPRENE

Eye Protection: UNDILUTED: CHEMICAL SPLASH PROOF GOGGLES

Other Protective Equipment: WHERE GROSS EYE/SKIN CONTACT MAY BE A

PROBLEM, WEAR/USE APPROPRIATE PROTECTIVE

EQUIPMENT.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE PRACTICES. LAUNDER CONTAMINATED CLOTHING/EQUIPMENT BEFORE REUSE.

Supplemental Safety and Health

Melt/Freeze Pt:M.P/F.P Text: