

C R C CHEMICALS U.S.A. -- 3-36 AEROSOL, PRODUCTS:3004,3005,3005T. -- 6850-00-050-0659

=====
Product Identification
=====

Product ID:3-36 AEROSOL, PRODUCTS:3004,3005,3005T.

MSDS Date:03/12/1993

FSC:6850

NIIN:00-050-0659

MSDS Number: BVGXW

=== Responsible Party ===

Company Name:C R C CHEMICALS U.S.A.

Address:885 LOUIS DRIVE

City:WARMINSTER

State:PA

ZIP:18974-2820

Country:US

Info Phone Num:215-674-4

300

Emergency Phone Num:215-674-4300

Preparer's Name:JON BROWN

CAGE:IO004

=== Contractor Identification ===

Company Name:C R C CHEMICALS

Address:885 LOUIS DR

City:WARMINSTER

State:PA

ZIP:18974

Country:US

Phone:215-674-4300

CAGE:IO004

Company Name:CRC INDUSTRIES, INC.

Address:885 LOUIS DRIVE

Box:City:WARMINSTER

State:PA

ZIP:18974-2820

Country:US

Phone:215-674-4300/800-424-9300

CAGE:10136

Company Name:NETEX INDUSTRIES(FORMER NORTHEAST TEXAS IND)

Address:1700 NORTH EDWARDS STREET

Box:City:MOUNT PLE

ASANT
State:TX
ZIP:75455
Country:US
Phone:903-577-0388
CAGE:0WAG0

=====
===== Composition/Information on Ingredients =====
=====

Ingred Name:PETROLEUM DISTILLATES
CAS:64742-47-8
RTECS #:OA5504000
Fraction by Wt: 60-70%
Other REC Limits:NONE RECOMMENDED

Ingred Name:INHIBITED PARAFFINIC OIL
Fraction by Wt: 25-30%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 OIL MIST
ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name:CARBON DIOXIDE
CAS:124-38-9
RTECS #:FF6400000
Fraction by Wt: 3-6%
Other REC L
imits:NONE RECOMMENDED
OSHA PEL:5000 PPM
ACGIH TLV:5000PPM/30000STEL;94

Ingred Name:FATTY ACIDS AND FATTY ACID ESTERS (ADDITIVES ARE
PRIMARILY,)
Fraction by Wt: N/GIVEN
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====
=====

LD50 LC50 Mixture:OSHA SHORT TERM EXPO LIMIT IS 10MG/M3.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:MAY CAUSE BURNIN

G/IRRITATION OF

EYES. SKIN CONTACT WILL CAUSE DRYNESS. INHAL OF MIST MAY CAUSE BREATHING PROBLEMS. VAPORS MAY CAUSE HEADACHES, NAUSEA, DIZZINESS. CHRONIC:PROLONGED EXPOSURE TO SK IN MAY CAUSE DEVELOPMENT OF DERMATITIS.

Explanation of Carcinogenicity:PER MSDS:NO CHEMICAL LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN BY NTP/IARC/OSHA.

Effects of Overexposure:EYES:IRRIT. SKIN:DRYNESS. INHAL:BREATHING PROBLEMS.

Medical Cond Aggravated by Exposure:N/A.

=====
First Aid Measures =====

First Aid:IF SYMPTOMS PERSIST CALL A PHYSICIAN. INHAL:REMOVE TO FRESH AIR. APPLY ART RESP IF NECESSARY. EYES:FLUSH W/LG AMTS OF WATER FOR 15MINS. SKIN:REMOVE CONTAMIN CLOTHING. WASH W/SOAP & WATER. INGEST:DO NO T INDUCE VOMITING. CALL PHYSICIAN.

=====
Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:175F,79C
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM.
Fire Fighting Procedures:
NONE SPECIFIED BY MFG.
Unusual Fire/Explosion Hazard:AEROSOL CONTAINERS MAY EXPLODE WHEN HEATED ABOVE 120F.

=====
Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. ABSORB SPILL W/AN INERT MATERIAL AND PLACE IN CLOSED CONTAINERS.
Neutralizing Agent:NONE SPECIFIED BY MFG.

=====
Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY AREA. AEROSOL CANS MAY EXPLODE IF HEATED ABOVE 120F. VAPORS ARE HEAVIER THAN AIR AN DWILL COLLECT IN LOW AREAS.
Other Precautions:THIS PRODUCT CONTAINS NO CHEMICALS THAT ARE SUBJECT TO RELEASE REPORTING UNDER SECTION 313 OF SARA TITLE III.

=====
Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED RESP FOR HIGH MIST CONCENTRATION.
Ventilation:ADEQUATE TO MAINTAIN ALL MIST BELOW PEL.
Protective Gloves:SOLVENT REISISTANT.
Eye Protection:SAFETY GLASSES.
Other Protective Equipment:N

OT NORMALLY REQUIRED WITH AEROSOL PRODUCT
USAGE.

Work Hygienic Practices:WASH HANDS AFTER HANDLING. LAUNDER CONTAMIN
CLOTHING PRIOR TO REUSE.

Supplemental Safety and Health

PHYSICAL DATA GIVEN IS W/O PROPELLENT.

===== Physical/Chemical Properties =====

HCC:V2

Boiling Pt:=193.3C, 380.F

Vapor Pres:0.23

Vapor Density:>AIR

Spec Gravity:0.617

Evaporation Rate & Reference:SLOW, 0.01 (TOLUENE=1)

Solubility in Water:NEGLIGIBLE.

Appearance and Odor:BLUE LIQUID, P

LEASANT ODOR.

Percent Volatiles by Volume:7070

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS.

Stability Condition to Avoid:NONE SPECIFIED BY MFG. HOWEVER AVOID TEMPS
ABOVE 120F, OPEN FLAMES, AND OTHER SOURCES OF IGNITION.

Hazardous Decomposition Products:CARBON DIOXIDE AND CARBON MONOXIDE
(FIRE).

===== Disposal Considerations =====

Waste Disposal Methods:ALL USED AND UNUS

ED PRODUCT SHOULD BE DISPOSED

OF IN CONFORMANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verif

y and
assume responsibility for the suitability of this information to their
particular situation.