View NSN Online: https://aerobasegroup.gr/nsn/6750-01-048-4560

Product ID:821 4637 FLEXICOLOR BLEACH III REPLENISHER, PART A MSDS Date:11/22/1996 FSC:6750 NIIN:01-048-4560 MSDS Number: BVQBK === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Phone Num:716-477-3194/MSDS 800-242-2424 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES Address:800 LEE RD Box:City:ROCHESTER State:NY ZIP:14650-3129 Country:US Phone:800-828-6203 CAGE:5K871

======= Composition/Informati

on on Ingredients ========

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 70-75% Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM ACETATE (SARA III) CAS:631-61-8 RTECS #:AF3675000 Fraction by Wt: 10-15% Other REC Limits:NONE RECOMMENDED EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:AMMONIUM BROMIDE CAS:12124-97-9 RTECS #:BO9170000 Fraction by Wt: 10-15% Other REC Limits:NONE RECOMMENDED

Ingred Name:ACETIC ACID (SARA III) CAS:64-19-7 RTECS #:AF1225000 Fraction by Wt: 5-10% Other REC Limits:NONE RECOMMENDED OSHA PEL:10 PPM ACGIH TLV:10 PPM/15 STEL; 9394 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

LD50 LC50 Mixture:ORAL LD50 (RAT): NOT GIVEN Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EXPECTED TO BE A LOW INHALATION HAZARD

FOR RECOMMENDED HANDLING. VAPOR MAY BE IRRITATING. CAUSE S EYE

IRRITATION. LOW SKIN CONTACT HAZARD FOR RECOMMENDED HANDLING. EXPECTED TO BE A LOW INGESTION HAZARD .

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:EYE IRRITATION, RESPIRATORY TRACT IRRITATION. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:INHALA

TION: IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: WASH OUT IMMEDIATELY WITH WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKIN: WASH WITH SOAP AND WATER . GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION: DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

Flash Point:NONFLAMMABLE Lower Limits:NOT GIVEN Upper Limits:NOT GIVEN Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. Unusual Fire/Explosion Hazard: FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSTION PRODUCTS. Spill Release Procedures: FLUSH TO SEWER IF ALLOWABLE WITH LARGE AMOUNTS OF WATER. OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER **INERT** MATERIAL, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE TO REMOVE RESIDUA L CONTAMINATION. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: AVOID CONTACT WITH EYES. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. USE WITH ADEQUATE VENTILATION. KEEP CONTAINER TIGHTLY CLOSED.
Other Precautions: KEEP AWAY FROM INCOMPATIBLE MATERIALS. KEEP FROM CONTACT WITH O
XIDIZING MATERIALS.

Respiratory Protection:NONE SHOULD BE NEEDED. A FULL-FACE POSITIVE-PRESSURE AIR-SUPPLIED RESPIRATOR MUST BE WORN IF HAZARDOUS DECOMPOSITION PRODUCTS ARE LIKELY TO BE RELEASED OR HAVE BEEN RELEASED.
Ventilation:GOOD GENERAL VENTILATION, TYPICALLY 10 AIR CHANGES PER HOUR, SHOULD BE USED. RATES SHOULD MATCH CONDITIONS.
Protective Gloves:IMPERVIOUS Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR

GOGGLES Other Protective Equipment: CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE. Work Hygienic Practices: WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. Supplemental Safety and Health REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. KEY1:C3. HCC:C3 Boiling Pt:B.P. Text:>212F,>100C Mel t/Freeze Pt:M.P/F.P Text:NOT GIVEN Vapor Pres:18 Vapor Density:0.6 Spec Gravity:1.09 pH:4.9 Evaporation Rate & amp; Reference: NOT GIVEN Solubility in Water:COMPLETE Appearance and Odor: COLORLESS LIQUID, STRONG VINEGAR ODOR Percent Volatiles by Volume:70-75% Stability Indicator/Materials to Avoid:YES BASES, SODIUM HYPOCHLORITE (BLEACH), STRONG OXIDIZING AGENTS. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardo us Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF NITROGEN, HYDROGEN BROMIDE, AMMONIA, CHLORAMINE.

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE OR LOCAL LAWS. MAY REQUIRE NEUTRALIZATION IF PH < 2.0 OR PH > 12.5. DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the co

mpiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.