

HENTZEN COATINGS, INC -- WHITE 17925 GLOSS EPOXY MIL-C-22750E 08525WEF, COMPONENT A
-- 8010-01-313-8700

===== Product Identification =====

Product ID:WHITE 17925 GLOSS EPOXY MIL-C-22750E 08525WEF, COMPONENT A

MSDS Date:06/16/1994

FSC:8010

NIIN:01-313-8700

Kit Part:Y

MSDS Number: BVVFS

=== Responsible Party ===

Company Name:HENTZEN COATINGS, INC

Address:6937 W MILL ROAD

City:MILWAUKEE

State:WI

ZIP

:53218

Country:US

Info Phone Num:414-353-4200

Emergency Phone Num:414-353-4200/800-424-9300 CHEMTREC

Preparer's Name:JANE FREEMAN

CAGE:09225

=== Contractor Identification ===

Company Name:HENTZEN COATINGS INC

Address:6937 WEST MILL ROAD

Box:18749

City:MILWAUKEE

State:WI

ZIP:53218

Country:US

Phone:414-353-4200

CAGE:09225

===== Composition/Information on Ingredients =====

Ingred Name:EPOXY RESIN

Fraction by Wt: 20-30%

Other REC Limits:NONE RECOMMENDED

Ingred Name:TITANIUM DIOX

IDE (PIGMENT)
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 50-75%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:ETHYL BENZENE (SOLVENT) (SARA III)
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: 1.428%
Other REC Limits:STEL: 125 PPM
OSHA PEL:100 PPM
ACGIH TLV:100 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENE (SOLVENT) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 9.813%
Other REC Limits:STEL: 150 PPM
OSHA PEL:100 PPM
ACGIH
TLV:100 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VOC: 2.658 LBS/GAL 318.508 GRAMS/LITER
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====
=====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN: IRRITATION, SENSITIZATION &
DERMATITIS. EYE: IRRITATION. INHALATION: NAUSEA & RESPIRATORY TRACT
IRRITATION. CHRONIC: REPORTS ASSOCIATE REPEATED & PROLONGED
OVEREXPOS

URE WITH PERMANENT BRAIN & NE RVOUS SYSTEM DAMAGE, LIVER & KIDNEY DAMAGE. PROLONGED/REPEATED SKIN CONTACT: DERMATITIS &/OR ALLERGIC SKIN REACTIONS.

Medical Cond Aggravated by Exposure:ASTHMA AND OTHER RESPIRATORY AILMENTS; CHEMICAL SENSITIZATION.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET. NOTIFY A PHYSICIAN. EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF RUNNING WATE
R FOR AT LEAST 15 MINUTES. TAKE TO A
PHYSICIAN F OR MEDICAL TREATMENT. SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN. INGESTION: IF SWALLOWED, CALL PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:79.0F,26.1C

Lower Limits:1.0

Upper Limits:6.7

Extinguishing Media:FOAM, DRY CHEMICAL, CO2

Fire Fighting Procedures:FULL PROTECT EQUI

P W/SCBA.WATER SPRAY MAY BE

INEFFECTIVE,USE TO COOL (FOG NOZZLES REFERED)CLOSED CONTAINER TO PREVENT PRESSURE BLDUP,AUTOIGNITION OR EXPLOSION.

Unusual Fire/Explosion Hazard:KEEP CNTNR CLSD.KEEP FROM HEAT,IGNIT

SOURCE.CLSD CNTNR MAY EXPLODE W/HEAT.DON'T APPLY TO HOT

SURFACE.NEVER USE WELD/CUT TORCH ON/NEAR DRUM (EVEN EMPTY)-EXPLODE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFAC

ES AND ELECTRICAL, STATIC OR FRICTIONAL SPARKS). AVOID

BREATHING VAPORS. VENTILATE AREA. CONTAIN AND REMOVE WITH INERT ABSORBENT AND NONSPARKING TOOLS .

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES. DO NOT STORE ABOVE 120F.

Other Precautions:STORE LRG QTY IN BLDGS IN COMPLIANCE W/OSHA 1910.106. KEEP A

WAY FROM SPARKS & OPEN FLAME. USE W/VENT & RESPRTRY EQUIP.
AVOID SKIN CONTACT. EMPTY CNTNRS RETAIN HZD RESIDUE/EXPLOSIVE
VAPOR. FOLLOW PRECA UTIONS UNTIL CNTNR CLEANED OR DESTROYED.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN OPEN AREA DURING SAND/GRINDING,USE NIOSH
MECHAN FILTER RESPRTR.IN RESTRICTD VENT,WEAR NIOSH CHEM/MECHAN
FILTER.IN CONFIND AREA,WEAR NIOSH AIR SUPPLD RESPRTR/HOOD.USE NIOSH
RSPRTR WHEN FLAME CUT/WEL DING
OR HAZING MAT'L COATED W/PRODUCT.

Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENT TO KEEP AIR
CONTAMINANT CONCENTRATION BELOW OSHA PEL & REMOVE DECOMP PROD

Protective Gloves:REQUIRED FOR PROLONGED/REPEATED CONTACT.

Eye Protection:SAFETY EYEWEAR W/SPLASH GUARD/SIDE SHLD

Other Protective Equipment:USE PROTECTIVE SKIN CREAM WHERE CONTACT IS
LIKELY. PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING.

Work Hygienic Practices:WASH CONTAMINATED CLOTHING BEFORE REUSE. WASH

HANDS BEFORE EATING OR SMOKING. SMOKE IN DESIGNATED AREAS ONLY.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:290 TO 275F

Decomp Temp:Decomp Text:400F,204C

Vapor Pres:9.00@ 68F

Vapor Density:> AIR

Spec Gravity:1.86

Viscosity:99 KU

Evaporation Rate & Reference:SLOWER THAN BUTYL ACETATE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:OPAQUE LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:34.51

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Hazardous Decomposition Products:MAY PRODUCE HAZARDOUS FUMES WHEN
HEATED TO DECOMPOSITION AS IN WELDING. FUMES MAY CONTAIN CARBON
MONOXIDE & DIOXIDE.

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND
FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.
INCINERATE IN AN APPROVE

D FACILITY. EPA HAZARDOUS WASTE CODE: D001,
IGNITABLE.

=====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek com
petent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.