

ROSE TALBERT PAINT CO. -- 378750600,V.V.LATEX (WHITE) -- 8010-00-598-5730

=====
Product Identification
=====

Product ID:378750600,V.V.LATEX (WHITE)

MSDS Date:03/05/1990

FSC:8010

NIIN:00-598-5730

MSDS Number: BVWYQ

=== Responsible Party ===

Company Name:ROSE TALBERT PAINT CO.

Address:901 FRINK STREET

City:CAYCE

State:SC

ZIP:29033

Country:US

Info Phone Num:803-796-0324

Emergency Phone Num:800-255-3

924

Preparer's Name:DAVID KELLY

CAGE:4792X

=== Contractor Identification ===

Company Name:JOHN J. MCMULLEN ASSOC.

Address:11771 ROCK LANDING DRIVE

Box:City:NEWPORT NEWS

State:VA

ZIP:23607

Country:US

Phone:804-873-6500

CAGE:3P768

Company Name:ROSE TALBERT PAINT CO.

Address:901 FRINK STREET

Box:City:CAYCE

State:SC

ZIP:29033

Country:US

Phone:800-255-3924

CAGE:4792X

=====
Composition/Information on Ingredients
=====

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fr

action by Wt: 14.32%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9394

Ingred Name:ETHYLENE GLYCOL (SARA III)
CAS:107-21-1
RTECS #:KW2975000
Fraction by Wt: 2.08%
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:C 50 PPM,VAPOR; 9394
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES:MAY CAUSE IRRITATION.SKIN:MAY CAUSE IRRITATION.INGEST:MAY CAUSE GI TRACT IRRITATION.INHAL:MAY CAUSE RESPIRATORY IRRITATION.CHRONIC:MAY DAMAGE,LIVER,KIDNEY AND CNS.
Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1% WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.
Effects of Overexposure:INHAL:HIGH CONCENTRATIONS MAY CAUSE FLUID IN THE LUNGS(PULMONARY EDEMA).
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING LIVER,KIDNEY OR CNS AILMENTS MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH LUKEWARM WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST:DO NOT INDUCE VOMITING. GET PROMPT QUALIFIED MEDICAL ATTENTION.IF CONSCIOUS,RINSE MOUTH;GIVE 6-8 OUNCES OF WATER.

===== Fire Fighting Measures

Flash Point Method:TCC

Flash Point:241F,116C

Lower Limits:3.2

Upper Limits:15.3

Extinguishing Media:CLASS B EXTINGUISHANTS--DRY CHEMICAL,CARBON DIOXIDE,FOAM.WATER MAY BE INEFFECTIVE AS AN EXTINGUISHANT.

Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER FOG.

Unusual Fire/Explosion Hazard:CONTAINERS MAY BURST AT ELEVATED TEMPERATURES.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION.USE PROPER RESPIRATORY AND PROTECTIVE EQUIPMENT.SHUT OFF LEAK IF SAFE. VENTILATE AREA.DIKE.SOAK UP WITH A NON-COMBUSTIBLE INERT ABSORBANT(CLAY,SAND);PLACE IN PROPER CONTAINER FOR DISPOSAL.AVOID DISCHARGE INTO SEWERS.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED PLACE.KEEP CONTAINER CLOSED WHEN NOT IN USE.AVOID SOURCES OF IGNITION.

Other Precautions:USE WITH ADEQUATE VENTILATION.EMPTY CONTAINERS ARE HAZARDOUS;DISPOSE OF PROPERLY.DO NOT INHALE VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN ENCLOSED SPACES USE A NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS AND PARTICULATES.

Ventilation:LOCAL VENTILATION AT THE WORKSITE;MECHANICAL(GENERAL) VENTILATION

LATION TO MAINTAIN TLV/PEL.

Protective Gloves:RUBBER,NEOPRENE,BUNA N,NITRILE.

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equipment:PROTECTIVE CLOTHING,AS NEEDED.PROVIDE A
LOCAL EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET
CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK
AREA.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:N1

Boili

ng Pt:B.P. Text:379-401F

Vapor Pres:0.1

Vapor Density:>1

Spec Gravity:1.345

Evaporation Rate & Reference: