

DAP INC -- DAP 1012 GLAZING -- 8030-00-823-7920

===== Product Identification =====

Product ID:DAP 1012 GLAZING

MSDS Date:01/07/1994

FSC:8030

NIIN:00-823-7920

MSDS Number: BVZHJ

=== Responsible Party ===

Company Name:DAP INC

Box:277

City:DAYTON

State:OH

ZIP:45401

Country:US

Info Phone Num:800-543-3840

Emergency Phone Num:800-535-5053; 800-543-3840

CAGE:90300

=== Contractor Identification ===

Company Name:DAP INC.

Box:277

City:DAYTON

State:OH

ZIP:45401-0277

Coun

try:US

Phone:513-253-7154/800-543-3840

CAGE:90300

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 1-5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:HYDROUS MAGNESIUM SILICATE

CAS:14807-96-6

RTECS #:WW2710000

Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC LESS WATER LESS EXEMPT SOLVENTS: 48 GRAMS/LITER. VOC

MATERIAL: 48 GRAMS/LITER

RTECS #:9999999VO

Other

REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE EFFECTS: MAY IRRITATE EYES,
SKIN, NOSE & RESPIRATORY TRACT. HARMFUL IF INHALED. HARMFUL OR
FATAL IF SWALLOWED. IF INGESTED, THIS PRODUCT MAY CAUSE VOMITING,
DIARRHEA, & DEPRESSED RESPIRATION. IN HALATION MAY AFFECT THE BRAIN
OR NERVOUS
SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA.
Effects of Overexposure:CHRONIC EFFECTS: REPORTS HAVE ASSOCIATED
PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE WITH PROLONGED AND REPEATED
OCCUPATIONAL OVEREXPOSURE TO SOLVENTS. PROLONGED OR REPEATED
CONTACT WITH SKIN MAY CAUSE IR RITATION.

===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER FOR 15
MINUTES. CONTACT A PHYSICIAN IMMEDIATELY. SKIN CONTACT: WASH WITH
SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. CONTACT A
PHYSICIAN IMMEDIATELY . INGESTION: DO NOT INDUCE VOMITING. CONTACT
A PHYSICIAN IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:194F,90C
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICALS
* (MINERAL SPIRITS)
Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT, INCLUDING
SELF-CONTAINED BREATHING APPARATUS, IS RECOMMENDED TO PROTECT FROM

COMBUSTION PRODUCTS. COOL EXPOSED CONTAINERS WITH WATER.
Unusual Fire/Explosion Hazard:CONTAINER MAY EXPLODE W/EXTREME
HEAT.ELIMINATE IGNITION SOURCES:HEAT,ELECTRICAL EQUIP,SPARKS,& OPEN
FLAMES.DON'T PUT IN CONTACT W/OXIDIZERS OR CAUSTIC MATERIALS

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP DRIED MATERIAL AND PLACE INTO
CONTAINERS.

===== Handling and Storage =====

Handling and Stora

ge Precautions:STORE AWAY FROM CAUSTICS AND
OXIDIZERS. KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINERS FROM
EXCESSIVE HEAT AND FREEZING.
Other Precautions:KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. DO
NOT STORE AT TEMPERATURES ABOVE 120F. INTENTIONAL MISUSE BY
DELIBERATELY CONCENTRATING AND INHALING VAPOR MAY BE HARMFUL OR
FATAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF 8 HOUR EXPOSURE LIMIT OR VALUE IS EXCEEDED
F
OR ANY COMPONENT, USE AN APPROVED NIOSH/OSHA RESPIRATOR. CONSULT
YOUR SAFETY EQUIPMENT SUPPLIER AND THE OSHA REGULATION, 29 CFR
1910.134 FOR RESPIRATOR R EQUIREMENTS.
Ventilation:PROVED SUFFICIENT MECHANICAL VENT (LOCAL OR GENERAL
EXHAUST) TO MAINTAIN EXPOSURE BELOW PEL/TLV. *
Protective Gloves:IMPERVIOUS GLOVES RECOMMENDED
Eye Protection:SAFETY GLASSES ARE RECOMMENDED
Other Protective Equipment:PROVIDE EYEWASH AND SOLVENT IMPERVIOUS APRON
IF BODY CONTACT WITH PRODUCT MAY OCCUR.
BARRIER CREAMS MAY BE USED.
Work Hygienic Practices:WASH CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health
* VAPORS ARE HEAVIER THAN AIR AND WILL COLLECT IN LOW AREAS. CHECK ALL
LOW AREAS (BASEMENTS, SUMPS, ETC) FOR VAPOR BEFORE ENTERING.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>325F,>163C
Vapor Pres:3.1 *
Vapor Density:> 1
Spec Gravity:2.2 (WATER=1)
Evaporation Rate & Reference: