

FARWEST PAINT MFG CO -- PURPLE QUICK DRY ENAMEL COLOR #17100 -- 8010-01-040-3761

=====
Product Identification
=====

Product ID: PURPLE QUICK DRY ENAMEL COLOR #17100

MSDS Date: 06/22/1993

FSC: 8010

NIIN: 01-040-3761

MSDS Number: BWFBL

=== Responsible Party ===

Company Name: FARWEST PAINT MFG CO

Address: 4522 S 133 ST

Box: 68726

City: TUKWILA

State: WA

ZIP: 98168-3251

Country: US

Info Phone Num: 206-244-8844

Em

ergency Phone Num: 206-941-1619

CAGE: 6F266

=== Contractor Identification ===

Company Name: FARWEST PAINT MANUFACTURING CO

Address: 4522 SOUTH 133RD ST

Box: City: TUKWILA

State: WA

ZIP: 98168

Country: US

Phone: 206-244-8844

CAGE: 6F266

=====
Composition/Information on Ingredients
=====

Ingred Name: (STODDARD SOLVENT) ALIPHATIC HYDROCARBON

CAS: 8052-41-3

RTECS #: WJ8925000

Fraction by Wt: 51%

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 500 PPM

ACGIH TLV: 100 PPM; 9394

Ingred Name: VOLITILE OR

ORGANIC CONTENT (PER MSDS:GRAMS/LITER LESS WATER)

RTECS #:9999999VC

Fraction by Wt: 470%

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN:IRRIT, SENSITIZATION, DEFATTING

UPON PROLONGED/REPEATED CONTACT. INHAL:EXCESSIVE VAP/SPRAY MIST
EXPOSURE CAN RESULT IN HEADACHE, DIZZ, NAU, LOSS OF CONSCIOUSNESS.

SOME REPORTS ASSOC REPEATED/PROLONGED OCCUPATIONAL OVEREXPOSURE TO
SOLVENTS/PERM BRAIN & NERVOUS SYS DAMAGE. EYES:IRRIT.

Explanation of Carcinogenicity:PER MSDS:THIS PROD CONTAINS NO KNOWN
CARCINOGENS IN REPORTABLE QUANTITIES AS DEFINED BY NTP, IARC, OSHA,
EPA.

Effects of Overexposure:SKIN/EYES:IRRITATION. SKIN SENSITIZATION,
DEFATTING. INHAL:HEADACHE, DIZZINESS, NAUSEA, LOSS OF
CONSCIOUSNESS. PERM BRAIN & NERVOUS SYS DAMAGE.

Medical Cond Aggravated by Exposure:N
ONE WHEN USED IN ACCORDANCE WITH
SAFE HANDLING INSTRUCTIONS.

=====
===== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR. IF RESP SYMPTOMS DEVELOP SEEK MED
ATTN @ONCE. SKIN:PROMPTLY WASH W/SOAP & WATER. REMOVE CONTAMINATED
CLOTHING. EYE:FLUSH W/LG QUANTITIES OF WATER FOR 15MINS. SEEK MED
ATTN. INGEST:DONOT INDUCE VOMIT. KEEP PERSON WAR/QUIET. GET MED
ATTN. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL
PNEUMONITIS WHICH CAN BE FATAL.

=====
===== Fire Fighting Measures =====

Flash Point:107F,42C

Lower Limits:0.7

Extinguishing Media:FOAM,CO2,DRY CHEM,WATER FOG OR ANY CLASS B EXT
AGENT.WATER MAY BE UNSUITABLE AS EXT MED BUT HELPFUL IN KEEPING
CONTN COOL

Fire Fighting Procedures:FIREFIGHTERS & OTHERS EXPOSED TO VAP/PROD OF
COMBUST SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS.EVACUATE
AREA OF UPORT PERSONNEL.WEAR PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:VAP MAY

FORM EXPLOSIVE MIXTURE IN AIR &
MAY BE IGN BY SPARKS/PILOT LIGHT/ETC.CLOSED CONTAINERS MAY RUPTURE
WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE
AREA. ABSORB SPILL W/ABSORBENT MATL SUCH AS
SAWDUST/VERMICULTIE/SAND. PLACE MATL INTO CLOSED CONTAINER. IF LG
DIKE AREA TO PREVENT FROM ENTERING WATER SYS/SEW ERS. WEAR PROT
EQPMT DURING CLEANUP.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID PROLONGED/REPEATED INHAL OF
HEATED VAP/SPRAY MIST.KEEP AWAY FROM HEAT/OPEN FLAME.MATL MAY CAUSE
SENSITIZATION.DO NOT GET IN EYE/SKIN/CLOTHING.

Other Precautions:DO NOT ALLOW CONTAMINATED CLOTHING TO CONTACT SKIN.
DO NOT WELD ON FULL/EMPTY CONTAINER. KEEP CONTAINER CLOSED WHEN NOT
IN USE & PROPERLY LABELED. GROUND HANDLING EQPMT TO PREVENT SPARKS.
EPA RCRA HOT LINE:800-424-9346/202-
382-3000.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:CANISTER-TYPE RESP MUST BE WORN TO PREVENT INHAL
OF VAP/SPRAY MIST WHEN TLV/PEL EXCEEDED.

Ventilation:GEN VENTI REQUIRED DURING NORMAL USE.LOC VENTI MAY BE
REQUIRED DURING CERTAIN OPERATIONS TO KEEP EXPO LEVEL BELOW LIMITS

Protective Gloves:CHEMICAL RESISTANT GLOVES.

Eye Protection:CHEMICAL GOGGLES OR FACE SHIELD.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN
C

ONTACT. EYEWASH STATION & SAFETY SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH CONTAMIN CLOTH BEF REUSE.WASH HANDS BEFORE
EATING/SMOKING.

Supplemental Safety and Health
WT/GAL:7.7LBS.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:307F,153C

Vapor Pres:2.6

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NIL

Appearance and Odor:PURPLE OILY LIQUID, MILD ODOR.

Percent Volatiles by Volume:65

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

CONTACT WITH STRONG OXIDANTS, ACIDS, BASES & EPOXY HARDENERS UNDER UNCONTROLLED CONDITIONS.

Stability Condition to Avoid: HEAT/SPARKS AND OPEN FLAMES. IF PRODUCT CONTAINS ALUMINUM MOISTURE IN CLOSED CONTAINERS WILL GENERATE HYDROGEN GAS.

Hazardous Decomposition Products: INCOMPLETE COMBUSTION CAN YIELD CARBON MONOXIDE AND TOXIC VAPORS.

===== Disposal Considerations =====

Waste Disposal Methods: IF DISCARDED, MATERIALS/CONTAINERS SHOULD BE TREATED AS HAZARDOUS WASTE BASED ON CHARACTERISTIC OF IGNITION AS DEFINED UNDER FEDERAL RCRA REGULATIONS (40CFR241). DISPOSAL OF MATERIALS/CONTAINERS REQUIRES COMPLIANCE WITH APPLICABLE LABEL/PACKAGING/RECORD KEEPING STANDARDS. DISPOSE IN ACCORDANCE WITH FEDERAL/LOCAL/STATE AGENCIES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.