View NSN Online: https://aerobasegroup.gr/nsn/8010-01-040-3760

ROSE TALBERT PAINT CO -- 16376 IMFLO RUST INHIBITIVE INDUSTRIAL ENAMEL HIGH GLOSS -- 8010-01-040-3760

Product ID:16376 IMFLO RUST INHIBITIVE INDUSTRIAL ENAMEL HIGH GLOSS MSDS Date:06/24/1993 FSC:8010 NIIN:01-040-3760 MSDS Number: BWGLB === Responsible Party === Company Name: ROSE TALBERT PAINT CO Address:901 FRINK ST City:CAYCE State:SC ZIP:29033 Country:US Info P hone Num:803-796-0324 Emergency Phone Num:800-796-0324 Preparer's Name: DAVID KELLY CAGE:0CUY5 === Contractor Identification === Company Name: ROSE TALBERT PAINT CO Address:901 FRINK ST Box:City:CAYCE State:SC ZIP:29033 Country:US Phone:803-796-0324 CAGE:0CUY5

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 Fraction by Wt: 21.09% Other REC Limits:NONE RECOMMENDED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9 394

Ingred Name:STODDARD SOLVENT CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 42.5% Other REC Limits:NONE RECOMMENDED OSHA PEL:500 PPM ACGIH TLV:100 PPM; 9394

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES:MAY CAUSE IRRITATION.SKIN:MAY
CAUSE IRRITATION AND DEFATTING.INGEST:MAY CAUSE GI TRACT
IRRITATION.INHAL:MAY CAU
SE RESPIRATORY IRRITATION AND CNS
DEPRESSION.CHRONIC:SOLVENTS MAY CAUSE PERMANENT BR AIN AND CNS
DAMAGE.
Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1%
WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.
Effects of
Overexposure:INHAL:DIZZINESS,HEADACHE,EUPHORIA.SKIN:DERMATITIS,CRAC
KING.

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING BRAIN AND CNS AILMENTS MAY BE AT INCREASED RISK FROM EXPOSURE.

======= First Aid M

easures =======================

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH WARM WATER.EYES:FLUSH WITH LUKEWARM WATER FOR 15 MINUTES.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST:DO NOT INDUCE VOMI TING.GET PROMPT QUALIFIED MEDICAL ATTENTION.IF CONSCIOUS,RINSE MOUTH WITH WATER;GIVE 6-8 OUNCES OF WATER TO DILUTE STOMACH CONTENTS.

Flash Point Method:TCC Flash Po

<ul> <li>int:107F,42C</li> <li>Lower Limits:0.7</li> <li>Upper Limits:6</li> <li>Extinguishing Media:CLASS B EXTINGUISHERDRY CHEMICAL,CARBON DIOXIDE,FOAM.</li> <li>Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER FOG.</li> <li>Unusual Fire/Explosion Hazard:A DIRECT WATER STREAM MAY SPREAD BURNING</li> </ul>
LIQUID.CONTAINERS MAY BURST FROM HEAT OF FIRE.DECOMPOSITION PRODUCT MAY BE TOXIC.
======================================
Spill Release Procedures: ELIMINATE SOURCES OF IGNITION.USE PROPER RESPIRATORY AND PROTECTIVE EQUIPMENT.VENTILATE AREA.SOAK UP WITH A NON-COMBUSTIBLE INERT ABSORBANT(CLAY,SAND);PLACE IN PROPER CONTAINER FOR DISPOSAL.SPILL ON W ATER;CALL NATL RESPONSE CTR,800-424-8802.
Neutralizing Agent:NOT APPLICABLE.
======================================
<ul> <li>Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED PLACE.KEEP CONTAINER CLOSED WHEN</li> <li>NOT IN USE.KEEP AWAY FROM HEAT,SPARKS,FLAMES AND INCOMPATIBLE MATERIALS.</li> <li>Other Precautions:EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUE;DISPOSE OF PROPERLY.AVOID BREATHING VAPORS;AVOID SKIN AND EYE CONTACT.</li> </ul>
======================================
Respiratory Protection:WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN ENCLOSED SPACES USE A NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/PARTICULATES. Ventilation:LOCAL VENTILATION AT THE WORKSITE ;MECHANICAL(GENERAL) VENTILATION TO MAINTAIN TLV/PEL.
Protective Gloves:NBR,BUNA N, NITRILE,NEOPRENE. Eye Protection:CHEMICAL SPLASH GOGGLES
Other Protective Equipment: PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER.
Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK AREA.
Supplemental Safety and Health THIS ITEM IS LEAD AND CHROMATE FREE.
======================================

HCC:F4 Boiling Pt:B.P. Text:318-383F Vapor Pres:2.6 Vapor Density:>1 Spec Gravity:1.105 Evaporation Rate & amp; Reference: