View NSN Online: https://aerobasegroup.gr/nsn/4820-01-015-9246

MARSTON BENTLEY -- HYLOMAR PL32 HEAVY GRADE -- 8030-01-015-9246

Product ID: HYLOMAR PL32 HEAVY GRADE MSDS Date:08/13/1992 FSC:8030 NIIN:01-015-9246 MSDS Number: BXNYL === Responsible Party === **Company Name: MARSTON BENTLEY** Address:223 N BROCKMAN ST City:PASADENA State:TX ZIP:77506-5000 Country:US Info Phone Num:800-424-9300 Emergency Phone Num:800-424-9300 Preparer 's Name:OLIVER W BARR CAGE:DO449 === Contractor Identification === Company Name: MARSTON BENTLEY **Box:UNKNOW** CAGE:MARBT Company Name: MARSTON BENTLEY INC. Address:1820 STAR BATT DRIVE EAST City:ROCHESTER State:MI ZIP:48063 Phone: (313) 852-6730 CAGE:DO449

Ingred Name:DICHLOROMETHANE (METHYLENE CHLORIDE) (SUSP HUMAN CARC BY ACGIH, SUSP ANIM CARC BY IARC; NTP - IARC GROUP 2B) *95-2* CAS:75-09-2 RTECS #:PA8050000 Fraction by Wt: 28.2% ACGIH TLV:174 MG/CUM (A2) EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE; DIMETHYL KETONE; 2-PROPANONE CAS:67-64-1 RTECS #:AL3150000 Fraction by Wt: 1.8% OSHA PEL:2400 MG/CUM ACGIH TLV:750 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:POLYESTER POLYOL Fraction by Wt: 65-75%

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO Health Hazards Acute and Chronic:EYES/SKIN: IRRITATION. (SOLVENTS ONLY). INHALATION/INGESTION: NARCOTIC & TOXIC. Explanation of Carcinogenicity:SEE INGREDIENTS. Effects of Overexposure:IRRITATION, HEADACHE, DIZZINESS, NARCOSIS, COMA Medical Cond Aggravated by Exposure:PERSONS W/ANGINA/HEART DISEASE/THOSE WHO ARE HEAVY DRINKERS/SMOKERS.

First Aid:EYES/SKIN: FLUSH W/WATER FOR 15 MINS. INGESTION: DON'T GIVE LIQUIDS IF UNCO NSCIOUS/VERY DROWSY. DON'T INDUCE VOMITING. INHALATION: REMOVE TO FRESH AIR. TREAT SYMPTOMS. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Flash Point Method:COC Flash Point:165F Lower Limits:13 Upper Limits:22 Extinguishing Media:FOAM, DRY CHEMICAL, CO2 Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:PHOSGENE & CHLOROHYDROCARBONS WILL BE PRODUCED AT HIGH TEMP & IN PRESENCE OF OPEN FLAMES.

Spill Release Procedures: ALLOW SOLVENT TO EVAPORATE IN A FORCED DRAUGHT, SCRAPE UP PUTTY & PLACE IN SUITABLE CONTAINER FOR DISPOSAL. AVOID BREATHING FUMES/SPRAY MIST. VENTILATE CONFINED SPACES. KEEP FROM WATER COURSES & SEWER S.

Handling and Storage Precautions:STORE BETWEEN 41-95F. Other Precautions:KEEP AWAY FROM FOODSTUFFS. DON'T EAT, DRINK/SMOKE WHILE USIN

G.

Respiratory Protection: A NIOSH APPROVED/EQUIVALENT RESPIRATOR IS RECOMMENDED. Ventilation: GENERAL VENTILATION Protective Gloves: IMPERMEABLE Eye Protection: CHEMICAL SPLASH GOGGLES Other Protective Equipment: SAFETY SHOWER, EYE BATH, WASHING FACILITIES. Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH THOROUGHLY AFTER HANDLING. Supplemental Safety and Health FLASH POINT IS CONSIDERED FLAM MABLE WHEN ACETONE IS PRESENT IN THE COMPOUND. PHONE # IS DISCONNECTED. USE CHEMTREC AT 800-424-9300.

Boiling Pt:B.P. Text:104F Vapor Pres:400 Vapor Density:2.9 Spec Gravity:1.3 Evaporation Rate & amp; Reference:(BU AC =1): 25 (SOLVENT) Solubility in Water: