View NSN Online: https://aerobasegroup.com/nsn/6850-00-160-8480

Product ID:D-70 DEVELOPER MSDS Date:01/01/1997 FSC:6850 NIIN:00-160-8480 MSDS Number: BXTGV === Responsible Party === Company Name: MET-L-CHEK COMPANY Address:1639 EUCLID STREET **City:SANTA MONICA** State:CA ZIP:90404 Country:US Info Phone Num:310-450-1111 Emergency Phone Num:310-450-1111 Chemtrec Ind/Phone:(8 00)424-9300 CAGE:98733 === Contractor Identification === Company Name:MET-L-CHEK COMPANY Address:1639 EUCLID ST Box:00000 **City:SANTA MONICA** State:CA ZIP:90404 Country:US Phone:310-450-1111/FAX 310452-4046 Contract Num:SP0450-99-M-NH74 CAGE:98733

Ingred Name:ISOPROPYL ALCOHOL (SARA 313) CAS:67-63-0 RTECS #:NT8050000 Other REC Limits:NONE RECOMMENDED OSHA PEL:400 PPM ACGIH TLV:400 PPM/500STEL;9596

Ingred Name:BUTANE CAS:106-97 -8 RTECS #:EJ4200000 ACGIH TLV:1900 MG/M3;800 PPM

Ingred Name:PROPANE CAS:74-98-6 RTECS #:TX2275000 OSHA PEL:1800 MG/M3;1000 PPM

Ingred Name:ISOBUTANE CAS:75-28-5 RTECS #:TI4300000

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, CNS, RESPIRATORY & GI TRACTS. ACUTE- MAY CAUSE EYE IRRITATION.
PROLONGED
/REPEATED SKIN CONTACT CAN CAUSE DRYNESS & MILD
IRRITATION. EXCESSIVE INHALATION CAN CAUSE IRRITATION, CNS DEPRESSION. LOW ORDER OF ORAL ACUTETOXICITY. CHRONIC- UNKNOWN.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, HEADACHE, DIZZINESS, NAUSEA, VOMITING, DROWSINESS, REDNESS, TEARNING, BLURRED VISION, SKIN

DRYNESS Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION MAY BE MOR

E SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:MOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:WASH WITH PLENTY OF SOAP & WATE R. ORAL:IF CONSCIOUS, INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.

Flash Point

Method:TCC Flash Point:=11.7C, 53.F FLAMMABL AEROSOL Lower Limits:2% Upper Limits:12% Extinguishing Media:USE WATER FOG, CARBON DIOXIDE (CO2), ALCOHOL FOAM OR DRY CHEMICAL. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS. Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL FIRE-EXPOSED CONTAINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard:SPRAY CANS UNDER PRESSURE. EXTREMELY FLAMMABLE. EXPLOSION HAZARD EXISTS WHE N SPRAY CANS HEATED. DO NOT ENTER SPRAY CAN STORAGE AREA IF FIRE PRESENT.
======================================
Spill Release Procedures:LEAKING CONTAINERS SHOULD BE PLACED OUTDOORS, IN AN OPEN CONTAINER, AWAY FROM SOURCES OF IGNITION. ALLOW PRESSURE TO DISSIPATE. VENTILATE AREA. ABSORB LIQUID WITH NON-FLAMMABLE ABSORBENT MATERIALS AND PLACE IN CONTAINER FOR DISPOSAL. Neutralizing Agent:NOT RELEVANT
======================================
 Handling and Storage Precautions:STORE SPRAY CANS IN COOL, WELL VENTILATED AREAS AWAY FROM SOURCES OF IGNITION AND STRONG OXIDIZING AGENTS. DO NOT STORE ABOVE 120F. Other Precautions:"EMPTY" CONTAINERS RETAIN RESIDUE AND MAY BE DANGEROUS. FOLLOW ALL LABEL INSTRUCTIONS. AVOID REPEATED/PROLONGED SKIN CONTACT. KEEP OUT OF REACH OF CHILDREN. DO NOT BREATHE VAPORS.
======================================
 Respiratory Protection: IF EXP OSURE EXCEEDS LIMITS, USE NIOSH-APPROVED RESPIRATOR Ventilation: MECHANICAL (GENERAL AND/OR LOCAL EXHAUST: EXPLOSION-PROOF TO MAINTAIN TLV. Protective Gloves: CHEMICAL RESISTANT Eye Protection: GOGGLES IF THERE IS LIKLIHOOD OF CONTACT. Other Protective Equipment: EYE WASH FOUNTAINS & SAFETY SHOWERS SHOULD BE AVAILABLE. Work Hygienic Practices: OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH THOROUGHLY BEFORE EATING, DRINKING/SMOKING. Supplemental Safety a

nd Health FORMULA CHANGED. FOR PREVIOUS FORMULATIONS SEE PNI A, B AND C, SAME NSN.

HCC:V3 NRC/State Lic Num:NOT RELEVANT Boiling Pt:=82.2C, 180.F Melt/Freeze Pt:=-88.3C, -127.F Vapor Pres:33@68F Vapor Density:2.1 Spec Gravity:0.8 LIQUID Evaporation Rate & amp; Reference:1.4 (N-BUTYL ACETATE=1) Solubility in Water:LIQUID IS SOLUBLE Appearance and Odor:WHITE, MILKY SUSPENSION - MILD ODOR

Stability Indicator/Materials to Avoid:YES
DO NOT STORE OR HANDLE IN ALUMINUM EQUIPMENT AT TEMPERATURES ABOVE 120F
Stability Condition to Avoid:HEAT SPARKS, FLAMES,CONTACT WITH STRONG
OXIDIZING AGENTS
Hazardous Decomposition Products:CARBON MONOXIDE, UNIDENTIFIED ORGANIC
COMPOUNDS
Conditions to Avoid Polymerization:AVOID HEAT SPARKS, FLAMES & CONTACT
WITH STRONG OXIDIZING AGENTS

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT PUNCTURE, INCINERATE SPRAY CANS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.